

CHASSIS

MODEL WBOC4 - 18/20 - 16 TON



The H&S WBOC4-18/20 chassis w/385 x 22.5 truck tires is manufactured for use under the 18' rear unload, 18' front and rear unload and 20' rear unload industrial forage boxes.



H&S trailer chassis feature heavy gusseted box style framing for superior strength and oscillating tandem axles for flexibility.

MODEL WBOC4 - 22/24 - 22 TON

Featuring 10 Bolt hubs and 425 x 22.5 truck tires, the H&S WBOC4-22/24 chassis is ideal for the 20', 21' & 22' front and rear unload industrial forage boxes and 20', 22' & 24' Wide Body forage boxes.



MODEL WBOC4 - 24/26



Shown with optional 600/50x22.5 truck tire.

Model WBOC4-24/26 is adjustable to weight balance 22', 24' & 26' forage boxes.



Greasable Swivel Hitch comes standard on WBOC4 - 24/26.



H&S WBOC4 - 24/26 Chassis can accommodate 22', 24' & 26' front and rear unload industrial forage boxes and 22', 24' & 26' Wide Body forage boxes.

SPECIFICATIONS

MODEL	CAPACITY	WEIGHT W/TIRES	TREAD WIDTH	SPINDLES	HUBS	BOLSTER	C-REACH	WHEEL BASE	STANDARD WHEEL	WHEEL OPTIONS	BRAKES	BACK HITCH	TELESCOPING POLE
SINGLE AXLE													
406	6 TON	732# w/9.5L	74"	1 3/4"	6 BOLT	3" x 6"	10 GAUGE	119"	15 x 6	N/A	N/A	N/A	77"
408	8 TON	902# w/11L	74"	1 3/4"	6 BOLT	3" x 6"	8 GAUGE	TO 159" in	15 x 8	N/A	N/A	YES	FIXED, EXTENDS TO 89"
410	10 TON	1126# w/12.5L	80"	2"	6 BOLT	3" x 8"	7 GAUGE	10" increments	15 x 10	N/A	N/A	YES	EXTENDS TO 89"
412	12 TON	1190# w/12.5L	80"	2 1/4"	8 BOLT	3" x 8"	7 GAUGE	119"	15 x 10	16.1 x 11 22.5 x 8 22.5 x 13.5	OPT. HYD. SURGE	YES	89"
415	15 TON	1520# w/16.5L	80"	2 3/4"	8 BOLT	4" x 8"	" WELDMENT	16.1 x 14	22.5 x 8 22.5 x 13.5	OPT. HYD. SURGE	YES		
416	16 TON	1890# w/16.5L	80"	2 3/4"	8 BOLT	4" x 8" W/ROCKING BOLSTER	" WELDMENT	119" TO 179" in	16.1 x 14	22.5 x 8 22.5 x 13.5	OPT. HYD. SURGE	YES	FIXED
417	17 TON	2100# w/19L	87"	3"	8 BOLT	4" x 8"	" WELDMENT	10" increments	16.1 x 16	16.1 x 14 22.5 x 8 22.5 x 13.5	OPT. HYD. SURGE	YES	AT 89"
420	20 TON	3440# w/TRUCK TIRES	86"	3"	10 BOLT	4" x 10"	" WELDMENT	16.1 x 18 or 22.5 x 13.1	N/A	OPT. HYD. SURGE	YES		
TANDEM AXLE													
612	12 TON	1524# w/12.5L	80"	2"	6 BOLT	3" x 8"	7 GAUGE	119" TO 159" in 10" increments	15 x 10	N/A	N/A	N/A	77" FIXED, EXTENDS TO 89"
614	14 TON	1620# w/12.5L	80"	2 1/4"	8 BOLT	4" x 8"	7 GAUGE	15 x 10	16.1 x 11	OPT. HYD. SURGE	N/A		
617	17 TON	2480# w/16.5L	80"	2 3/4"	8 BOLT	4" x 8"	3/8" WELDMENT	119" TO 179" in 10" increments	16.1 x 14	N/A	OPT. HYD. SURGE	N/A	FIXED AT 95.5"
622	22 TON	3580# w/21.5L	87"	3"	8 BOLT	4" x 8"	3/8" WELDMENT	16.1 x 18 or 22.5 x 13.5	N/A	OPT. HYD. SURGE	N/A		FIXED AT 89"
MODEL	CAPACITY	WEIGHT W/TIRES	TIRE SIZE	TREAD WIDTH	SPINDLES	HUBS	STANDARD WHEEL	TIRES	BACK HITCH	JACK			
CHASSIS													
WBOC4-18/20	32,000#	N/A	385 X 22.5 TRUCK TIRES	90"	3" STRESS PROOF	8 BOLT	22.5 X 13.5	OPTIONAL ELECTRICALLY ACTIVATED OVER HYDRAULIC BRAKE SYSTEM W/CAB CONTROL BOX	N/A	N/A	STANDARD		
WBOC4-22/24	44,000#	N/A	425 X 22.5 TRUCK TIRES	90"	3" STRESS PROOF	10 BOLT	22.5 X 13		N/A	N/A	STANDARD		
WBOC4-24/26	48,000#	7150#	425 X 22.5 TRUCK TIRES 600/50X22.5 FLOATATION TIRES	100"	3" STRESS PROOF	10 BOLT - 12,000#	22.5 X 13		N/A	N/A	STANDARD		

Warranty: See operators manual for warranty details and limitations. H&S reserves the right to change its products or the description at any time without notice or obligation.



NEED A QR CODE READER? DOWNLOAD THE APP TO YOUR SMARTPHONE!




Buy the BEST BUY



Models and specifications are to change without prior notice.

4/13 4M



RUNNING GEARS AND CHASSIS



PLUS...
3 MODELS OF
CHASSIS NOW
AVAILABLE!

12 MODELS OF
RUNNING GEARS
AVAILABLE!

H & S MANUFACTURING CO. INC.

2608 S. Hume Avenue
P.O. Box 768 • Telephone (715) 387-3414
FAX (715) 384-5463 • Website www.hsmfgco.com
MARSHFIELD, WI 54449




H & S WAREHOUSE 10145 Lakeshore Road
P.O. Box 1260 • Telephone (716) 736-7595
FAX (716) 736-7596 • Website www.hsmfgco.com
RIPLEY, NY 14775

ASAE
Stress Tested


SUPERIOR Construction and Performance on ALL MODELS!



MODEL 410 - 10 TON



Full Contact Turn Stops distributes the pressure exerted in tight dragging turns along the bolster face – this reduces the possibility of bunk damage or collapse.



The H&S models **416**, **417**, **420** and **622** utilize a T (T) style spindle assembly, and use truck type steering because of increased torque loads that result from the use of wide flotation or truck tires.


**All H&S 4 wheel models
(except the 406)
have a rear hitch.**



DEL 415 - 15 TON




MODEL 612 - 12 TON



C SECTION REACH FEATURES

C SECTION BEACH FEATURES

- No rotating collars or moving parts to wear out.
- The Square C-Section Reach provides both strength and flexibility.
- Torsional flexibility without rotating collars.




**Stake pocket wear plates
are standard on ALL MODELS!**



MODEL 420 - 20 TON



MODEL 617 - 17 TON



The model **617** rear incorporates a boxed type bolster support. All H&S running gears utilize heavy duty full depth bolster support **braces (hounds)**.

Maximum Flexibility • Straight Trailing • Rugged Dependability • Wide Track Stability • Over-Built Construction