

H&S

MANURE SPREADERS



GROUND DRIVE MODELS

MODEL 25 GROUND DRIVE 25 Bu.



The beater on Model 25 is 20" in diameter and with 8 paddles provides an even spread of material. Shown with optional fine spread pan.

MODEL 50 GROUND DRIVE 50 Bu.



The Model 50 uses a heavy duty 8 paddle beater assembly.



To engage the beater and main apron on Models 50 and 80, lower the control lever.

MODEL 80 GROUND DRIVE 80 Bu.



Shown with safety shields removed.

The Beater is chain driven. The main apron is driven by a simple adjustable ratchet drive mechanism.

P.T.O. MODELS

Shown with optional rear trip pan.

The heavy duty 10 paddle beater assembly assures aggressive shredding action with even wide spread patterns.



The spreader box sides are constructed of corrosion resistant galvanized steel.

Beater engage/disengage lever.



Manure Spreader Models 25 through Models 175 the main apron tightener bolts are located outside on the lower right and left corners of the main frame.



The Model 125 uses heavy duty worm gear drive for a positive drive and long life.



The large diameter beater on Models 125 and 175 provides an even spread pattern.



Shifting on the 175 is done in the H&S two spread gear box plus beater shutoff.

PTO 80 Bu. MODEL 80



PTO 125 Bu. MODEL 125



PTO 175 Bu. MODEL 175



STANDARD FEATURES ON ALL SPREADERS

- Spreader box is constructed of corrosion resistant galvanized steel.
- All spreaders utilize a bonded poly floor to reduce main apron drag and power needed to move the load.

MANURE SPREADER Specifications

| MODEL NUMBER | 25 GROUND DRIVE | 50 GROUND DRIVE | 80 GROUND DRIVE | 80 PTO | 125 PTO | 175 PTO |
|---------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| CAPACITY - HEAPED (OLD RATING) BU. | 25 BU. | 50 BU. | 80 BU. | 80 BU. | 125 BU. | 175 BU. |
| CAPACITY - CU. FT. STRUCK LEVEL | 13.6 | 35 | 47 | 53 | 75 | 105 |
| TOP OF FLARE WIDTH | 28-1/2" (73 cm) | 36" (91 cm) | 48" (122 cm) | 48" (122 cm) | 54" (137 cm) | 63-1/2" (161 cm) |
| INSIDE WIDTH | 22" (56 cm) | 36" (91 cm) | 48" (122 cm) | 48" (122 cm) | 48" (122 cm) | 54" (137 cm) |
| INSIDE LENGTH | 6' (183 cm) | 8'1" (264 cm) | 7'1" (216 cm) | 7'4" (223 cm) | 10'6" (320 cm) | 11'1" (338 cm) |
| INSIDE DEPTH | 17" (43 cm) | 17-1/2" (44 cm) | 17-1/2" (44 cm) | 19-3/4" (50 cm) | 22" (56 cm) | 25-3/4" (65 cm) |
| OVERALL LENGTH | 9'1" (277 cm) | 13'4" (406 cm) | 13'4" (406 cm) | 13'10" (422 cm) | 15'3" (465 cm) | 17'8" (538 cm) |
| OVERALL LOADING HEIGHT - TOP OF FLARE | 30" (76 cm) | 32-1/2" (82 cm) | 33" (84 cm) | 35" (89 cm) | 43-1/2" (110 cm) | 45-1/2" (116 cm) |
| OVERALL HEIGHT W/HYD. ENDGATE | N/A | N/A | N/A | N/A | N/A | 49" |
| OVERALL WIDTH W/STANDARD TIRES | 42" (107 cm) | 58" (147 cm) | 72" (183 cm) | 76" (193 cm) | 80" (203 cm) | 83-1/2" (212 cm) |
| STANDARD TIRE SIZE | 6.00 X 12 | 7.60 X 15 | 7.60 X 15 | 6.70 X 15 | 10.00 X 15 | 9.00 X 20 |
| SPINDLE SIZE | 1-1/4" (3 cm) | 1-3/4" (4 cm) | 2" (5 cm) | 2" (5 cm) | 2" (5 cm) | 2" (5 cm) |
| DIAMETER OF BEATER | 20" (51 cm) | 17-1/2" (44 cm) | 18-1/2" (47 cm) | 18-1/2" (47 cm) | 22" (56 cm) | 27" (68 cm) |
| NUMBER OF PADDLES | 8 | 8 | 10 | 10 | 10 | 8 |
| MAIN APRON CHAIN | 55 | 62 | 67H | 67H | 67XH | T-ROD |
| BOX CONSTRUCTION | CORROSION RESISTANT GALVANIZED STEEL |
| FLOOR CONSTRUCTION | BONDED POLY |
| APRON DRIVE | ADJUSTABLE RATCHET DRIVE | ADJUSTABLE RATCHET DRIVE | ADJUSTABLE RATCHET DRIVE | GEARBOX, 1 SPEED PTO | GEARBOX, 1 SPEED PTO | GEARBOX, 2 SPEED PTO |
| UPPER BEATER | N/A | N/A | N/A | N/A | N/A | OPTIONAL |
| SWING AWAY JACK | N/A | STANDARD | STANDARD | STANDARD | STANDARD | STANDARD |
| WEIGHT W/TIRES | 350 LBS. (159 kg) | 790 LBS. (358 kg) | 975 LBS. (442 kg) | 1140 LBS. (517 kg) | 1600 LBS. (726 kg) | 2030 LBS. (921 kg) |
| OPTIONS | FINE SPREAD PAN | FINE SPREAD PAN OR HYD. END GATE |

Warranty: See operators manual for warranty details and limitations.
H&S reserves the right to change its products or the description at any time without notice or obligation.



Manufactured in U.S.A.



NEED A QR CODE READER?
DOWNLOAD THE FREE APP
TO YOUR SMARTPHONE!

Buy the BEST
BUY **H&S**

Models and specifications are subject
to change without prior notice.

8/12 5M

H&S MANUFACTURING

2608 S. Hume Avenue
P.O. Box 768 • Telephone (715) 387-3414
FAX (715) 384-5463 • Website www.hsmfgco.com
MARSHFIELD, WI 54449



H&S WAREHOUSE 10145 Lakeshore Road
P.O. Box 1260 • Telephone (716) 736-7595
FAX (716) 736-7596 • Website www.hsmfgco.com
RIPLEY, NY 14775