

AWS Head Transports

All Wheel Steer 32', 38', 42' & 48' Models



**Front and Rear
Articulating Pivots**



Heavy Duty articulating pivots add strength, durability and provide a short turning radius.

Minimum Turning Radius:

48' AWS = 27.5 ft.

42' AWS = 24 ft.

38' AWS = 21.4 ft.

32' AWS = 17.5 ft.

Steering Linkages



Steering linkages with ball joints for smooth steering of rear axle. Located on side of main frame, also allows increased ground clearance.

Adjustable Top Rail



Adjustable upper support tube for flexibility when mounting heads.

Torsion Axles with LED lights and SMV

Torsion flex axles, front and rear for a smooth ride.

LED lights and SMV sign are standard equipment.



Standard Features

- 7K Torsion Flex Front Axle - 32' & 38'
- 7K Rear Torsion Flex Axle - 32' & 38'
- 8K Torsion Flex Front Axle - 42' & 48'
- 8K Rear Torsion Flex Axle - 42' & 48'
- LED Rear Tail Lights w/ 7 Pole RV Plug
- New 235/80R16 Load Range E Tires - 32', 38', & 42'
- New 215/75R17.5 Load Range H Tires - 48'

- Adjustable Tie Downs, Qty 2
- Telescoping Tongue w/ Clevis & 1" Hitch Pin
- Adjustable Slider Brackets, Qty 2
- Adjustable Upper Support Tube
- SMV Sign
- Carrying Capacity 14,000 lbs - 32' & 38'
- Carrying Capacity 16,000 lbs - 42' & 48'
- Additional Options Available

P.O. Box 160 ◆ Spencer, IA 51301
1-888-274-6010 ◆ (712) 262-2992 ◆ www.maurermfg.com