



# Utility & Tiltbed Trailers



P.O. Box 160 ♦ Spencer, IA 51301  
1-888-274-6010 ♦ (712) 262-2992 ♦ [www.maurermfg.com](http://www.maurermfg.com)



# Full & Partial Tiltbed Trailer Standard Features



- 6" tubular steel frame with cushion hydraulic system
- Tilting bed cross member spacing of 10 inches
- 81" bed width between fenders
- 14 gauge fenders with mudflaps
- Choice of paint colors (red, black, gray, yellow)
- D.O.T. approved conspicuity tape
- Breakaway kit with 12 volt battery
- Tandem Dexter 6 bolt torsion flex axles w/electric brakes & E-Zlube spindles
- 205 75R15 load range D radial tires w/6 bolt white mod rims ( 14' full tilt w/7,000 lb GVW)
- 225 75 R15 load range E radial tires w/6 bolt white mod rims (16', 18', & 20' full tilt & 14'-4', 14'-6' partial tilt w/10,000 lb GVW)

- Painted steel deck w/non slip silica sand finish (14', 16' 18' & 20', full tilts)
- Painted steel deck w/non slip silica sand finish on tilting deck & treated/kiln dried southern yellow pine on stationary deck (14'-4' & 14'-6' partial tilts)
- Truck-Lite LED lights and sealed wire harness with 7-pole RV plug
- Adjustable 2 5/16" ball or pintle coupler
- Evenly spaced stake pockets (4 side 14' full tilt; 5 side 16' & 18' full tilt; 6 side 20' full tilt & 14'-4', 14'-6' partial tilt)
- Full front bump rail
- Single 7,000 lb dropleg front sidewind jack (14' full tilt)
- Single 12,000 lb dropleg front sidewind jack (16', 18' & 20' full tilts 14'-4' & 14'-6' partial tilts)



*Truck-Lite LED lights*



*81" bed width between fenders*



*14 Gauge Fenders with Mudflaps*



*Breakaway Kit*



*6" Tubular Steel Frame*



*Truck-Lite 7 Pole RV Plug*



*Demco Adjustable 2 5/16 ball coupler*



*Closed Hydraulic Cylinder*



*Cross member spaced 10"*



*Full Front Rail & Evenly spaced pockets*



*Dropleg Front Sidewind Jack*



**Choose from  
a variety of  
colors**

**Maurer leads the utility trailer industry by providing quality workmanship into each trailer.  
The attention to detail in both design and construction is unrivalled.**

## **Maurer Utility Trailer Standard Features**

- 6" channel frame and wrap around tongue construction
- 3" junior i-beam cross members at 16" centers
- 81" bed width between fenders
- 14 gauge fenders with mudflaps
- Tandem 6,000lb spring axles w/electric brakes & 6 bolt hubs
- 225 75 r15 load range e radial tires w/6 bolt white mod rims (10,000 lb gvw)
- Flooring is treated and kiln dried southern yellow pine
- Choice of paint colors (red, black, gray, yellow)
- D.O.T. approved conspicuity tape
- Breakaway kit with 12 volt battery
- Truck-lite led lights and sealed wire harness with 7-pole rv plug
- Adjustable 2 5/16" ball or pintle coupler
- Evenly spaced stake pockets
- Full front bump rail
- Single 12,000 lb dropleg front sidewind jack

## **Maurer Utility Trailer Common Options**


- Rubber Flooring
- Hydraulic Surge Brakes
- Spring Assist Ramps
- Chain Tray
- Spare Tire & Carrier
- D-Rings
- Custom Trailer Color
- 6k 8 Bolt Spring Axles (12k Gvw)
- 7k 8 Bolt Spring Axles (14k Gvw)
- 8k 8 Bolt Spring Axles (16k Gvw)



**Choose from  
a variety of  
colors**



***Rubber Flooring***




***6" Tubular Steel Frame***




***D.O.T. Approved Conspicuity  
Tape***


## Maurer Tiltbed Trailers




**Standard Duty, 14' FULL TILT Trailer, 7,000 GVW**




**Standard Duty, 16' FULL TILT Trailer, 10,000 GVW**




**Standard Duty, 18' FULL TILT Trailer, 10,000 GVW**



**Standard Duty, 20' FULL TILT Trailer, 10,000 GVW**




**Standard Duty, 14'-4' PARTIAL TILT Trailer, 10,000 GVW**




**Standard Duty, 14'-6' PARTIAL TILT Trailer, 10,000 GVW**


## Maurer Utility Trailers



**Standard Duty, 14'-2' Utility Trailer, Slide-In Ramps, 10,000 GVW**



**Standard Duty, 14'-2' Utility Trailer, Tip-Up Ramps, 10,000 GVW**



**Standard Duty, 14' Utility Trailer, Slide-In Ramps, 10,000 GVW**



**P.O. Box 160 ♦ Spencer, IA 51301**  
**1-888-274-6010 ♦ (712) 262-2992 ♦ www.maurermfg.com**