



6200 Series Tandem Disc Harrow Specifications

3-Row Coil Tine Harrow

6211 Non-Folding Models

Adapts To:	6211-12	6211-14	6211-15
Approximate Weight	1,042 lbs. (473 kg)	1,673 lbs. (759 kg)	1,673 lbs. (759 kg)
Tines	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Distance Between Bars	14 in. (3.56 mm)	14 in. (3.56 mm)	14 in. (3.56 mm)
Coil Tine Protection	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs
Tine Angle	Adjustable By Row	Adjustable By Row	Adjustable By Row
Section Width	(1) 13 ft. 3 in. (4.0 m)	7 ft. 4 in. (2.2 m) -- 7 ft. 4 in. (2.2 m)	7 ft. 4 in. (2.2 m) -- 7 ft. 4 in. (2.2 m)

6231 Three-Section Folding Models

Adapts To:	6231-21	6231-23	6231-26	6231-29
Approximate Weight	1,785 lbs. (810 kg)	1,932 lbs. (876 kg)	2,106 lbs. (955 kg)	2,349 lbs. (1,066 kg)
Tines	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Distance Between Bars	14 in. (3.56 mm)	14 in. (3.56 mm)	14 in. (3.56 mm)	14 in. (3.56 mm)
Coil Tine Protection	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs
Tine Angle	Adjustable By Row	Adjustable By Row	Adjustable By Row	Adjustable By Row
Section Width	6 ft. (1.8 m) -- 10 ft. (3.0 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 8 ft. (2.4 m) -- 8 ft. (2.4 m)	10 ft. (3.0 m) -- 8 ft. (2.4 m) -- 10 ft. (3.0 m)	12 ft. (3.7 m) -- 8 ft. (2.4 m) -- 12 ft. (3.7 m)

Adapts To:	6231-30	6231-33	6231-36
Approximate Weight	2,352 lbs. (1,067 kg)	2,587 lbs. (1,174 kg)	2,822 lbs. (1,280 kg)
Tines	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Distance Between Bars	14 in. (3.56 mm)	14 in. (3.56 mm)	14 in. (3.56 mm)
Coil Tine Protection	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs
Tine Angle	Adjustable By Row	Adjustable By Row	Adjustable By Row
Section Width	10 ft. (3.0 m) -- 12 ft. (3.7 m) -- 10 ft. (3.0 m)	10 ft. (3.0 m) -- 14 ft. (4.3 m) -- 10 ft. (3.0 m)	12 ft. (3.7 m) -- 14 ft. (4.3 m) -- 12 ft. (3.7 m)

6250 Five-Section Folding Models

Adapts To:	6250-40	6250-45	6250-50
Approximate Weight	3,390 lbs. (1,538 kg)	3,785 lbs. (1,717 kg)	4,170 lbs. (1,891 kg)
Tines	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)	0.5 in. x 22 in. (12.7 x 559 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Distance Between Bars	14 in. (3.56 mm)	14 in. (3.56 mm)	14 in. (3.56 mm)
Coil Tine Protection	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs	Individual Arm Mounted Adjustable Springs
Tine Angle	Adjustable By Row	Adjustable By Row	Adjustable By Row
Section Width	8 ft. (2.4 m) -- 8 ft. (2.4 m) -- 10 ft. (3.0 m) -- 8 ft. (2.4 m) -- 8 ft. (2.4 m)	10 ft. (3.0 m) -- 8 ft. (2.4 m) -- 12 ft. (3.7 m) -- 8 ft. (2.4 m) -- 10 ft. (3.0 m)	10 ft. (3.0 m) -- 10 ft. (3.0 m) -- 12 ft. (3.7 m) -- 10 ft. (3.0 m) -- 10 ft. (3.0 m)