



6200 Series Tandem Disc Harrow Specifications

Double Chevron Conditioner Reel

6231 Three-Section Folding Models

Adapts To:	6231-21	6231-23	6231-26	6231-29	6231-30	6231-33	6231-36
Approximate Weight	2,625 lbs. (1,191 kg)	2,773 lbs. (1,258 kg)	2,928 lbs. (1,328 kg)	3,112 lbs. (1,412 kg)	3,370 lbs. (1,529 kg)	3,492 lbs. (1,584 kg)	4,114 lbs. (1,866 kg)
Reel Diameter	(2) 14 in. (356 mm) Reels	(2) 14 in. (356 mm) Reels	(2) 14 in. (356 mm) Reels	(2) 14 in. (356 mm) Reels	(2) 14 in. (356 mm) Reels	(2) 14 in. (356 mm) Reels	(2) 14 in. (356 mm) Reels
Rod Diameter	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)
Reel Protection	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure
Independent Hydraulic Lift	Optional	Optional	Optional	Optional	Optional	Optional	Optional