



ROTARY RAKES
KVERNELAND 9000

WHEN FARMING MEANS BUSINESS

Realising the full potential of farming is about growing and developing your business, not only your crop or livestock, but also your profit. Improve productivity and profitability by focusing on the positives and minimising disadvantageous aspects, through strong, dedicated management.

Success springs from determination and clear targets, from laying down the appropriate strategy and allocating correct investments for the future. Quality results require the right ideas and equipment. When there is work to be done, you need the optimal setup and smart solutions that support you towards an easier, more profitable way of working. You need solutions that make tough and demanding conditions less complicated.





PROCESS

Processing the crop efficiently will boost your grass management, ensuring the correct dry matter content and best possible nutritional value.

MADE TO PERFORM

- DAY IN, DAY OUT




Correctly adjusting and customising the rake to the exact conditions facing you today is what adds the extra quality to your forage, ensuring that dirt stays out of the swath, yet leaving no crop behind. Setting the rotor height, adjusting the swath width and fine tuning the cam track (ProLine) is done easily and intuitively on all Kverneland rakes, taking the hassle out of the daily work optimisation.

Curved Tine Arms Support Regular and Even Swaths

All Kverneland rakes are fitted with curved tine arms, to ensure a regular and even swath formation. Additionally the curved shape prevents material from being pushed in the direction of the rotor.


The specially angled tine arms ensure a higher lift out of the swath and leave the swath at just the exact right time in order to prepare regular and even swaths.



Duo Tines

The special **Kverneland Duo Tines**, with their characteristic two-row raking, accurately move the crop into the swath, and with a wire diameter of up to 10mm they additionally provide the **necessary capacity** to move even large volumes of crop.


- ① **Unique DuoTine system**
- ② **Raking** in two rows
- ③ **Excellent performance** with sensitive setup
- ④ **High capacity** with very low raking depth
- ⑤ **Reduced dirt** accumulation in the crop



Curved Tine Arms

The **curved tine arms**, a true Kverneland hallmark, engineered to ensure that the tine arms will leave the swath at exactly the right time, promotes better and **more accurate swath formation**. Essential for running the following machines at maximum capacity.

- ① **Increased capacity**
- ② **Higher lifting** out of the swath
- ③ **Faster drying rates** due to better formed, more fluffy swaths
- ④ **Higher driving speed**, as crop is pressed against the tines



ProLine gearbox.

- ① **Steplessly** adjustable cam track for easy adaptation to different amounts and sorts of crop.
- ② **Injection** moulded aluminium tine arm support housings provide strength and reduced weight.
- ③ **Pinion gear** with two bearings separate from the main driveline, keeping pinion and crown wheel securely in place.
- ④ **All rotor star axles** including housing can be removed individually by just removing 3 bolts.
- ⑤ **Oil-immersed** crown wheel and pinion reduces wear to a minimum.
- ⑥ **Heavy duty** ball bearings with large distance for excellent support of tine arm shafts.
- ⑦ **Flat 400mm** cast iron cam track with optimised shape, for smooth tine arm control and reduced running speed.
- ⑧ **Guide rollers** with hardened surface minimises wear on cam track and cam follower.
- ⑨ **Unique** 4-point ball bearing on crown wheel ensures efficient power transfer to the tine arms.

THE RELIABLE AND SOLID SOLUTIONS

CompactLine

The Kverneland CompactLine rakes features oil-immersed cam discs, guide rollers and tine bearings, alleviating maintenance on these components. Strong tine arms and bearings in an oilbath, ensure **longevity and easy maintenance**. The oil level of the gearbox is easily controlled from the outside.

High-tensile tine arm holders and two bearings on either side of the driveshaft, provide the compact unit with **strength and dependability**. Kverneland-developed cam tracks are specifically tailored to individual rotor diameters, for **optimum raking** at any working width and on any model.


ProLine

The Kverneland ProLine rakes feature a **unique drive system**, which comprises oil-immersed pinion and crown wheels. The fully enclosed design ensures **full and permanent lubrication**, and makes the entire system **absolutely maintenance-free**.


Our extensive experience guarantees well-proven technology of the highest standard.

The hardened cam track is adjustable and with an extremely large **400mm diameter**, giving positive guidance to the steel rotors and quiet machine running.

The optimised shape of the curve disc allows the tine arms to exit the crop faster, leaving a more **uniform swath formation**. Aluminium bearing housings, with two integral ball bearings and wide support, provide solid and maintenance-free tine arm mounting. Additionally all tine arms including housing are removed by simply removing 3 bolts. Fast and easy!.



CompactLine gearbox.



ProLine 10mm diameter tines.




Each ProLine tine arm can be dismounted and repaired individually.


TERRALINK QUATTRO

- STAY ON TRACK!

What really matters is the quality of the silage and hay, which you produce. Precision in every part of the raking process is paramount to ensure that none of the valuable material is left behind, while at the same time securing a clean and attractive crop without dirt.



The rotors are fully flexible in all directions, which means the tines have an exceptional ground following ability....



... ensuring a clean raking result without dirt in the crop.

Three-Dimensional Adaptation

The TerraLink Quattro system has become a true legend related to accurate ground following, vital to avoid dirt in the swath - especially in uneven field conditions. It is a rather simple, yet unique system providing excellent 3-dimensional adaption to ground contours. And it is absolutely maintenance- and wear-free.

The Strength is in the Arm

The openly constructed frame arm absorbs vibrations away from the rotor and allows torsion flexibility, adding the extra tracking flexibility and stability of the rotor. Each rotor operates in 3 dimensions to accurately respond and adjust to uneven field conditions.

High Stability

The trailed wheel axle configuration, where weight is centered on the front boogie wheels, enhances quiet running and prevents lifting and tine bouncing. Each wheel is positioned as close as possible to the raking tines to ensure highest possible rotor stability, inviting for higher travel speed.



The Real TerraLink Quattro Advantage

The TerraLink system consists of two parts. First the lifting arm and second the undercarrier. The arm is slotted on the downside. This, together with special steel quality comparable with tension bars, makes it possible for the frame to flex without breaking.



- 1 **Absolutely** maintenance- and wear-free.
- 2 **Unique combination** of flexible frame arm and 3-dimensional rotor suspension.
- 3 **Rotor operates in 3 dimensions** to accurately respond and adjust to uneven field conditions
- 4 **The boogie wheels** are positioned as close as possible to the raking tines to ensure high rotor stability.
- 5 **The trailed axle configuration** enhance quiet running and prevents lifting and tine bouncing.
- 6 **The openly constructed frame arm** absorbs vibrations away from the rotor and allows torsion flexibility.
- 7 **The accurate tracking** made possible by the TerraLink Quattro feature, ensures that a minimum of crop is lost during raking.

KVERNELAND 97150 C

NEXT LEVEL RAKING

Beef and dairy farming is all about the production of high quality milk and meat. That's why you constantly strive for optimising productivity and profitability. Ruminants need high quality roughage, for their health and productivity. The more nutritional value per hectare you harvest, the more your forage management contributes to the farming business.

Every farm has different possibilities for growing forage crop. Circumstances vary by region and even by lot. Farmers and contractors also have to deal with the seasonal effects, such as field conditions, changing crop intensity during the season and - in particular - the weather. Planning means constantly adapting to unexpected conditions.

Raking is all about the efficient production of high quality forage

Capacity and Flexibility

Two factors are key for optimising the quality of the silage and hay: **capacity and flexibility**. You need capacity to get the complete work done in time, before the weather changes. You need flexibility to adjust the rake to whatever challenges you meet.

With an adjustable working width of 9.8-15.0m the Kverneland 97150 C 4-rotor rake is well prepared to tackle whatever conditions might appear. The [extensive working range](#) allows exact adjustment to each individual field. Whether it's heavy first cut crop or later on in the season, the following machines are fed a [perfect size swath](#) for optimised work flow.







TERRALINKQUATTRO
Ground Contour Following System

The Elbow Design Makes the Difference

The special elbow design of the front rotor arms is a unique feature of the Kverneland 97150 C. This special Kverneland design allows an impressive, continuously adjustable, working range between 9.80 and 15.00m, which is unmatched flexibility that only Kverneland offers. Raking width can be matched to differing crop characteristics, to obtain an evenly shaped and equally wide swath across the full width.



IT'S ALL ABOUT PERFORMANCE

15m Working Width

The special elbow design allows quick working width adjustment. In case of contact with an obstacle, the overload protection on the outer arm ensures that it folds back at a certain pressure, securing the main frame structure from damages.

Also when raking along borders, the fast moving front arms can be used to steer along fences etc. without slowing down. Specially while raking corners, it is possible to clean them in one go as the front rotor can be pushed inside the corner.

The biggest benefit with the system though, is that the next swath will still be straight, as the rotor towards the non-raked area stays in position. When passing obstacles in the field, the front rotors can quickly be moved inwards, ensuring the swaths stay straight.

Tackle the Terrain

The front rotors are fitted with hydraulic ground pressure control for constant adjustment of ground pressure. Regardless of chosen working width, ground pressure remains even, allowing the rotor to instantly react to uneven field conditions for accurate tracking.

The advantages are obvious, as it leads to less damage and faster regrowth from the stubble and minimum dirt into the crop. Especially in wet conditions the low remaining weight on the rotor is a big advantage in order to get clean crop.

A Superbly Manoeuvrable Unit

The 2-pt headstock allows a turning angle up to 80° and the optional unique steered wheel axles ensure these Kverneland rakes have unequalled manoeuvrability. Despite a total length of 9.20m, even narrow gateways or approach lanes to fields are easily negotiated. For easy headland management it is possible to optimise the time delay of lifting and lowering the front and rear rotors. Three different possibilities can be chosen. All 4 rotors can be lifted individually, allowing you to rake any size or shape of field in a professional and efficient way.



Each rotor can be independently and hydraulically set for height.



All 4 rotors can be lifted individually.



High lift of rotors ensures generous clearance during headland turns. Lifting height can be adjusted infinitely.



CUSTOMISE THE SIZE OF YOUR SWATH



Hydraulic adjustment of swath width.



Transport height below 4.0m, even without removing tine arms.

Adjustable Working Width

Raking width can be continuously varied on the move between 9.80m and 15.00m. Raking width can be matched to the density of crop to obtain an **evenly shaped and equally wide swath** over the full length. Change of working width can be done in all situations, while driving, but as well while standing still with rotors on the ground. If the width needs to be adjusted shortly, the previously set working width can be recalled automatically.


Brakes and Tyres

The wide tyres not only ensures gentle treatment of the ground, but also makes for **excellent stability** both in the field and on the road. Hydraulic or pneumatic brakes permit road speeds up to 40 km/h. All rotors are equipped with 3 twin wheels, **360° free turnable**, for perfect guidance and no problem in narrow curves with destroyed grass fields.



9.8 – 15m w

1.4 – 2.5m sv



Everything Under Control with ISOBUS Technology

The Kverneland 97150 C is **fully ISOBUS compatible**. This means that it will plug directly into an ISOBUS compatible tractor without the need for a separate terminal. The Kverneland 97150 C is available with the IsoMatch Tellus or the new IsoMatch Tellus Go control terminals.

The IsoMatch Tellus GO is especially developed for controlling machines in a simple way. Just connect your machine, step into the tractor cab, switch on the power button and GO.

The terminal brings the implement automatically into view

To **maximise user comfort** on the Tellus GO terminal, all buttons are positioned on right hand side of the terminal. No need to look at touchscreen when operating the machine.



Take Full Control

The following functions can be operated with the terminals:

- Swath and working width indication.
- Programmable lifting height of rotors.
- Automatic selection of transport or working position by pressing an icon.
- Separate lifting of all four rotors.
- Setting of rotor height.
- Adjustment of working width, left and right hand side.
- Active and selectable hydraulic suspension on front rotors.
- Steering of transport axle.
- Headland management activation.
- Adjustment of delay time/meters or manual operation of headland management.
- Special customized user interface, developed with contractors, for very simple control of functions.
- Optional with joystick.





MAXIMISE PRODUCTIVITY

NO CROP LEFT BEHIND

The Kverneland GEORAKE solution is the answer when it comes to managing raking operations in the most efficient and productive way. Making accurate, well-shaped swaths has never been easier. GEORAKE automatically lifts and lowers each individual rotor at exactly the right time – all you need to do is to focus on running the tractor in the most efficient way. The stress factor of finishing swaths correctly, before turning on headlands, or in odd shaped plots, has been completely eliminated.

GEORAKE Supports Performance

To [maximise productivity](#), precision is needed, from both machine and operator, especially during headland operation. You need to lift and lower the rotors at just the right time, to rake up crop in the most efficient manner. This essential operation has been [fully automated](#) with the introduction of the 97150C GEORAKE. Each of the 4 rotors is individually controlled via [section control](#), without any attention needed from the operator, who can then fully focus on optimising the raking operation.

No crop is left behind, and no swaths on headlands are destroyed by interference from the rotors. Work is done correctly, always.

Accurate, Efficient Raking

GEORAKE registers the areas already raked. If a rotor enters into such an area, it will automatically lift. Each rotor lifts individually and acts as one of four sections. When entering an unraked area the rotor automatically lowers again in due time to prepare the next swath.

When raking awkwardly shaped fields GEORAKE automatically avoids raking into already prepared swaths, [automatically lifting](#) the rotor or rotors involved, without the need for any counter steering from the driver.

GEORAKE is a license based application, and requires a machine license and section control license for the Terminal. The Terminal license can also be used for other operations like planters, spreaders and sprayers.



As already raked areas are registered, each individual rotor will automatically lift for headland turns.



GEORAKE optimises the raking result – every time and under all conditions. It provides less stress for the driver and supports him in doing an excellent job.





TERRALINKQUATTRO

Ground Contour Following System

KEEP THINGS SIMPLE

- EASE YOUR WORK

ProLine or CompactLine Specification

The Kverneland 12.5m 4-rotor rake is offered with a choice of either ProLine or CompactLine gearbox. Both machines are similar in construction. They are build up on the same frame concept. The Kverneland 94125 C CompactLine version is an [easy-to-use machine](#) with substantial working width for the professional segment, looking for a dependable machine to ensure stability in the complete harvesting process.

For heavy duty use, the Kverneland 95130 C ProLine machine has been developed.

Boost Your Capacity

The Kverneland 94125 C and 95130 C are targeted at making lighter work of tough and demanding operations. Being able to accurately feed the machine that follows and [keep up efficiency](#) of the complete harvesting system is an essential part of the raking job.

With their impressive capacity of 12.50m working width, [straightforward design](#) and the possibility to adjust both work and swath width from the cabin, these machines are [designed to boost the complete process](#) of collection and pick-up, altering to the changing crop intensity during the season.

Easy Handling - More Productivity

These rakes are designed with uncomplicated work days in mind. Forget about sophisticated sensors and control functions, they are designed around the operator with [simplicity in mind](#), focusing on the elements that add real value. Take the control unit for instance. It comes with a rather handy design including pre-selected functions for an array of easy operations. Only one double acting and one single acting spool valve are required to run the Kverneland 94125 C and 95130 C.

Excellent Swath Formation

To prevent an uneven appearance of the swath and to keep capacity up, the rear rotors are smaller in diameter and turn faster. This secures the [additional capacity](#) needed on the rear rotors for the double volume, and as the speed is different it also prevents roping.

The [maintenance-free TerraLink Quattro](#) rotor suspension system, operating in 3 dimensions for excellent tracking, works in close combination with the 4 wheeled rotor to ensure [high accuracy and stability](#) on slopes. And it is absolutely maintenance- and wear-free.



Easy and intuitive control function, all handled from the tractor cab.



Individual pairwise lift of front and rear rotors. Adjustable time delay for headland position is standard.

EASY HANDLING – MORE PRODUCTIVITY



Hydraulic Adjustment of Working and Swath Width

The hydraulic adjustment of working and swath width allows you to **customize swath intensity** and width to the capacity of the following machine.

All conveniently handled and controlled from the tractor seat. Working width can be set between 10-12.50m and swath width can be adjusted between 1.20-2.20m, adding the necessary flexibility.

Easy Headland Management

These machines come with **enhanced headland management**. In addition to high ground clearance of rotors during headland turns, it is possible to tailor time delay between lifting/lowering the front and rear rotors to driving speed and field conditions. This is done mechanically in an easy and uncomplicated way.

Kverneland 94125 C and 95130 C will do sharp turns of up to 80°, both on headlands and during transport when passing narrow gate ways. The rotors can, as a standard feature, lift pairwise which is convenient for raking also triangular shaped fields in an optimal way.

More Uptime with max 4m Transport Height

No reasons for wasting time, not even when moving between fields. Just raise the rotors and off you go, safely below 4.00m transport height – no need to leave the tractor for removing tines arms. Large transport wheels and hydraulic brakes are standard.

For storage all tines arms are detachable on Kverneland 94125 C to allow a storage height as low as 3.40m. A strong and stable storage foot ensures fast and trouble-free coupling and uncoupling. For Kverneland 95130 C tine arms are generally fixed, but the top 4 are detachable, to reach same low storage height.





- ① **Easy operation** of all functions via simple control unit. No sensors needed for control.
- ② **Transport height** below 4m, even without detaching tine arms.
- ③ **Kverneland 95130 C** comes equipped with ProLine gearbox, while Kverneland 94125 C is fitted with CompactLine gearbox.
- ④ **Hydraulic adjustment** of working and swath width, 10.0-12.5 and 1.2-2.2m respectively.
- ⑤ **Simple design** – just one single and one double acting valve needed.
- ⑥ **TerraLink Quattro** – Absolutely maintenance- and wear-free 3-dimensional adaptation for outstanding raking quality.
- ⑦ **Individual pairwise lift** of front and rear rotors. Standard fitted with adjustable time delay for headland position.
- ⑧ **Compact but efficient** – can be operated with tractors starting from 80hp.
- ⑨ **3.35m front rotors** and 3.0m rear rotors, each with 12 tine arms and 4 tines per arm. Faster rotating rear rotors ensure uniform swaths.

HIGH PERFORMANCE AND PRECISION



The control box, placed in the tractor cab, controls the main functions needed during work. Lift and height adjustment of rotors can be done individually. Working width can be easily adjusted, and the box also features a transport locking device.

Heavy Duty Machine with Compact Design

The Kverneland 95110 C is a twin rotor rake with 11.00m working width for the [high performance segment](#), normally covered by more expensive four rotor rakes. 95110 C offers easy operation, excellent manoeuvrability and a [heavy duty design](#). Despite the working width of 11.0m, the rake is still very compact, something very convenient when working in smaller fields. Standard on the machine, besides the height adjustment, is as well the individual lifting of the rotors and [hydraulic height adjustment](#) with the possibility of setting a mechanical minimum height.

Easy Operation with Minimum Maintenance

The 95110 C is designed for [easy operation](#), with a number of features making the working day as comfortable as possible. The machine is built around two fully enclosed, heavy duty gearboxes, that ensures full and permanent lubrication, making the system [absolutely maintenance-free](#).

ProLine Gearbox

The ProLine gearbox offers excellent swath formation. The shape of the Kverneland hallmark, the massive 400mm curve disc, allows the tine arms to leave the crop faster, leaving a more uniform swath shape. The tine arm shafts and housings be easily changed if needed.

Perfect Ground Contour Following

The Kverneland 95110 C is fitted with the TerraLink Quattro system, offering perfect ground contour followings. A unique combination of an undercarriage with 6 wheels and a specially designed rotor suspension, ensures superb raking performance.

The hydraulic height adjustment, with possibility of setting a mechanical minimum height, is a highlight of the machine.





TERRALINKQUATTRO

Ground Contour Following System



Hydraulic adjustment of working width between 9.60m and 11.00m.



Hydraulic height adjustment of the rotors to suit length of the stubble or varying ground conditions.



Active wheel steering, allowing sharp turns on headlands and during transport.



The two rotors are hydraulically lifted on headlands, and ensure outstanding ground clearance in headland position.



To reach a transport height below 4.00m, the tine arms are removed and safely placed on the carrier frame.



TERRALINKQUATTRO
Ground Contour Following System

THE HEAVY DUTY CENTRE SWATH RAKES

Durable Performance

With adjustable working widths of 7.00-9.00m respectively these **heavy duty specification rakes** provide the swath formation capability to keep harvesting operations running at their **optimum output**. At the heart of all models is a heavy duty ProLine rotor head system. The machines are equipped with ground protecting 380/55-17 tires.

Excellent Manoeuvrability

The rear carrier frame with controlled steering facility gives this rake **excellent track following characteristics**, allowing tight turns on headlands and loss free swathing, even in awkwardly shaped fields. Even if the rotors are lifted on a steep slope, the steering system reliably counteracts any deviation. During headland turns the rotors are lifted min. 45cm from the ground to prevent swath damage.

- Actively steered wheels for excellent tracking.
- Ability to make sharp turns up to 80°.
- High lift of min. 45cm of rotors ensures generous clearance during headland turns.
- Raking with only one rotor (standard on 9590 C, optional on 9580 C and 9584 C).

On-the-Go Rotor Height Adjustment

A ComfortKit is optionally available for 9584 C and standard on 9590 C Pro. This includes a hand-held joystick control that brings all control functions into one. The height of each rotor is controlled electronically, and actual height of each rotor is shown on the screen of the control box. In this way **fine tuning rotor height**, improving your work result is easily done on the go.

A screen indicator shows the actual height in percent. It is as well possible to set a personal zero point, to prevent too deep raking. On top the kit includes individual rotor lifting. It is possible to adjust the rotors together or individual in all positions.

Flexible Working Width

Kverneland 9580 C: 7.00-8.00m working width.
Kverneland 9584 C: 7.60-8.40m working width.
Kverneland 9590 C Hydro: 8.00-9.00m working width.
Kverneland 9590 C Pro: 8.00-9.00m working width.



ComfortKit including electronic control of separate rotor height.



Kverneland 9584 C with 8.40m working width, fully enclosed gearbox and hydraulically adjustable working width.



TERRALINKQUATTRO
Ground Contour Following System

Transport Height below 4.00m

Kverneland 9580 C includes a transport height below 4.00m without leaving the tractor cab and actively steered axles supporting tight turns on headlands and during transport.



MORE UPTIME WITH CLEVER TRANSPORT

Kverneland 9580 C - Design Optimised for Transport

The Kverneland 9580 C masters both extensive working width and compact transport measures. The design of the wheel axles allows adding generous 380/55 wheels as standard and still offering a transport width as narrow as 2.75m, making it the perfect match for narrow roads and tight gateways.

Transport height is below 4.00m, even with all tine arms attached. No need to leave the tractor, just fold and go. Add in the 80° turning headstock and active wheel steering, and you have a highly manoeuvrable machine on road and in the field.

No need to leave the tractor, just fold and go

Kverneland 9590 C Hydro

- High Capacity in Field, Compact on the Road

The Kverneland 9590 C Hydro will go as wide as 9.00m during work with its' twin rotors, and offers the flexibility to adjust the working width between 8.00-9.00m. It will stay below 4.00m during transport, even with all tine arms mounted.

Thanks to the [hydro axles](#), which are a unique Kverneland feature, the complete rake can be lowered hydraulically for transport, ensuring that it will go below 4.00m transport height. Another benefit is that the gravity point is moved towards the ground, and in combination with the wide track width and large 380/55-17 tyres it creates [excellent weight distribution](#) and stability during transport. 9590 C Hydro comes as standard with a lift arm suspension and as well with single side lifting.



With 9.00m working width and transport height below 4.00m, even without detaching tine arms...



... the Kverneland 9590 C Hydro offers remarkable productivity with no downtime.

COST-EFFECTIVE HIGH-PERFORMANCE RAKES



Optional boogie wheels for the Quattro undercarriage for further improved ground contour following.



9476 C - Hydraulic 7.0-7.8m working width.



Kverneland 9476 C - easy storage of tine arms for transport.

Centre Swath Rakes

These rakes will produce a [nice even centre swath](#) from raking widths of between 6.20m and 7.80m. They are mounted on a [strong and stable frame](#), to ensure long lifetime. Features such as actively steered wheels, the TerraLink Quattro system and hydraulically raised rotors are standard - except for the low cost start up model 9464 C.

The double rotor rakes offer [hydraulically adjustable working widths](#) between 6.2 and 7.8m. The swath width can be set between 1.20-2.20m. A clever solution that makes it possible to adapt the swath size to the pick-up width of loader wagons, balers and foragers.



TERRALINK QUATTRO
Ground Contour Following System

UNIQUE MANOEUVRABILITY

Active Wheel Steering

Kverneland centre swath rakes all have a carrier frame for strong and stable working performance. The wheels of the rear carrier have [active wheel steering](#), allowing the rakes to go around tight corners during work and narrow gateways during transport. This allows the rakes to follow swaths around bends, and to make turns of up to 80°.



The centre swath rakes are converted hydraulically for transport from the tractor cab.



Raking with only one rotor.



Turning on headlands – turning in one go due to the excellent manoeuvrability and the hydraulic QuickLift.



9472 C Hydro

The Kverneland 9472 C Hydro is fitted with [hydraulically operated axles](#) on the mainframe, in order to lift and lower the machine during transport. This feature significantly reduces transport height by 40cm. This is even without detaching the tine arms. The Hydro version is standard equipped with single side lifting of the rotors.

Add in features such as adjustable working width of 6.20-7.20m, TerraLink Quattro ground contour following and [heavy duty carrier frame design](#), and the result is low maintenance, higher productivity and [maximum operation comfort](#). As well the CompactLine gearbox, with all critical parts running in oil, helps to reduce maintenance time to a minimum.

All main functions, such as lifting and lowering of mainframe and rotors are operated from the tractor cab, using an [electro hydraulic control terminal](#). It is also possible to pre-select lift activation of the individual rotor units via the terminal. Such an integrated solution is offered only by Kverneland.



TERRALINKQUATTRO
Ground Contour Following System



Unique Manoeuvrability

The Kverneland 9469 S Vario and 9469 S Evo, like all Kverneland frame-based rakes, feature a headstock that turns through a 80° angle to give **superb tracking** and **superior manoeuvrability**. 40cm lifting height ensures that existing swaths remain undamaged when crossing.



9469 S: One Machine - Two Executions

Completing the line of side delivery rakes, these compact and nimble rakes feature a sturdy frame and the well-proven TerraLink Quattro ground-following system. With a working width of 6.90m, the machines rake up double swaths of up to 13.20m. All tine arms are removable and curved to the unique Kverneland design to enable cleaner raking.

The Vario execution offers additionally the possibility to rake up two separate swaths along each of the individual rotors, whereas the Evo model can do one swath to the side.

A host of exciting details such as the well thought out continuous driveline, all make the Kverneland 9469 S Vario and 9469 S Evo universal machines that suits a wide range of applications. Pivoting wheels made for tight cornering without risk of rotors tilting and tines scraping the ground. The two rotors provide generous overlapping, and the cam tracks are matched to each other to transfer the material uniformly.

DOUBLE UP ON EFFICIENCY!



Optional an hydraulic foldable swathboard is available for 9577 S.



The side delivery concept allows you to collect crop from 15.00m into a single swath.

9577 S: The Obvious Side Effect!

The 9577 S double rotor rake delivers a working width of 7.70m. The side delivery concept adds excellent flexibility in swath formation and allows you to collect crop from a working width of up to 15.00m into one swath. The high build mainframe concept offers excellent ground clearance in headland position. Actively steered wheels allow sharp turning, both on headlands and during transport.

9577 S is fitted with the renowned ProLine gearbox, with its' maintenance free oilbath solution. The shape of the Kverneland hallmark, the massive 400mm curve disc, allows the tine arms to leave the crop faster, leaving a more uniform swath shape. In addition the rotors have been upgraded to 12 tine arms on the front rotor, each with 4 tines, and 13 tine arms, each with 5 tines on the rear rotor. This ensures more accurate raking performance without roping, and allowing higher forward speed.

Kverneland side delivery rakes have steerable undercarriers on the front rotor to secure a smooth following in curves. As well a swath board on the first rotor stops the crop, so it can be pushed through the rear rotor (Option on 9469 S Evo). In addition Kverneland 9577 S is fitted with the TerraLink Quattro wheel system for superb ground contour followings. This system controls the rotor in 3 dimensions.

All side delivery rakes place the swath on the left hand side. This offers a superb view on the right hand rotor, to steer the machine along fence lines and obstacles in a comfortable position.



THE FLEXIBLE RAKING SOLUTIONS

The Kverneland 9471 S Vario and the Kverneland 9471 S Evo are designed for [maximum flexibility](#), for raking in a variety of conditions. The twin rotors work independently from each other, making it possible to collect either one large swath or two smaller night swaths. These rakes can place two large swaths into one, allowing a total of up to 12.50m crop to be gathered into one swath.

Large in The Field, Small in Transport

No need to remove the tine arms: Moving the Kverneland 9471 S Vario and the 9471 S Evo to transport position only requires a [simple operation](#) on the hydraulic leaver. The swath deflector can be fold hydraulically clear. Transport width is only 3.00m (to reach 2.45m, the tine arms can be removed).



Placing two smaller night swaths.



Turning on headlands: Kverneland is equipped with the QuickLift system as standard. This ensures a lifting height of 50cm to easily over cross existing swathes.



Pulled axle suspension for smooth running characteristics and reduced power requirement.

Kverneland TerraLink

- Absolutely maintenance- and wear-free.
- Superb tracking in road transport.
- Trailed axle configuration enhances quiet-running and reduces tractor input power, particularly in wet conditions.
- Boogies are set to wide track widths and specified with 18.5" tyres, to sense field contours right on the tines for perfect ground-following and stability on the slopes
- Automatic dampening provides quiet machine running.
- The machine comes as Evo standard with tandem axle in the front. As Vario the machine is equipped as well with a land wheel standard (option for EVO)
- Optionally the machine can be equipped with up to 13 wheels with tandem axles on the rear rotor and two sets of inner tandem axles on the front of the undercarrier.
- 11 arms in the front and 12 arms on the rear secure a even swath and good crop flow that prevents roping.





FOLLOWING THE TERRAIN

Kverneland SideShift

The Vario version also offers the patented **SideShift system** as an option, which comprises electro-hydraulic control of all functions. A special feature on the Kverneland 9471 S Vario is the possibility to operate both rotors – front and rear – in an offset position from the tractor cab.

Raking along field boundaries or around trees is no problem



SideShift to the right - conveniently passing trees.



SideShift to the left - raking without driving on unraked crop.

HIGH QUALITY AND RELIABILITY



For transport or storage, the rotor guard frames are folded up close to the mainframe, locking automatically into position. An assistor spring linked to the swath board reduces the effort required.



Standard oscillation dampers ensure excellent running characteristics.



Optional third wheel, allowing continuous use of the standard top link.



Adjustable cam track.



ProLine oilbath gearbox design ensures maintenance-free operation.

High Performance

Kvernelands generation ProLine single rotor rakes offer a gearbox design with excellent working result. Features such as oscillation dampers, tandem axles and **HydroLift height adjustment** are standard hallmarks of the single rotor rakes.

ProLine Gearbox

The single rotor rakes are based on the ProLine gearbox technology. These machines offer working widths of

4.20m and 4.60m respectively and are fitted with the Kverneland ProLine gearbox, with its' **maintenance-free oilbath solution**.


The ProLine gearbox now offers better swath formation. The shape of the Kverneland hallmark, the massive 400mm curve disc, has been improved to allow the tine arms to leave the crop faster, leaving a more **uniform swath shape**. The tine arm shafts and housings can be exchanged even faster.

Both rakes are standard fitted with both 4 wheel tandem axles and oscillation dampers, offering **excellent ground contour following**, minimizing the amount of dirt collected in the swath.

HydroLift Concept

A unique Kverneland feature of the 9542 and 9546 is the HydroLift concept. It is a hydraulic height adjustment system that allows the driver to **quickly adjust working height** to different ground conditions from the tractor cab.





1. Clearly visible oil level via inspection glass.
2. A pivoting 3-pt headstock ensures perfect ground following performance, and perfect tracking when cornering. Oscillation dampers are optionally available.
3. Optional third wheel, allowing continuous use of the standard top link.

MINIMUM POWER REQUIREMENTS

Kverneland offers six compact single rotor rakes, designed for use on low horsepower tractors, but which still deliver considerable working width. Kverneland single compact rotor rakes offer working widths from 3.20-4.70m. With the option of [pivoting and a trailed version](#), there is a model to suit all needs. On all models all tine arms can be removed and parked along the frame. A big advantage with regards to transport and storage dimensions.

Maintenance-Friendly Rotor Head

All Kverneland CompactLine rotary rakes are equipped with a maintenance-friendly rotor head. The rotor head is grease lubricated within a [hermetically sealed housing](#),

offering a very [reliable performance](#). This ensures a long lifetime, minimizing the effects of dirt. The rotor shaft, tine arms and pinion shaft are all mounted on two bearings, to provide maximum strength and a [long lifetime](#).

Trailed Rotary Rakes

The perfect machines for farmers looking for rakes for low horse power tractors. 9442 T and 9447 T can be run by tractors starting from 20HP, when attached to a linkage mounted drawbar or hitch. The rakes offer a [quick-lift system](#) to lift out of the swaths quickly. They offer a ground clearance of 50cm when lifted, something which is important when driving across swaths. 18.5" Tandem axles come standard.



Kverneland 9447 T with 4.70m working width and a weight of only 665kg.



Kverneland 9439 in transport position.



MANAGE YOUR FARM AS A BUSINESS WITH OUR ISOMATCH PRECISION FARMING OFFERING

Our precision farming offering is essential in managing your farming business with success. Applying electronics, software, satellite-technology, online tools and Big Data enables you to use your farming equipment more effectively and reach higher profitability of your crops.

iM FARMING - smart, efficient, easy farming



Maximum savings!
The IsoMatch GEOCONTROL precision farming application includes Manual Guidance and Data Management free of charge. It is possible to expand this application with Section Control.

Enhance your success with e-learning

IsoMatch Simulator is a free downloadable virtual training program. It simulates all functions of the IsoMatch Universal Terminals and Kverneland ISOBUS machines. Train yourself and make yourself familiar with your machine to avoid errors and enhance your machine performance.

The best overview in farm management

IsoMatch FarmCentre is the first of a series of telematics solutions. This fleet management solution is applicable for your ISOBUS machines in combination with an IsoMatch Tellus GO/PRO. Whether you wish to control your fleet, manage tasks remotely or analyse machine performance data, IsoMatch FarmCentre provides this in an efficient web application, linking implements, tractors, terminals and the cloud in one continuous flow of data and connectivity.





Be a PRO in increasing productivity

The **IsoMatch Tellus PRO** 12-inch terminal provides you with the optimal solution for an all-in-one control system inside the tractor cab including automatic steering. It is the centre for connecting all ISOBUS machines, running precision farming applications and Farm Management Systems. It offers everything you need to get the maximum out of your machines and crop, as well as cost savings in fertiliser, chemicals and seeds by using automatic section control and variable rate control. With the unique dual screen functionality it gives you the opportunity to view and manage two machines and/or processes simultaneously.



100%

100% focus on the result
in the field with
IsoMatch AutoDrive-E

100% focus, maximum performance

IsoMatch AutoDrive-E provides automatic tractor steering. Manage your work to be more efficient and avoid overlaps which leads to cost savings of up to 15%, better growing conditions and increased yield. (Only in combination with IsoMatch Tellus PRO).

Easy control management

The **IsoMatch Tellus GO** is a cost-efficient 7-inch terminal, especially developed for managing the machine in a simple way. Easily set up the machine with the soft keys and simply use the hard keys and rotary switch for optimal control while driving.

*Improve your performance
Maximum efficiency, minimum waste*



NEW

IsoMatch Global PRO

GPS antenna system with RTK precision for the highest accuracy (2-3 cm) and best productivity.



NEW

IsoMatch Grip

This ISOBUS auxiliary device is made for maximum machine control and efficient farming. Operate up to 44 implement functions from one device.



IsoMatch InLine

Light bar for manual guidance including section status information. Manage the distance from the A-B line and steer for the ideal position.



IsoMatch (Multi)Eye

Connect up to 4 cameras to the IsoMatch Universal Terminals. It gives you full control and overview of the entire machine operation.

ORIGINAL PARTS & SERVICE

ONLY ORIGINAL PARTS WILL KEEP YOUR MACHINE A KVERNELAND



Did you know that our parts are manufactured to the same high standards and strict specifications as the Kverneland machines? Original Parts will always work and fit as intended, and are guaranteed to keep your machine running at maximum performance.

Kverneland has been a symbol of quality since 1879; the experience we have, combined with a constant strive to improve our products, ensures you the best parts available for your Kverneland machine. Parts and Service surrounds your machine with a safety-net; the quality ensures optimal usage of the machine, the quality of the parts refers to a low life-cycle cost and longer wearing time.

Our long term relationship starts at the purchase of your Kverneland machine, and we will continuously stay by your side for support and assistance. We will guide you on the way to make sure you achieve maximum performance, productivity and profit.

Do not compromise quality with cheap solutions, remember that only Original Kverneland parts are the guaranteed solution to achieve what is expected by a Kverneland machine.



YOUR PARTS SPECIALIST

Through our worldwide dealer network you will find your local dealer, whom is always prepared to assist you. Your Kverneland dealer knows every inch of your machine and will gladly provide the expertise needed to ensure that you are operating at maximum potential.

Your parts specialist has got all the parts that you need and will also have the facilities to service your machine. Make sure to visit your Kverneland dealer on a regular basis to be updated on promotions and product news that you will not find elsewhere.



ALWAYS AVAILABLE

Time is money, and we know the importance of receiving the right parts at the right time! Your Kverneland dealer is supported by a massive distribution network to supply you with exactly what you need, when you need it.

Our main distribution centre is located in Metz, France. A strategic location for distributing parts to all corners of the world. With over 70.000 parts in stock and 24/7 service, we are ready to supply you with parts – at any time!



EASY ACCESS TO INFORMATION

Are you looking for a complete overview of parts for your machine? Maybe you are searching for more technical information? Our Online Search Database, *Quest*, provides all information available for your machine.

Various documentation like Parts Manuals, Operation Manuals, Software updates and FAQ's, it is all there. *Quest* is available in several different languages and can be accessed wherever and whenever. All answers are easy to find – just a few clicks away !

TECHNICAL DATA

Model	Single Rotor Rakes								
	9032	9035	9439	9542	9442 T	9443	9447 T	9464 C	9546
Dimensions & Weight									
Working width m	3.20	3.50	3.90	4.20	4.20	4.30	4.70	6.35	4.60
Working width (ft)	10'6"	11'6"	12'10"	13'9"	13'9"	14'1"	15'5"	20'10"	15'1"
Transport width m	1.60	1.75	1.75	1.75	2.00	2.10	2.40	2.80	2.15
Transport width (ft)	5'3"	5'9"	5'9"	5'9"	6'7"	6'11"	7'10"	9'2"	7'1"
Transport length m(ft)	3.10/10'2"	3.35/10'12"	3.60/11'10"	3.15/10'4"	3.90/12'10"	3.85/12'8"	4.80/15'9"	5.90/19'4"	3.35/11'
Parking height m	1.60	1.70	1.85	2.60	2.30	2.00	2.65	3.85	2.75
Parking height (ft)	5'3"	5'7"	6'1"	8'6"	7'7"	6'7"	8'8"	12'8"	9'0"
Weight appr. Kg(lbs)	315/694	420/926	460/1014	640/1410	570/1256	480/1058	665/1466	1510/3329	670/1477
Swath width m								1.20	
Swath width(ft)								3'11"	
Capacity theor. (ha/h)	3.5	3.9	4.3	4.6	4.6	4.7	5.2	6.9	5.1
Attachment to Tractor									
3-pt. tracking (cat.)	1/2	1/2	1/2	2	-	1/2	-	-	2
Lower links (2-pt.)	-	-	-	-	-	-	-	●	-
Linkage drawbar	-	-	-	-	●	-	●	-	-
Gauge wheel 16°	○	○	○	○	○	○	○	-	○
Rotors/Arms/Tines									
Rotor diameter m(ft)	2.60/8'6"	2.80/9'2"	3.05/10'	3.35/11'	3.35/11'	3.35/11'	3.65/12'	3.00/9'10"	3.65/12'
Swath presentation	Left	Left	Left	Left	Left	Left	Left	Centre	Left
Number of rotors	1	1	1	1	1	1	1	2	1
Number of tine arms per rotor	9	10	11	12	11	12	12	10	13
Number of Duo tines per arm	3	4	4	4	4	4	4	4	4
Tine diameter (mm)	9	9	9	10	9	9	9	9	10
Continuous cam track adjust.	-	-	-	●	-	-	-	-	●
Detachable tine arms	●	●	●	●	●	●	●	-	●
Height adjustment	Rack trail	Mech.	Mech.	Hydr.	Mech.	Mech.	Mech.	Mech.	Hydr.

Model	Single Rotor Rakes								
	9032	9035	9439	9542	9442 T	9443	9447 T	9464 C	9546
Wheels and axles									
Tyres (rotor)	15x6.00-6	16x6.50-6	16x6.50-6	16x6.50-6	18x8.50-8	16x6.50-6	18.5x8.5-8	16x6.50-6	16x6.50-6
Fixed tandem axle	○	○	○	●	●	○	●	○	●
Pivoting tandem axle	-	-	-	○	-	-	-	-	○
Stand. tyres (carrying frame)	-	-	-	-	-	-	-	10.0/75-15.3	-
Opt. tyres (carrying frame)	-	-	-	-	-	-	-	-	-
Further optional equipment									
Carrier arm compensating	○	○	○	●	-	○	-	-	●
Locking catch for slopes	○	○	○	●	-	○	-	-	●
Safety accessories									
Warning panels	○	○	○	○	○	○	○	●	○
Lighting equipment	○	○	○	○	○	○	○	●	○

- Standard equipment
- Option
- Not available
- * Double swath
- ** With detached tine arms
- *** Hydraulically lowered mainframe

TECHNICAL DATA

Model	Double Rotor Rakes								
	9469 S	9469 S	9471 S	9471 S	9472 C	9472 C	9476 C	9577 S	9580 C
	Vario	Evo	Vario	Evo		Hydro			
Dimensions & Weight									
Working width m	6.90/7.90	6.90	6.60/7.10*	6.60/7.10*	6.20/7.20	6.20/7.20	7.00/7.80	7.70	7.00-8.00
Working width (ft)	22'8"/25'11"	22'8"	21'8"/23'4"	21'8"/23'4"	20'4"/23'7"	20'4"/23'7"	23'-25'7"	25'3"	23'-26'3"
Transport width m	2.85	2.85	2.20**/3.00	2.20**/3.00	2.80	2.80	2.80	2.85	2.80
Transport width (ft)	9'4"	9'4"	7'3""**/9'10"	7'3""**/9'10"	9'2"	9'2"	9'2"	9'4"	9'20"
Transport length m(ft)	8.45/27'9"	8.45/27'9"	7.40**/24'3"	7.40**/24'3"	5.90/19'4"	5.90/19'4"	5.90/19'4"	8.90/29'2"	5.95/19'52"
Parking height m	3.45**/4.10	3.45**/4.10	-	-	3.85	3.45***/3.95	3.45**/4.10	3.70**/4.10	3.41/3.90
Parking height (ft)	11'3"/13'5"	11'3"/13'5"	-	-	12'8"	11'4"/13"	11'4"/13'5"	10'6"/13'5"	11'2"/12'10"
Weight appr. Kg(lbs)	1930/4255	1740/3836	1400/3086	1350/2976	1640/3615	1680/3704	1640/3615	2160/4762	2065/4553
Swath width m					1.20-1.90	1.20-2.20	1.30-1.90		1.20-2.20
Swath width(ft)					3'11"-6'3"	3'11"-7'3"	4'3"-6'3"		3'11"-7'3"
Capacity theor. (ha/h)	7.6/8.7	7.6	7.3	7.3	7.5	7.5	8.4	8.5	8.8
Attachment to Tractor									
3-pt. tracking (cat.)	-	-	-	-	-	-	-	-	-
Lower links (2-pt.)	●	●	-	-	●	●	●	●	●
Linkage drawbar	-	-	●	●	-	-	-	-	-
Gauge wheel 16°	-	-	●	○	-	-	-	-	-
Rotors/Arms/Tines									
Rotor diameter m(ft)	3.35/11'	3.35/11'	2.95/9'8"	2.95/9'8"	3.00/9'10"	3.00/9'10"	3.35/11'	3.65/12'	3.35/11'
Swath presentation	Left	Left	Left	Left	Centre	Centre	Centre	Left	Centre
Number of rotors	2	2	2	2	2	2	2	2	2
Number of tine arms per rotor	11/12	11/12	11/12	11/12	11	11	11	12/13	2x12
Number of Duo tines per arm	4/5	4/5	4	4	4	4	4	4/5	4
Tine diameter (mm)	9	9	9	9	9	9	9	10	10
Continuous cam track adjust.	-	-	-	-	-	-	-	●	●
Detachable tine arms	●	●	●	●	-	-	●	●	● (4)
Height adjustment	Mech.	Mech.	Mech.	Mech.	Mech.	Mech.	Mech.	Mech.	Mech. /opt. hydr.

Model	Double Rotor Rakes								
	9469 S	9469 S	9471 S	9471 S	9472 C	9472 C	9476 C	9577 S	9580 C
	Vario	Evo	Vario	Evo		Hydro			
Wheels and axles									
Tyres (rotor)	16x6.50-6	16x6.50-6	18.5x8.50-8	18.5x8.50-8	16x6.50-6	16x6.50-6	16x6.50-6	16x6.50-6	16x6.50-6
Fixed tandem axle	-	-	○	○	○	○	○	-	○
Pivoting tandem axle	-	-	-	-	-	-	-	-	-
Stand. tyres (carrying frame)	10.0/75-15.3	10.0/75-15.3	-	-	10.0/75-15.3	10.0/75-15.3	10.0/75-15.3	380/55-17	380/55-17
Opt. tyres (carrying frame)	-	-	-	-	-	-	-	-	-
Further optional equipment									
Carrier arm compensating	-	-	-	-	-	-	-	-	-
Locking catch for slopes	-	-	-	-	-	-	-	-	-
Safety accessories									
Warning panels	●	●	●	●	●	●	●	●	●
Lighting equipment	●	●	●	●	●	●	●	●	●

- Standard equipment
- Option
- Not available
- * Double swath
- ** With detached tine arms
- *** Hydraulically lowered mainframe

TECHNICAL DATA

Model	Double Rotor Rakes			Four Rotor Rakes		
	9584 C	9590 C	95110 C	94125 C	95130 C	97150 C
Hydro/Pro						
Dimensions & Weight						
Working width m	7.60-8.40	8.00-9.00	9.20-11.0	10.00-12.50	10.00-12.50	9.80-15.00
Working width (ft)	24'11"-27'7"	26'3"-29'6"	30'2"-36'1"	32'10"-41'	32'10"-41'	32'2"-49'3"
Transport width m	2.98	2.98	2.98	2.99	2.99	2.99
Transport width (ft)	9'9"	9'9"	9'9"	10'	9'10"	9'10"
Transport length m(ft)	6.25/20'6"	6.25/20'6"	7.40/23'3"	8.75/28'8"	8.75/28'8"	9.85/32'4"
Parking height m	3.45**/4.10	3.50**/3.98	3.45**/5.00	3.45/3.99	3.45/3.99	3.45**/4.00
Parking height (ft)	11'4"/13'5"	11'6"/13'1"	11'4"/16'5"	11'4"/13'1"	11'4"/13'1"	11'4"/13'1"
Weight appr. Kg(lbs)	1950/4300	2350/5181	2865/6316	4300/9480	4700/10362	6000/13228
Swath width m	1.40-2.10	1.40-2.40	1.40-2.70	1.20-2.20	1.20-2.20	1.40-2.50
Swath width(ft)	4'7"-6'11"	4'7"-7'10"	4'7"-10'2"	3'11"-7'3"	3'11"-7'3"	4'7"-8'2"
Capacity theor. (ha/h)	9.2	9.9	12.0	13.8	13.8	16.5
Attachment to Tractor						
3-pt, tracking (cat.)	-	-	-	-	-	-
Lower links (2-pt.)	●	●	●	●	●	●
Linkage drawbar	-	-	-	-	-	-
Gauge wheel 16°	-	-	-	-	-	-
Rotors/Arms/Tines						
Rotor diameter m(ft)	3.65/12'	3.85/12'8"	4.55/14'11"	3.05-3.35/10'-11'	3.05-3.35/10'-11'	3.85/12'8"
Swath presentation	Centre	Centre	Centre	Centre	Centre	Centre
Number of rotors	2	2	2	4	4	4
Number of tine arms per rotor	2x12	2x14	2x15	4x12	4x12	13/15
Number of Duo tines per arm	4	4	4	4	4	4/5
Tine diameter (mm)	10	10	10	9	10	10
Continuous cam track adjust.	●	●	●	-	●	●
Detachable tine arms	●	● (4)	●	●	● (4)	● (4)
Height adjustment	Mech.	Mech. /Pro - el.	Hydr.	Mech.	Mech.	Hydr.

Model	Double Rotor Rakes			Four Rotor Rakes		
	9584 C	9590 C	95110 C	94125 C	95130 C	97150 C
Hydro/Pro						
Wheels and axles						
Tyres (rotor)	16x6.50-6	16x6.50-6	16x6.50-6	16x6.50-6	16x6.50-6	16x6.50-6
Fixed tandem axle	○	○	●	-	-	Terra
Pivoting tandem axle	-	-	-	○	○	Contact
Stand. tyres (carrying frame)	380/55-17	380/55-17	380/55-17	500/50-17	500/50-17	560/60x22.5
Opt. tyres (carrying frame)	-	-	-	-	-	-
Further optional equipment						
Carrier arm compensating	○	●	●	○	○	●
Locking catch for slopes	-	-	-	-	-	-
Safety accessories						
Warning panels	●	●	●	●	●	●
Lighting equipment	●	●	●	●	●	●

- Standard equipment
- Option
- Not available
- * Double swath
- ** With detached tine arms
- *** Hydraulically lowered mainframe

Information provided in this brochure is made for general information purposes only and for worldwide circulation. Inaccuracies, errors or omissions may occur and the information may thus not constitute basis for any legal claim against Kverneland Group. Availability of models, specifications and optional equipment may differ from country to country. Please consult your local dealer. Kverneland Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations. Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purposes, please contact proper assistance or supervision of a technical assistant. © Kverneland Group Kerteminde AS

WHEN FARMING MEANS BUSINESS

kverneland.com

