

Efficient Mowing - Low Power Input



Kverneland 4132 L – 4140 L

Designed For Smaller Tractors



User-Friendly Trailed Disc Mower

Kverneland 4132 L – 4140 L are easy to operate and have a low power requirement, allowing the mowers to be used with smaller tractors. Based on a responsive floatation system these trailede mowers have a remarkable ability to adapt to the ground structure which improves the grass flow and provides a gentler handling of the crop. It also protects the cutterbar from unforeseen obstacles which may occur.



Swivel hitch gearbox with standard 2pt lower linkage connection.

Swivel Hitch Gearbox

The gearbox is fixed to the mainframe in order to ensure less movement during operation. Yet it provides unlimited rotational movement between the machine and the tractor, and thus makes it easier to perform sharp turns.



Swivel hitch gearbox with optional clevis connection.

Built To Work As Hard As You!

The 4100 L series mowers are built around the Kverneland cutterbar which has several unique design features, including the well established round discs for a clean and aggressive cut and an extremely strong, fully welded cutterbar housing which eliminates oil leaks. The gear wheels, with their unique rounded design, are tooled to perfection for silent, yet reliable power transmission.



Fully welded cutterbar with overlapping C-profiles for a very strong and stiff construction.

- **Working widths: 10'6" (3.2m) - 13'1" (4.0m).**
- **Swivel hitch gearbox.**
- **Easy to connect to tractor.**
- **Outstanding ground following ability.**
- **Easy to operate.**
- **Fully welded Kverneland cutterbar.**

Sideward Adaption

Kverneland 4100 L series has a sideward adaption ability of 8.5° up and down - in total 17°. This generates many benefits when working on hillsides or along ditches, and also makes it easier to control the unit on headlands.



Active Suspension

These mowers are characterized by an exceptional ability to adapt to the ground conditions and thus ensures an even pressure across the entire cutterbar in uneven conditions. The range is 1'2" (350mm) upwards and 9" (235mm)downwards.



Cutterbar Protection

Both mowers have a built-in protection for the Kverneland cutterbar. When encountering an obstacle the unit is forced upwards and over the obstacle. Once the unit has passed the obstacle it will return to the original working position.



Narrow transport

The 4100 L series offers a secure and convenient transport solution with a good overview backward during transport. To make transport width as narrow as possible the side guards are folded upwards. This reduces the transport width for 4132 L to 9'10" (3.0m) and 12'5" (3.8m) for 4140 L.



Kverneland 4100 L Series offer a secure and convenient transport solution with a good overview backward during transport.

Technical Specifications

Type	4132 L	4140 L
Working Width (ft/m)	10'6" (3.2)	13'1" (4.0)
Transport Width (ft/m)	9'10" (3.0)	12'5" (3.8)
Weight Appr. (lbs/kgs)	2513 (1140)	2256 (1250)
PTO (Rpm)	540 / 1000	540 / 1000
Number of Discs	8	10
Number of Knives	16	20
Operating Angle	-17° / +17°	-17° / +17°
Power Req. (kW/hp)	48 / 65	63 / 85
Optional Equipment		
Hitch, Clevis connection	○	○
Swath Roller (RH)	○	○
High Skids +0,8/+1,6/+3,2 (+20/+40/+80mm)	○	○

• = Standard ○ = Optional

Information provided in this brochure is made for general information purposes only and for worldwide circulation. Inaccuracies, errors or omissions may occur and the information may thus not constitute basis for any legal claim against Kverneland Group. Availability of models, specifications and optional equipment may differ from country to country. Please consult your local dealer. Kverneland Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations. Safety devices may have been removed from the machines for illustration purposes only, in order to better present functions of the machines. To avoid risk of injury, safety devices must never be removed. If removal of safety devices is necessary, e.g. for maintenance purpose, please contact proper assistance or supervision of a technical assistant. © Kverneland Group Kerteminde A/S



Kverneland Group

Kverneland Group is a leading international company developing, producing and distributing agricultural machinery and services.

Strong focus on innovation allows us to provide a unique and broad product range with high quality. Kverneland Group offers an extensive package aimed at the professional farming community, covering the areas of soil preparation, seeding, forage and bale equipment, spreading, spraying and electronic solutions for agricultural tractors and machinery.

Original Spare Parts

Kverneland Group spare parts are designed to give reliable, safe and optimal machinery performance - whilst ensuring a low cost life-cycle. High quality standards are achieved by using innovative production methods and patented processes in all our production sites.

Kverneland Group has a very professional network of partners to support you with service, technical knowledge and genuine parts. To assist our partners, we provide high quality spare parts and an efficient spare parts distribution worldwide.



Watch us on YouTube
www.youtube.com/kvernelandgrp



Like us on facebook
www.facebook.com/KvernelandGroup
www.facebook.com/iMFarming



Follow us on Twitter
[@KvernelandGroup](https://twitter.com/KvernelandGroup)
[@iM_Farming](https://twitter.com/iM_Farming)

MEMBER OF



www.kverneland.com

