

DISCOMIX

**Shallow cultivation
disc harrows
mounted and traile**



for tractors from **90 to 210 HP**

DISCOMIX

Discomix mounted and trailede

Efficiency and versatility

**The experience
of Grégoire Besson
makes it possible
to offer a product
dedicated
for shallow
cultivations
in various
types of soils.**



Polyvalency

Destruction of the residues :

- "stale seedbed"
- harvesting residues
- crop residues

Discing depth from 4 to 9 cm

Good seed bed preparation

- helps for "stale seedbed"
- Works on ploughed ground (secondary cultivation)

Consolidation

Mix "green" fertiliser residues into the soil (manure, mud, ...)

Disc

Wide diameter : 630 mm

- useful to work in presence of residues
- stepless working depth
- bearing protected against impacts

"Flat" profil:

- aggressivity
- reduce the risk of sticking
- less pulling effort

Bearing

Dustproof seals

Possibility to change the grease

Relief valve in case of grease excess

Duo disc :

- risk of blockage reduced
- good balance of the stress on the bearing



Device protection

Roll Choc protection :

- wide caoutchouc sausage
- raising height + 20 cm
- no maintenance,
- high level of reliability

Regular working depth,
whatever the working speed

Makes possible to work
in medium stony condition

Weight/disc

Regular working depth

High level of penetration

Able to work in heavy soil

Finish

Residues crushed

Good mixing

Consolidation

- different rollers available
- optimum seed bed preparation
- contact seed/ground improved, ideal for false seedbed
- Levelling of the soil

Deflector : perfect overlapping

DISCOMIX

Discomix fully mounted
Manoeuvrability and polyvalence

Discomix P

**is the right tool
for various tasks :
stubble harrow,
stale seedbed,
work after
ploughing,
seedbed
preparation.**



Fixed frame

Compact chassis : 3,00, 3,50 and 4,00 m

Easy to handle

Foldable roller in transport:

- reduce the stress for the lift arms
- compact implement

Better weight balance

Hydraulic adjustment of the working depth

Foldable chassis

Transport width 2,50 m

High output : working width
4,00, 5,00 and 6,00 m

Trailed discomix

Wide working width and versatility

Discomix SP offers a high level of output.

**Equiped with the Diamond roller,
it will be your right partner,
for your soil
preparation.**



Maxi'Control

Hitch on tractor arms

Hydraulic compensation kit on drawbar = optimum weight transfert

Hydraulic control of the working depth of the rear roller

Discomix SP is held on both ends = precise working depth and stability

Transport

Transport width 2,50 m

Folding and unfolding are carried out automatically from the cab

Pneumatic or hydraulic breaks

2 configuration available

Wheels in the center:

- possibility to work with the wheels in case of difficult soil conditions
- possibility to work with or without the rear roller

Wheels at the rear:

- combination with heavy packer roller (emopak)


DISCOMIX

Discomix mounted and trailede

High output and versatility



Technical specifications



Discomix mounted (fixed frame)

24	230 mm	3,00 m	3,00 m	2400	90 HP
28		3,50 m	3,50 m	2550	110 HP
32		4,00 m	4,00 m	2700	130 HP

Discomix mounted (foldable chassis)

32	230 mm	4,00 m	2,80 m	3250	100 HP
40		5,00 m		3550	120 HP
48		6,00 m		3950	140 HP

Discomix trailede (wheels at the rear)

32	230 mm	4,00 m	2,80 m	5900	140 HP
40		5,00 m		6400	170 HP
48		6,00 m		6900	210 HP

Discomix trailede (wheels in the center)

32	230 mm	4,00 m	2,80 m	5600	130 HP
40		5,00 m		6200	160 HP
48		6,00 m		6800	190 HP

Weights, dimensions and HP requirements are indicative only, subjects to variations according to options, type of soil, design modifications.


Genuine Grégoire Besson wearing parts :

the simplest way to achieve high output


For its wearing parts, Grégoire Besson uses the best technologies to reach higher quality. Parts are designed to be easy to pull, to ensure penetration and to lead to the top of the range ploughing.

	Discomix	Discomix R	Discomix SP	Discomix SPRC
Emopak profil "V" Ø 600 ou 740 mm	-	-	•	-
Emopak flat profil Ø 600 mm	-	-	•	-
Crumbler Ø 500 mm	Standard	Standard	Standard	Standard
Crumbler Ø 600 mm	•	•	•	•
Diamond	•	•	•	•
Emopak F	•	-	-	-


Emopak flat and "V" profil



Crumbler



Diamond



Emopak F



www.gregoire-besson.com

Authorized dealer

GRÉGOIRE BESSON

49230 Montfaucon-Montigné | France
Tél. +33 (0)2 41 64 72 67 | Fax +33 (0)2 41 64 67 73
contactfr@gregoirebesson.fr