

# CORVUS VKE

RABE TECHNOLOGY

POWER HARROWS RABE TECHNOLOGY

**Corvus VKE | Corvus VKE K**



FOR TRACTORS FROM 100 TO 350 HP

## Corvus VKE

Power harrows Rabe Technology

# CORVUS VKE and VKE K

Due to its external development, and in particular through the take-over of the Rabewerk German company, Grégoire-Besson has completed its range of products with power harrows. These power harrows benefit from the German know-how and experience, allowing Grégoire-Besson to offer a performant, enduring and proven range of machines.



### High-positioned reinforced driving system:

- Appropriate to strong-powered tractors
  - No mechanical stress on the cardan during work
- Rear PTO as standard equipment
- Interchangeable pinions on VKE
- 3-speed gear box on VKE K



### Driving system through helical pinions

- For tractor powers up to 350 HP
  - More contact surface area between pinions
  - Pinions are always in touch: better torque output
  - Smoother driving --> less vibrations, less noises
  - Industrial type assembly



### Mounting with double taper rollers

- Resistant to stones
- No deformation problem





- Reinforced assembly with gear teeth at shaft end and on pinion, to let a maximum of power come through
- Single system and high technology

#### One-piece gear housing (tube)

- 8mm thick
- Rigidity and robustness



#### 4 rotors per meter

- Wearing part optimization
- Good clod breaking, particularly in difficult conditions
- Overlapping of the working elements for a homogeneous soil preparation
- Less HP power requirement for the same result
- Perfect levelling
- Machine overall dimensions = worked width

## Corvus VKE

Efficiency, versatility and performance

# CORVUS VKE and VKE K

The power harrows VKE and VKE K (foldable) are available in 3,00 to 8,00m working width. They are ideal for soil preparation after ploughing and for seeding on pre-loosened soils. The VKE range is ultra enduring thanks to its one-piece gear housing (8mm thick) and driving system through helical pinions. **THE WHOLE volume of earth passes through the tines**, which ensures a homogeneous finish.



- Lower link hitch cat. III
- Depth adjustment of the hitch positions (on VKE only)



- Track eradicators, with spring-loaded protection
- Side plates with two positions work / transport (real working width = 3,00m)
- Suspended machine (stone protection springs)




- Wrap around protection bar at front (option)
- No stone jamming under the gear housing
- Efficient protection of bearings
- The volume of earth is obliged to pass through the rotors



- Rear clod bar, adjustable by means of spindle (option)
- Curved shape, to make the earth evacuation easier



- Rear three-point linkage reinforced with single-acting central ram (option)
- Multi-position arms, with height and depth adjustment
- High lift capacity (over 2 Tonnes) on the whole ram stroke



### Suspended gear housing

The stone protection spring operates as a safety device against obstacles (option)

- When tripping, the gear housing releases, taking support on the roller



## Corvus VKE





A large and full range

# CORVUS VKE

This range is appropriate to the strongest tractor powers, and the assembly of **4 rotors per meter** meets requirements concerning output and working quality.



### Technical specifications

			 max.	KG
CORVUS VKE (FIXED)				
3.00	3.00	4	280	1200
4.00	4.00			1600
CORVUS VKE K (CAN BE FOLDED)				
4.00	> 3m	4	380	2150
4.50				2300
5.00				2500
6.00				2850
8.00				3600

## ROLLERS

**Large choice in the rollers to equip the Grégoire-Besson power harrows.**

Packer roller, Grégoire-Besson know-how:

- Precision steel tube (no roundness imperfection)
- Rows of packer tines, with a spacing of 125mm --> High seeding precision
- The packer tines are treated and welded on both sides of the roller

	VKE		VKE K				
	3	4	4	4.5	5	6	8
<b>Crumbler roller D. 540</b>	•	•	•	•	•	•	-
<b>Packer roller D. 510</b>	•	•	•	•	•	•	-
<b>Mulch packer D. 500</b>	•	-	-	-	-	•	-
<b>Furrow packer RIPA D. 580</b>	•	•	•	•	•	•	•

• : available / - : not available

Packer roller

Crumbler roller

Furrow packer RIPA


## TINES AND TINE-HOLDERS



### Bolted tines (standard). Multi-Fix version adaptable

- Multi-Fix support can be bolted on the tine-holder
- Multi-Fix tines, with Quick-Change fittings (option)
- Tine fixation by means of axles and pins
- The tine is entirely blocked in its support

## RABID HARD COATING



RABID hard coating:  
Grégoire-Besson exclusivity

- Long-lasting improved (up to 3 times longer) than a normal tine
- Solid binding of hard coating on base material
- Coating thickness = 2mm
- Regular and homogeneous treatment on all the surface
- No additional tractor power is required



A l'épreuve du temps

**GRÉGOIRE-BESSON**

49230 Montfaucon-Montigné - France  
Tél. (+33) 2 41 64 72 67  
Fax (+33) 2 41 64 67 73  
contactfr@gregoirebesson.fr

**GREGOIRE-BESSON UK LIMITED**

Spalding Road  
Bourne  
Lincs. PE10 0AU - England  
Tel : 01778 423787  
Fax. : 01778 394431  
enquiries@gregoire-besson.co.uk

**GRÉGOIRE-BESSON CANADA INC**

4480, Rue Martineau  
St Hyacinthe (P. Québec) J2R 1V1 - Canada  
Tel (1) 450 799 56 15  
info@gregoirebesson.ca

**GREGOIRE-BESSON GmbH**

Am Rabewerk 1  
D - 49152 Bad Essen - Germany  
Tel (+49) 5472-771 0 / (+49) 5472-771 190  
E-mail : info@rabe-agri.eu

**ГРЕГУАР-БЕССОН ВОСТОК**

Россия 308006 г. Белгород,  
ул. Корочанская, 132а  
Тел/факс: +7(4722) 58 70 36  
Тел: +7(4722) 58 70 35

**ТОВ «ГРЕГУАР-БЕССОН УКРАЇНА»**

18028, Україна, Черкаська обл.,  
м. Черкаси, вул. Рози Люксембург, буд. 202.  
UKRAINE  
тел. : +38 (0472) 71-28-23  
факс: +38 (0472) 71-28-23  
gregoirebesson.ua@yandex.ua

**GREGOIRE-BESSON POLSKA Sp.zo.o.**

Kowanówko  
ul. Obornicka 1a  
64-600 Oborniki - Polska  
Tel/fax : 067 261 97 79  
gbesson@poczta.onet.pl

**GREGOIRE-BESSON BEIJING OFFICE**

法国格力格尔-贝松公司北京代表处  
100025北京市朝阳区延静里中街3号 长信大厦220室  
Tel: 010-65 08 06 40; Fax: 010-65 08 06 41.

**www.gregoire-besson.com**