

ATLAS JSV

LEARN MORE AT GRAVELY.COM

Crew Worthy. Field Ready.

Packed with power and torque, the Atlas JSV® features heavy-duty suspension. Haul, tow, work, dump—this ultimate job site vehicle seats three to six, comfortably.



SUSPENSION the heavy-duty de Dion suspension minimizes sag, to maintain full ground clearance even with cargo, tongue weight and towing maxed out.

POWER choose the 3-cylinder, 1028cc Kohler Diesel engine to maximize torque and traction. Or run with an electronically fuel-injected DOHC gasoline engine.

CAPACITY with bed capacity of 1250 lbs. and a 1900-lb. total payload, the Atlas JSV holds its own, and then some.

ALL-STEEL JOBOX the Atlas JSV's fabricated all-steel cargo bed won't buckle or bend. Dump cargo with the touch of a button and haul a fully loaded pallet, thanks to a generous 18 cubic feet of cargo space.

SEATING the Atlas JSV-3000 seats three adults comfortably, with a total payload capacity of 1,900 lbs. The crew-size JSV-6000 seats six adults across two benches, with a total payload of 2,100 lbs.

TOWING the Atlas JSV can tow a ton. Literally. Hitch up a full 2000 lbs. of trailer and cargo and you'll get more done in less time.



See your professional
Gravely® dealer for complete
warranty details.



GRAVELY



ATLAS JSV 3000



ATLAS JSV 6000

	3000 GAS	6000 GAS	3000 DIESEL	6000 DIESEL
MODEL NUMBER	996200	996201	996202	996203
ENGINE	POLARIS® 1-CYLINDER, DOHC, GAS	POLARIS® 1-CYLINDER, DOHC, GAS	KOHLER® 3-CYLINDER DIESEL	KOHLER® 3-CYLINDER DIESEL
HORSEPOWER	40 HP	40 HP	24 HP	24 HP
DISPLACEMENT (CC)	570 CC	570 CC	1028 CC	1028 CC
DRIVE SYSTEM	ON-DEMAND TRUE AWD/2WD/VERSATRAC TURF MODE			
FUEL CAPACITY	10 GAL.			
GROUND SPEED (Approx. Mph)	35 MPH			
STARTER	ELECTRIC IGNITION			
TIRES & WHEELS				
FRONT & REAR TIRES	25 X 10 CARLISLE ALL TRAIL I (FRONT) / 25 X 11 CARLISLE ALL TRAIL II (REAR)			
FRONT & REAR WHEELS	12 X 6 STEEL (FRONT) / 12 X 8 STEEL (REAR)			
FEATURES				
BED LIFT	ELECTRIC			
FRONT BUMPER	STANDARD, HEAVY DUTY			
HITCH	STANDARD, HEAVY DUTY			
ROPS	ACCORDING TO ANSI/OPEI B71.9, OSHA 1928.53			
VEHICLE DIMENSIONS				
WEIGHT	1,575 LBS.	1,800 LBS.	1,675 LBS.	1,900 LBS.
LENGTH	128 IN.	165 IN.	128 IN.	165 IN.
WIDTH	64 IN.			
HEIGHT	73.5 IN.			
WHEEL BASE	84 IN.	116 IN.	84 IN.	116 IN.
GROUND CLEARANCE	10 IN.			
WARRANTY				
UNIT	1 YEAR LIMITED COMMERCIAL			
INSTRUMENTATION				
SPEEDOMETER, TACHOMETER, FUEL GAUGE, HOUR METER, ODOMETER & TRIP METER, GEAR INDICATION, GLOW PLUG INDICATOR LIGHT* & ENGINE OIL PRESSURE* (*DIESEL MODELS ONLY), SEAT BELT REMINDER LIGHT, BATTERY VOLTAGE CHARGE SYSTEM, ENGINE/COOLANT TEMP, 2 IN-DASH 12V POWER OUTLETS				

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2018 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.



GRAVELY