

PRO-TURN® 200

LEARN MORE AT GRAVELY.COM

Never Cut Expectations.

Smart design and durability are packed into the Pro-Turn 200. Nimble and comfortable, the 200 delivers performance season after season.



X-FACTOR® II DECK is fabricated from top to bottom, providing industrial-strength peace of mind.

MAINTENANCE-FREE SPINDLES with forged aluminum housings for lasting durability.

FLIP-UP SIDE DISCHARGE CHUTE reduces damage to the surrounding environment.

FOOT-OPERATED DECK LIFT SYSTEM provides effortless adjustments between 17 cutting positions in 1/4-inch increments.

CONSTANT BELT TENSION SYSTEM (CBT) ensures belt tension is constant, blade tip speed is consistent and cutting results are right on the money.

FULL SUSPENSION SEAT 200 series seat with integral suspension for added lateral stability and improved durability, plus added vibration control and a 4-inch seat slide for all-day cruising comfort.

FOLDABLE ROPS comes standard to provide extra protection for the operator.

UPDATED DESIGN improves the line of sight for the operator to easily see the deck cutting edge.



NO HOUR LIMIT FIRST TWO YEARS

LIMITED LIFETIME DECK SHELL & FRAME

See your professional Gravely® dealer for complete warranty details.



GRAVELY

	252	260	260	260	260	260	272
MODEL NUMBER	992268	992267	992269	992272	992281	992296	992270
ENGINE	KAWASAKI® FX850V AIR-COOLED HEAVY-DUTY AIR CLEANER	KOHLER® ZT740 AIR-COOLED HEAVY-DUTY AIR CLEANER	KAWASAKI® FX850V AIR-COOLED HEAVY-DUTY AIR CLEANER	KOHLER® EFI ECV860 AIR-COOLED HEAVY-DUTY AIR CLEANER	YAMAHA® EFI MXV775 AIR-COOLED HEAVY-DUTY AIR CLEANER	YAMAHA® MX825V AIR-COOLED HEAVY-DUTY AIR CLEANER	KAWASAKI® FX921V AIR-COOLED HEAVY-DUTY AIR CLEANER
HORSEPOWER	27 HP	25 HP	27 HP	29 HP	29 HP	27.5 HP	31 HP
DISPLACEMENT	852 CC	747 CC	852 CC	824 CC	824 CC	824 CC	999 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-5400 TRANSAXLES						
FUEL CAPACITY	13.4 GAL.						
GROUND SPEED (Approx. Mph) (Forward/Reverse)	13 MPH / 6 MPH						
DECK							
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT						
DECK CONSTRUCTION	FABRICATED						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	18,000						
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM						
SPINDLE BEARINGS	BALL BEARING						
DECK ENGAGEMENT	OGURA® GT3.5 ELECTRIC CLUTCH						
CUTTING WIDTH	52 IN.	60 IN.	60 IN.	60 IN.	60 IN.	60 IN.	72 IN.
CUTTING HEIGHTS	1.5 IN. - 5.5 IN.						
CUTTING POSITIONS	17						
WHEELS							
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES						
FRONT	SMOOTH 15 X 6-6						
REAR	TURF 23 X 10.5-12	TURF 24 X 12-12	TURF 24 X 12-12	TURF 24 X 12-12	TURF 24 X 12-12	TURF 24 X 12-12	TURF 24 X 12-12
FEATURES							
SEAT	HIGH BACK W/ FULL SUSPENSION & PADDED ARMRESTS						
FOLDABLE ROPS	STANDARD						
MACHINE							
WEIGHT (W/O FUEL)	1302 LBS.	1322 LBS.	1336 LBS.	1332 LBS.	1355 LBS.	1355 LBS.	1410 LBS.
LENGTH	80 IN.	80 IN.	80 IN.	80 IN.	80 IN.	80 IN.	82 IN.
WIDTH (W/O CHUTE)	55.5 IN.	63 IN.	63 IN.	63 IN.	63 IN.	63 IN.	75 IN.
WIDTH (W/ CHUTE)	67.5 IN.	75 IN.	75 IN.	75 IN.	75 IN.	75 IN.	87 IN.
HEIGHT (W/ ROPS EXT/DOWN)	70 IN. / 47.75 IN.	70 IN. / 47.75 IN.	70 IN. / 47.75 IN.	70 IN. / 47.75 IN.	70 IN. / 47.75 IN.	70 IN. / 47.75 IN.	70 IN. / 47.75 IN.
WARRANTY							
UNIT	5 YEAR / 1250 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS						
DECK SHELL & FRAME	LIMITED LIFETIME						
ATTACHMENTS & ACCESSORIES	3 BUCKET BAGGER (12 BU.), 12V OUTLET, SEAT ISOLATOR KIT, RADIAL DRIVE, TIRES, STRIPING KIT, OPERATOR-CONTROLLED DISCHARGE CHUTE, SEMI-PNEUMATIC FRONT TIRE KIT, HEADLIGHT KIT						

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2018 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

