

PRO-TURN® SERIES

LEARN MORE AT GRAVELY.COM

We've always worked to outperform even the highest commercial demands. The Gravely Pro-Turn series was designed for professionals with industry insight to cut through the clutter and establish itself as the undisputed benchmark.



X-FACTOR® II DECK is fabricated from top to bottom, providing industrial strength peace of mind.

MAINTENANCE-FREE SPINDLES with forged aluminum housings for lasting durability.

FLIP-UP SIDE DISCHARGE CHUTE reduces damage to the surrounding environment.

CONSTANT BELT TENSION SYSTEM (CBT) ensures the belt tension is constant, blade speed is consistent and cutting results are right on the money.

HIGH-BACK INTEGRATED SUSPENSION SEAT enhances operator comfort and reduces fatigue with adjustable arm rests, seat isolators and large diameter steering arms.

FOLDABLE ROPS comes standard to provide extra protection for the operator.

UPDATED DESIGN Improves the line of sight for the operator to easily see the deck cutting edge.

FOOT-OPERATED DECK LIFT SYSTEM provide effortless adjustments between 17 cutting positions in $\frac{1}{4}$ " increments.



See your professional Gravely® dealer for complete warranty details.



PRODUCT NAME	PRO-TURN 48	PRO-TURN 52	PRO-TURN 60	PRO-TURN 48	PRO-TURN 52	PRO-TURN 60
MODEL #	991215 / 991221*	991216 / 991222*	991217 / 991223*	991218	991219	991220
ENGINE	Kawasaki® FS691V	Kawasaki® FS691V	Kawasaki® FS730V	Kohler® ZT730	Kohler® ZT730	Kohler® ZT740
			Air-cooled, Vertical twin			
HORSEPOWER	23 hp	23 hp	24 hp	23 hp	23 hp	25 hp
DISPLACEMENT	726 cc	726 cc	726 cc	747 cc	747 cc	747 cc
DRIVE SYSTEM			Hydro-Gear® ZT-3200 Transaxles			
FUEL CAPACITY			10 Gallon (37.8 L)			
GROUND SPEED (APPROX. MPH) (FWD/REV)			9 mph/5 mph			
STARTER			Electric			
DECK MATERIAL			10 ga. steel w/.25" Spindle Reinforcement			
DECK CONSTRUCTION			Fabricated			
NUMBER OF SPINDLES			3			
BLADE TIP SPEED (FPM)			18,000			
SPINDLE MATERIAL			Forged Aluminum			
SPINDLE SHAFT			Steel			
SPINDLE BEARINGS			Ball Bearing			
DECK DRIVE			Belt			
DECK ENGAGEMENT			Electric Ogura® GT1A			
DECK LIFT SYSTEM			Adj Foot Operated			
CUTTING WIDTH	48 in	52 in	60 in	48 in	52 in	60 in
CUTTING HEIGHTS			1 in - 5 in			
CUTTING POSITIONS			17			
WHEELS FRONT AXLE			Fixed. Greaseable Caster Fork Tubes			
WHEELS (FRONT)			13 in x 6.50 in - 6 in Smooth			
WHEELS (BACK)			22 in x 10 in - 10 in Turf			
SEAT			High Back Comfort w/ Integrated Suspension			
VIBRATION ISOLATORS			Standard			
HOUR METER			Standard			
ROPS			Foldable			
WEIGHT	964 lbs / 969 lbs*	977 lbs	1006 lbs	953 lbs	966 lbs	995 lbs
LENGTH			78.5 in			
WIDTH W/ CHUTE	62 in	67.5 in	75 in	62 in	67.5 in	75 in
HEIGHT W/ ROPS			70 in			
HEIGHT W/ ROPS FOLDED DOWN			46.7 in			
WIDTH W/ O CHUTE	50 in	55.5 in	63 in	50 in	55.5 in	63 in
WARRANTY (UNIT)			2 Year / 1000 hr. Limited Commercial			
ATTACHMENTS & ACCESSORIES	MULCHING KIT, DISCHARGE COVER KIT, HUB CAP KIT, SOLID TIRE KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, POWERED BAGGER KIT					

GRAVELY.COM

An *Ariens* Company Brand

© Copyright 2018 Ariens Company All rights reserved. Registered trademark and™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

