

PRO-TURN®

LEARN MORE AT [GRAVELLY.COM](https://www.gravelly.com)

Z

Performance From Beginning To End.

The Gravelly Pro-Turn Z series packs commercial grade features into every inch of this durable workhorse. The Pro-Turn Z ships standard with ROPS, seat isolators, and a full commercial warranty. Plus, it inherits the unparalleled durability of the Gravelly line, maximizing runtime and performance.



SEATING SYSTEM the high-back seat features arm rests, seat isolators and large-diameter steering arms to reduce fatigue and provide all-day comfort.

DECK LIFT SYSTEM effortless foot-operated system offers 15 cutting positions in .25-inch increments.

DISCHARGE CHUTE The flip-up side discharge chute is designed to avoid potential damage to the surrounding environment.

CBT SYSTEM our exclusive Constant Belt Tension System (CBT) ensures that belt tension is constant, keeping the blade tip speed and cutting results consistent.

FOLDABLE ROPS comes standard to provide extra protection for the operator.



See your professional Gravelly® dealer for complete warranty details.



| 52 | | 60 | |
|---|--|-----------------|--|
| MODEL NUMBER | 991188 | 991190 | |
| ENGINE | GRAVELY | | |
| HORSEPOWER | 26.5 HP | | |
| DISPLACEMENT | 764 CC | | |
| DRIVE SYSTEM | HYDRO-GEAR® ZT-3100 TRANSAXLES | | |
| FUEL CAPACITY | 5.0 GAL. | | |
| GROUND SPEED <i>(Approx. Mph) (Forward/Reverse)</i> | 7.5 MPH / 4 MPH | | |
| DECK | | | |
| DECK MATERIAL | 10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT | | |
| DECK CONSTRUCTION | FABRICATED | | |
| NUMBER OF SPINDLES | 3 | | |
| BLADE TIP SPEED <i>(FPM)</i> | 17,500 | | |
| SPINDLE HOUSING MATERIAL | FORGED ALUMINUM | | |
| SPINDLE BEARINGS | BALL BEARING | | |
| DECK ENGAGEMENT | ELECTRIC OGURA® GT1.5 | | |
| CUTTING WIDTH | 52 IN. | 60 IN. | |
| CUTTING HEIGHTS | 1.5 IN. - 5.0 IN. | | |
| CUTTING POSITIONS | 15 | | |
| WHEELS | | | |
| FRONT AXLE | FIXED | | |
| FRONT | SMOOTH 13 X 6.50-6 | | |
| REAR | TURF 22 X 10.5-12 | TURF 22 X 12-12 | |
| FEATURES | | | |
| SEAT | HIGH BACK COMFORT W/ INTEGRATED ISOLATION | | |
| FOLDABLE ROPS | STANDARD | | |
| MACHINE | | | |
| WEIGHT | 932 LBS. | 953 LBS. | |
| LENGTH | 81 IN. | | |
| WIDTH <i>(W/O CHUTE)</i> | 55 IN. | 63 IN. | |
| WIDTH <i>(W/ CHUTE)</i> | 67 IN. | 75 IN. | |
| HEIGHT <i>(W/ ROPS EXT/DOWN)</i> | 72 IN. / 52 IN. | | |
| WARRANTY | | | |
| UNIT | 4 YEAR / 750 HOUR LIMITED | | |
| ATTACHMENTS & ACCESSORIES | | | |
| MULCHING KIT, DISCHARGE COVER KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUN SHADE KIT, POWERED BAGGER KIT, OPERATOR CONTROLLED DISCHARGE CHUTE | | | |

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2018 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

