

ZT XL

LEARN MORE AT GRAVELY.COM

Built For Big Jobs.

Cut any acreage down to size with the professional-grade quality of the ZT XL. With finely tuned cutting precision and power, you'll do more with the ZT XL.



FULLY WELDED TUBULAR FRAME this fully fabricated tubular frame is welded into a single piece, providing a strong, stable backbone you won't get from a competitive bolted, multi-sectional frame.

11-GAUGE FABRICATED DECK drop this 11-gauge steel deck and it won't let you down. The 4 1/2-inch-deep design delivers adequate airflow to handle challenging mowing conditions, delivering professional-grade cut quality and durability.

SEATING COMFORT this plush high-back seat with cut and sewn armrests ensures upgraded comfort for longer mowing sessions.

HYDRO-GEAR ZT-2800 TRANSMISSION The Hydro-Gear® ZT-2800 transmission provides increased torque, a smoother ride and longer life.

COMMERCIAL ENGINE OPTIONS Kawasaki® provides the same power, durability and dependability trusted by professional cutters every day. Meanwhile, the Kohler® 7000 Series™ with Smart Choke™ technology is ready to run as soon as you turn the key.

TIRES roll right by the competition with 20" drive tires and 11" x 6" front caster wheels – designed to provide better traction, control and handling.



NO HOUR LIMIT

FIVE YEAR DECK SHELL & FRAME

See your professional Gravely® dealer for complete warranty details.



GRAVELY

	42	42	52	52	60	60
MODEL NUMBER	915202	915206	915200	915204	915216	915218
ENGINE	KOHLER® 7000 SERIES HD V-TWIN W/ SMART CHOKE™	KAWASAKI® FR V-TWIN	KOHLER® 7000 SERIES HD V-TWIN W/ SMART CHOKE™	KAWASAKI® FR V-TWIN	KOHLER® 7000 SERIES HD V-TWIN W/ SMART CHOKE™	KAWASAKI® FR V-TWIN
HORSEPOWER	24 HP	21.5 HP	25 HP	23 HP	26 HP	24 HP
DISPLACEMENT	725 CC	726 CC	725 CC	726 CC	747 CC	726 CC
DRIVE SYSTEM			HYDRO-GEAR® ZT-2800 TRANSAXLES			
FUEL CAPACITY			2.8 GAL.			
GROUND SPEED (Approx. Mph) (Forward/Reverse)			7 MPH / 3 MPH			
DECK						
DECK MATERIAL			11 GA.			
DECK CONSTRUCTION			FABRICATED			
NUMBER OF SPINDLES			3			
BLADE TIP SPEED (FPM)			17,000			
SPINDLE HOUSING MATERIAL			STEEL			
SPINDLE BEARINGS			1 IN. SEALED			
DECK ENGAGEMENT			ELECTRIC WARNER®			
DECK LIFT SYSTEM			FOOT OPERATED, DIAL SELECTION			
CUTTING WIDTH	42 IN.	42 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHT			1.5 IN. - 4.5 IN.			
CUTTING POSITIONS			13			
WHEELS						
FRONT			11 X 6-5			
REAR	20 X 8-10	20 X 8-10	20 X 10-10	20 X 10-10	20 X 12-10	20 X 12-10
FEATURES						
SEAT			HIGH BACK COMFORT, LEVER ADJUST, PADDED ARM RESTS			
HOUR METER			STANDARD			
MACHINE						
WEIGHT	661 LBS.	661 LBS.	679 LBS.	679 LBS.	697 LBS.	697 LBS.
LENGTH			77.5 IN.			
WIDTH	54 IN.	54 IN.	63.4 IN.	63.4 IN.	73.75 IN.	73.75 IN.
HEIGHT			40.9 IN.			
WARRANTY						
UNIT			3 YEAR LIMITED RESIDENTIAL			
DECK SHELL & FRAME			5 YEAR LIMITED			
ATTACHMENTS & ACCESSORIES						
2-BAG POWERED BAGGER, BAGGER ADAPTER (60" MODEL ONLY), MULCH KIT, L.E.D. LIGHT KIT, FLEX-TEND® SHOULDER SUPPORT SYSTEM, CHROME FRONT WHEEL COVERS, CHROME REAR WHEEL COVERS, 48-IN PLUG AERATOR, 36-IN. POLY ROLLER, 48-IN. DETHATCHER, 15-GALLONSPRAYER, TOW-BEHIND SPREADER, TRAILER HITCH KIT						

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2018 AriensCo. All rights reserved. Registered trademark and™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravely.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

