

PRO-TURN[®]

ZX

LEARN MORE AT [GRAVELY.COM](https://www.gravelly.com)

Put Every Penny To Work.

Put every penny to work with the Pro-Turn ZX. This proven design delivers on core components of the Pro-Turn line, providing the performance commercial applications demand while keeping costs in check. And like every Gravelly[®] mower, it comes backed by an unbeatable warranty.



A KAWASAKI[®] FX ENGINE powerful and easy to maintain, this workhorse has a four-stroke, v-twin design with commercial canister air filtration to ensure maximum power and torque even in the toughest conditions.

TRANSMISSION built to perform season after season, the commercial-grade, high-efficiency transmission delivers responsive control.

ROPS safety gets simpler with the foldable Rollover Protection System (ROPS) that's standard on all PT-Series mowers.

SEAT ISOLATION make all-day mowing sessions more comfortable with a plush, high-back seat designed with vibration isolation.

WARRANTY Gravelly delivers performance and backs it up with a full four-year / 750-hour commercial grade warranty.



See your professional Gravelly[®] dealer for complete warranty details.



	48	52	60
MODEL NUMBER	991230	991232	991234
ENGINE	KAWASAKI® FX691V AIR-COOLED, VERTICAL TWIN	KAWASAKI® FX691V AIR-COOLED, VERTICAL TWIN	KAWASAKI® FX730V AIR-COOLED, VERTICAL TWIN
HORSEPOWER	22 HP	22 HP	23.5 HP
DISPLACEMENT	726 CC	726 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3200 TRANSAXLES		
FUEL CAPACITY	5.0 GAL.		
GROUND SPEED (Approx. Mph) (Forward/Reverse)	8.5 MPH / 4 MPH		
DECK			
DECK MATERIAL	10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT		
DECK CONSTRUCTION	FABRICATED		
NUMBER OF SPINDLES	3		
BLADE TIP SPEED (FPM)	17,500		
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM		
SPINDLE BEARINGS	BALL BEARING		
DECK ENGAGEMENT	ELECTRIC OGURA® GT1.5		
CUTTING WIDTH	48 IN.	52 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN. - 5.0 IN.		
CUTTING POSITIONS	15		
WHEELS			
FRONT AXLE	FIXED		
FRONT	SMOOTH 13 X 6.50-6		
REAR	TURF 22 X 10.5-12	TURF 22 X 10.5-12	TURF 22 X 12-12
FEATURES			
SEAT	HIGH BACK COMFORT W/ INTEGRATED ISOLATION		
FOLDABLE ROPS	STANDARD		
MACHINE			
WEIGHT	924 LBS.	932 LBS.	953 LBS.
LENGTH	81 IN.		
WIDTH (W/O CHUTE)	50 IN.	55 IN.	63 IN.
WIDTH (W/ CHUTE)	63 IN.	67 IN.	75 IN.
HEIGHT (W/ ROPS EXT/DOWN)	72.5 IN. / 49 IN.		
WARRANTY			
UNIT	4 YEAR / 750 HOUR LIMITED		
ATTACHMENTS & ACCESSORIES			
2 BUCKET POWERED BAGGER, MULCHING KIT, DISCHARGE COVER KIT, TRAILER HITCH KIT, HEADLIGHT KIT, SUN SHADE KIT, SUSPENSION SEAT KIT, OPERATOR CONTROLLED DISCHARGE CHUTE			

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2018 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

