



**GRAVELY**

PRO-TURN 200 SERIES

COMMERCIAL

GRAVELY.com

# THE BADDEST YOUNGER BROTHER ON THE PLANET



## PRO-TURN® 200 SERIES

Simple math says that 400 is greater than 200 but, this machine is out to prove otherwise. The Pro-Turn 200 has the same DNA, determination and dapper new design as the 400 while delivering signature, Gravely performance.

- **X-Factor II Deck** – Is fabricated from top to bottom, providing industrial strength peace of mind
- **Maintenance-free Spindles** – With cast iron housings for lasting durability
- **Flip-up Side Discharge Chute** – Reduces damage to the surrounding environment
- **Foot-Operated Deck Lift System** – Provide effortless adjustments between 17 cutting positions in  $\frac{1}{4}$ " increments
- **Constant Belt Tension System (CBT)** – Ensures the belt tension is constant, blade speed is consistent and cutting results are right on the money

- **Full Suspension Seat** – 200 series seat with integral suspension for added lateral stability and improved durability, plus added vibration control and a 4-inch seat slide for all-day cruising comfort.
- **Foldable ROPS** – Comes standard to provide extra protection for the operator
- **Updated Design** – Improves the line of sight for the operator to easily see the deck cutting edge



## PRO-TURN 200

| PRODUCT NAME                         | Pro-Turn 260  | Pro-Turn 252      | Pro-Turn 252      | Pro-Turn 252       | Pro-Turn 260     | Pro-Turn 260      | Pro-Turn 260         | Pro-Turn 272     | Pro-Turn 272       |
|--------------------------------------|---|-------------------|-------------------|--------------------|------------------|-------------------|----------------------|------------------|--------------------|
| MODEL NUMBER                         | 992267  | 992268            | 992271            | 992284/<br>992291* | 992269           | 992272            | 992281/<br>992292*   | 992270           | 992295/<br>992283* |
| ENGINE                               | Kohler ZT740  | Kawasaki® FX850V  | Kohler EFI ECV860 | Yamaha EFI MXV775  | Kawasaki® FX850V | Kohler EFI ECV860 | Yamaha EFI<br>MXV775 | Kawasaki® FX921V | Yamaha EFI MXV825  |
| Air-cooled Vertical Twin             |   |                   |                   |                    |                  |                   |                      |                  |                    |
| Heavy-Duty Air Cleaner               |   |                   |                   |                    |                  |                   |                      |                  |                    |
| HORSEPOWER (HP)                      | 25  | 27                | 29                | 29                 | 27               | 29                | 29                   | 31               | 33                 |
| DISPLACEMENT (CC)                    | 747   | 852               | 824               | 824                | 852              | 824               | 824                  | 999              | 824                |
| DRIVE SYSTEM                         | Hydro-Gear® ZT-5400 Integrated pump/motor                   |                   |                   |                    |                  |                   |                      |                  |                    |
| FUEL CAPACITY - GALLONS (LITERS)     | 13.4 (50.7)   | 13.4 (50.7)       | 13.4 (50.7)       | 13.4 (50.7)        | 13.4 (50.7)      | 13.4 (50.7)       | 13.4 (50.7)          | 13.4 (50.7)      | 13.4 (50.7)        |
| GROUND SPEED (APPROX. MPH) (FOR/REV) | 13 mph/6 mph  |                   |                   |                    |                  |                   |                      |                  |                    |
| <b>DECK</b>                          |   |                   |                   |                    |                  |                   |                      |                  |                    |
| DECK MATERIAL                        | 7 ga steel with .25 inch spindle reinforcement              |                   |                   |                    |                  |                   |                      |                  |                    |
| DECK CONSTRUCTION                    | Welded  | Welded            | Welded            | Welded             | Welded           | Welded            | Welded               | Welded           | Welded             |
| NUMBER OF SPINDLES                   | 3   | 3                 | 3                 | 3                  | 3                | 3                 | 3                    | 3                | 3                  |
| BLADE TIP SPEED (FPM)                | 18,348  | 18,348            | 18,633            | 18,633             | 18,633           | 18,633            | 18,229               | 18,229           | 18,633             |
| SPINDLE MATERIAL                     | Cast Iron   |                   |                   |                    |                  |                   |                      |                  |                    |
| SPINDLE BEARINGS                     | Ball Bearing  |                   |                   |                    |                  |                   |                      |                  |                    |
| DECK ENGAGEMENT                      | Ogura® GT3.5 Electric Clutch                                |                   |                   |                    |                  |                   |                      |                  |                    |
| CUTTING WIDTH (INCHES)               | 60"   | 52"               | 52"               | 52"                | 60"              | 60"               | 60"                  | 72"              | 72"                |
| CUTTING HEIGHTS (INCHES)             | 1.5-5.5"  | 1.5-5.5"          | 1.5-5.5"          | 1.5-5.5"           | 1.5-5.5"         | 1.5-5.5"          | 1.5-5.5"             | 1.5-5.5"         | 1.5-5.5"           |
| CUTTING POSITIONS                    | 17  | 17                | 17                | 17                 | 17               | 17                | 17                   | 17               | 17                 |
| <b>WHEELS</b>                        |   |                   |                   |                    |                  |                   |                      |                  |                    |
| FRONT AXLE                           | Fixed with greaseable caster fork tubes                     |                   |                   |                    |                  |                   |                      |                  |                    |
| FRONT (INCHES)                       | Smooth 15 x 6-6 w/<br>greaseable tapered<br>roller bearings | Smooth 15 x 6-6   | Smooth 15 x 6-7   | Smooth 15 x 6-7    | Smooth 15 x 6-8  | Smooth 15 x 6-9   | Smooth 15 x 6-10     | Smooth 15 x 6-11 | Smooth 15 x 6-12   |
| REAR (INCHES)                        | Turf 24 x 12-12   | Turf 23 x 10.5-12 | Turf 23 x 10.5-12 | Turf 23 x 10.5-12  | Turf 24 x 12-12  | Turf 24 x 12-12   | Turf 24 x 12-12      | Turf 24 x 12-12  | Turf 24 x 12-12    |
| <b>FEATURES</b>                      |   |                   |                   |                    |                  |                   |                      |                  |                    |
| SEAT                                 | High Back w/ Full Air Ride Suspension and seat isolators    |                   |                   |                    |                  |                   |                      |                  |                    |
| HOOD                                 | N/A   | N/A               | N/A               | N/A                | N/A              | N/A               | N/A                  | N/A              | N/A                |
| FOLDABLE ROPS                        | Standard  | Standard          | Standard          | Standard           | Standard         | Standard          | Standard             | Standard         | Standard           |
| <b>MACHINE DIMENSIONS</b>            |   |                   |                   |                    |                  |                   |                      |                  |                    |
| WEIGHT (LBS) W/O FUEL                | 1322  | 1302              | 1166              | 1166               | 1336             | 1232              | 1228                 | 1410             | 1414               |
| LENGTH (INCHES)                      | 80"   | 80"               | 80"               | 80"                | 80"              | 80"               | 80"                  | 82"              | 80"                |
| WIDTH (INCHES) (W/O CHUTE)           | 63 w/o chute  | 55.5"             | 55.5"             | 55.5"              | 63               | 63                | 63                   | 75               | 75                 |
| WIDTH W/ CHUTE                       | 75"   | 67.5"             | 67.5"             | 67.5"              | 75"              | 87"               | 87"                  | 87"              | 87"                |
| HEIGHT W/ ROPS EXT/ DOWN (INCHES)    | 70/47.75  | 70/47.75          | 70/47.75          | 70/47.75           | 70/47.75         | 70/47.75          | 70/47.75             | 70/47.75         | 70/47.75           |
| <b>WARRANTY</b>                      |   |                   |                   |                    |                  |                   |                      |                  |                    |
| UNIT                                 | 2 Year Limited Commercial                                   |                   |                   |                    |                  |                   |                      |                  |                    |
| DECK SHELL & FRAME                   | Limited Lifetime Deck Shell & Frame                         |                   |                   |                    |                  |                   |                      |                  |                    |
| SPINDLES                             | 3 Year Limited Spindle                                      |                   |                   |                    |                  |                   |                      |                  |                    |

Updated 10/16

© Copyright 2016 Ariens Company All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [gravely.com](http://gravely.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

**GRAVELY.com**

An **Ariens** Company Brand