



GRAVELY

PRO-TURN SERIES

COMMERCIAL

GRAVELY.com

BEAUTY, BRAINS AND BRAWN

PRO-TURN® SERIES

We've always worked to outperform even the highest commercial demands. The Gravely Pro-Turn series was designed for professionals with industry insight to cut through the clutter and establish itself as the undisputed benchmark.



- **X-Factor II Deck** – Is fabricated from top to bottom, providing industrial strength peace of mind
- **Maintenance-free Spindles** – With cast iron housings for lasting durability
- **Flip-up Side Discharge Chute** – Reduces damage to the surrounding environment
- **Foot-Operated Deck Lift System** – Provide effortless adjustments between 17 cutting positions in $\frac{1}{4}$ " increments
- **Constant Belt Tension System (CBT)** – Ensures the belt tension is constant, blade speed is consistent and cutting results are right on the money

- **High-back Integrated Suspension Seat** – Enhances operator comfort and reduces fatigue with adjustable arm rests, seat isolators and large diameter steering arms
- **Foldable ROPS** – Comes standard to provide extra protection for the operator
- **Updated Design** – Improves the line of sight for the operator to easily see the deck cutting edge

PRO-TURN

PRODUCT NAME	Pro-Turn 48	Pro-Turn 52	Pro-Turn 60	Pro-Turn 48	Pro-Turn 52	Pro-Turn 60	Pro-Turn 48
MODEL NUMBER	991215	991216	991217	991218	991219	991220	991221*
ENGINE	Kawasaki® FS691V	Kawasaki® FS691V	Kawasaki® FS691V	Kohler ZT730 w/ Heavy-Duty Air Cleaner	Kohler ZT730 w/ Heavy-Duty Air Cleaner	Kohler ZT740 w/ Heavy-Duty Air Cleaner	Kawasaki® FS691V
HORSEPOWER (HP)	23	23	24	23	23	25	23
DISPLACEMENT (CC)	726	726	726	747	747	747	726
DRIVE SYSTEM	Hydro-Gear® ZT-3200 Transaxles	Hydro-Gear® ZT-3200 Transaxles	Hydro-Gear® ZT-3200 Transaxles	Hydro-Gear® ZT-3200 Transaxles	Hydro-Gear® ZT-3200 Transaxles	Hydro-Gear® ZT-3200 Transaxles	Hydro-Gear® ZT-3200 Transaxles
FUEL CAPACITY - GALLONS (LITERS)	10 (37.8)	10 (37.8)	10 (37.8)	10 (37.8)	10 (37.8)	10 (37.8)	10 (37.8)
GROUND SPEED (APPROX. MPH) (FOR/REV)	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric	Electric
DECK							
DECK MATERIAL	10 ga. steel w/ 1/4" spindle reinforcement	10 ga. steel w/ 1/4" spindle reinforcement	10 ga. steel with 10 ga. spindle reinforcement	10 ga. steel w/ 1/4" spindle reinforcement	10 ga. steel w/ 1/4" spindle reinforcement	10 ga. steel with 10 ga. spindle reinforcement	10 ga. steel w/ 1/4" spindle reinforcement
DECK CONSTRUCTION	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated
NUMBER OF SPINDLES	3	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000	18,000	18,000	18,000
SPINDLE MATERIAL	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH (INCHES)	48	52	60	48	52	60	48
CUTTING HEIGHTS (INCHES)	1.0 - 5.0	1.0 - 5.0	1.0 - 5.0	1.0 - 5.0	1.0 - 5.0	1.0 - 5.0	1.0 - 5.0
CUTTING POSITIONS	17	17	17	17	17	17	17
WHEELS							
FRONT AXLE	Fixed. Greaseable caster fork tubes	Fixed. Greaseable caster fork tubes	Fixed. Greaseable caster fork tubes	Fixed. Greaseable caster fork tubes	Fixed. Greaseable caster fork tubes	Fixed. Greaseable caster fork tubes	Fixed. Greaseable caster fork tubes
FRONT (INCHES)	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6
REAR (INCHES)	Turf 22 x 10-10	Turf 22 x 10-10	Turf 22 x 10-10	Turf 22 x 10-10	Turf 22 x 10-10	Turf 22 x 10-10	Turf 22 x 10-10
FEATURES							
SEAT	High Back Comfort w/ Integrated Suspension	High Back Comfort w/ Integrated Suspension	High Back Comfort w/ Integrated Suspension	High Back Comfort w/ Integrated Suspension	High Back Comfort w/ Integrated Suspension	High Back Comfort w/ Integrated Suspension	High Back Comfort w/ Integrated Suspension
VIBRATION ISOLATORS	Standard	Standard	Standard	Standard	Standard	Standard	Standard
HOUR METER	Standard	Standard	Standard	Standard	Standard	Standard	Standard
ROPS	Foldable	Foldable	Foldable	Foldable	Foldable	Foldable	Foldable
MACHINE DIMENSIONS							
WEIGHT (LBS)	1013	1025	1061	1002	1014	1050	1018
LENGTH (INCHES)	78.5	78.5	78.5	78.5	78.5	78.5	78.5
WIDTH (INCHES)	62.25	67.75	75.25	62.25	67.75	75.25	62.25
HEIGHT W/ ROPS (INCHES)	70	70	70	70	70	70	70
HEIGHT W/ ROPS FOLDED DOWN (INCHES)	46.7	46.7	46.7	46.7	46.7	46.7	46.7
WIDTH W/ O CHUTE (INCHES)	50	55.5	63	50	55.5	63	50
WARRANTY							
UNIT	2 Year / 1000 hr. Commercial						
DECK SHELL & FRAME	5 Year Limited Deck Shell & Frame						