



GRAVELY

PRO-WALK SERIES

COMMERCIAL

GRAVELY.com

WALK THE WALK

PRO-WALK® SERIES

Completely redesigned and tough enough to take on any terrain, our Pro-Walk commercial lawn mowers are built for minimal maintenance and maximum performance, so powering across the landscape feels like a walk in the park.



- **Controls** - Intuitive steering shortens the learning curve and provides precise handling while ergonomic controls position the operator in a neutral position to lessen fatigue.
- **Handlebars** - Adjustable handlebars provide four height positions to comfortably accommodate operators of any size.
- **Wide Wheel Base** - Cut with confidence and control with a wide wheel base that provides superior hillside stability.
- **Height of Cut** - A single-point height of cut allows you to control your cutting performance in .25-inch increments.
- **X-Factor® II Deck** - The 7-gauge, all-steel welded X-Factor® II Deck is fabricated from top to bottom, providing industrial-strength peace of mind that's reinforced with an exclusive limited lifetime warranty.
- **Discharge Chute** - The flip-up side discharge chute is designed to avoid potential damage to the surrounding environment.

PRO-WALK

PRODUCT NAME	Pro-Walk 48	Pro-Walk 52	Pro-Walk 60
MODEL NUMBER	98817200	98817300	98817400
ENGINE	Kawasaki® FS600V	Kawasaki® FS600V	Kawasaki® FS691V
HORSEPOWER (HP)	18.5	18.5	23
DISPLACEMENT (CC)	603	603	726
DRIVE SYSTEM	Hydro-Gear® ZT-2800 Integrated pump/motor	Hydro-Gear® ZT-2800 Integrated pump/motor	Hydro-Gear® ZT-2800 Integrated pump/motor
FUEL CAPACITY - GAL-LONS (LITERS)	5.8 (22)	5.8 (22)	5.8 (22)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	7 mph / 3 mph	7 mph / 3 mph	7 mph / 3 mph
STARTER	Electric	Electric	Electric
DECK			
DECK MATERIAL	10 Ga. Steel	10 Ga. Steel	10 Ga. Steel
DECK CONSTRUCTION	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast	Cast	Cast
SPINDLE SHAFT	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A
DECK LIFT SYSTEM	Manual	Manual	Manual
CUTTING WIDTH (INCHES)	48	52	60
CUTTING HEIGHTS (INCHES)	1.5 - 5.0	1.5 - 5.0	1.5 - 5.0
CUTTING POSITIONS (1/4" INCREMENTS)	15	15	15
WHEELS			
FRONT AXLE	Swivel	Swivel	Swivel
FRONT WHEELS	11x4.00-5 Semi-Pneumatic	11x4.00-5 Semi-Pneumatic	11x4.00-5 Semi-Pneumatic
REAR	20 X 8-10	20 X 8-10	20 X 8-10
MACHINE DIMENSIONS			
WEIGHT (LBS)	758	768	788
LENGTH (INCHES)	79	81	83
WIDTH (INCHES)	51	55	63
HEIGHT (INCHES)	44	44	44
WARRANTY			
UNIT	2 Year Limited Commercial		
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame		
SPINDLES	3 Year Limited Spindle		
ATTACHMENTS			
HOUR METER	Standard		
MULCHING KIT	Available		
TWO-WHEEL SULKY	Available		
GRASS COLLECTOR	Grass Catcher Mount - Standard		