

## PRO-WALK



GRAVELY

PRO-WALK SERIES

COMMERCIAL



GRAVELY.com

An **Ariens** Company Brand  
 © Copyright 2016 Ariens Company All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [www.gravely.com](http://www.gravely.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

Mulching Kit, Cloth Grass Collector, Grass Catcher Attachment Bracket, Single Wheel Sulky, Two Wheel Sulky, Operator Controlled Discharge Baffle

PRODUCT NAME	Pro-Walk 32GR	Pro-Walk 36GR	Pro-Walk 48GR	Pro-Walk 36HR PS	Pro-Walk 48HE PS	Pro-Walk 52HE PS	Pro-Walk 61HE PS	Pro-Walk 48HE PS
<b>MODEL NUMBER</b>	988150*	988151*	988152*	988156*	988180	988182	988183	988181*
<b>ENGINE</b>	Kawasaki® FS481V	Kawasaki FS481V	Kawasaki FS481V	Kawasaki FS481V	Kawasaki FS600V	Kawasaki FS600V	Kawasaki FS691V	Kohler® PCV680 EFI LP
<b>HORSEPOWER</b>	14.5	14.5	14.5	14.5	18.5	18.5	23	22
<b>DISPLACEMENT (CC)</b>	603	603	603	603	603	603	726	747
<b>DRIVE SYSTEM</b>	Peerless Gear Drive	Peerless Gear Drive	Peerless Gear Drive	10cc Pumps and 12ci Motors				
<b>FUEL CAPACITY – GALLONS (LITERS)</b>	5.8 gallon (22 L)	5.8 gallon (22 L)	5.8 gallon (22 L)	5.8 gallon (22 L)	5.8 gallon (22 L)	5.8 gallon (22 L)	5.8 gallon (22 L)	5.8 gallon (22 L)
<b>GROUND SPEED (APPROX. MPH FOR/REV)</b>	5.4 mph / Reverse Assist	5.4 mph / Reverse Assist	5.4 mph / Reverse Assist	7 mph / 3 mph				
<b>STARTER</b>	Recoil	Recoil	Recoil	Recoil	Electric	Electric	Electric	Electric
<b>DECK</b>								
<b>DECK MATERIAL</b>	7 ga steel	7 ga steel	7 ga steel	7 ga steel	7 ga steel	7 ga steel	7 ga steel	7 ga steel
<b>DECK CONSTRUCTION</b>	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded
<b>NUMBER OF SPINDLES</b>	2	2	2	2	2	2	2	2
<b>BLADE TIP SPEED (FPM)</b>	18,500	18,152	18,500	18,261	18,220	18,246	18,246	18,220
<b>SPINDLE HOUSING MATERIAL</b>	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
<b>SPINDLE SHAFT</b>	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
<b>SPINDLE BEARINGS</b>	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed	1" Sealed
<b>DECK DRIVE</b>	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt
<b>DECK ENGAGEMENT</b>	Electric Clutch	Electric Clutch	Electric Clutch	Electric Clutch	Electric Clutch	Electric Clutch	Electric Clutch	Electric Clutch
<b>DECK LIFT SYSTEM</b>	Manual	Manual	Manual	Manual	Manual	Manual	Manual	Manual
<b>CUTTING WIDTH</b>	32"	36"	48"	36"	48"	52"	61"	48"
<b>CUTTING HEIGHT</b>	1.5"-4.5"	1.5"-4.5"	1.5"-4.5"	1.5"-5.0"	1.5"-5.0"	1.5"-5.0"	1.5"-5.0"	1.5"-5.0"
<b>CUTTING POSITIONS</b>	13	13	13	15	15	15	15	15
<b>WHEELS</b>								
<b>FRONT AXLE</b>	Swivel	Swivel	Swivel	Swivel	Swivel	Swivel	Swivel	Swivel
<b>FRONT</b>	9 x 3.50	9 x 3.50	9 x 3.50	9 x 3.50	9 x 3.50	9 x 3.50	9 x 3.50	9 x 3.50
<b>REAR</b>	13 x 5	13 x 6.5	13 x 6.5	16 x 6.5	16 x 7.5	16 x 7.5	18 x 8.5	16 x 7.5
<b>FEATURES</b>								
<b>HOOD</b>	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
<b>HOUR METER W/ MAINTENANCE REMINDER</b>	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>MACHINE</b>								
<b>WEIGHT (LBS) W/O FUEL</b>	504	504	572	558	662	686	764	765 w/ full 33.5# LP tank
<b>LENGTH</b>	77"	77"	77"	72"	66"	69"	69"	77"
<b>WIDTH WITH CHUTE</b>	45.7"	48.4"	60.8"	37"	48.5"	52.5"	61.5"	48.5"
<b>HEIGHT W/ ROPS EXT/DOWN</b>	41.9"	41.9"	41.9"	43"	43"	43"	43"	44.5"
<b>WARRANTY</b>								
<b>UNIT</b>	2 Year Limited Commercial							
<b>DECK SHELL &amp; FRAME</b>	Limited Lifetime Deck Shell & Frame							
<b>SPINDLES</b>	2 Year Limited Spindle							
<b>ATTACHMENTS &amp; ACCESSORIES</b>								



See your professional dealer for complete warranty details.