



AN AMERICAN WORKHORSE SINCE 1916

DISCOVER HOW COMPACT SIZE HAS A BIG ADVANTAGE AS YOU MANEUVER THROUGH NARROW GATES AND TIGHT, CONFINED SPACES WITH EASE. EVEN ON THE TRAILER, THIS MACHINE IS SIZED JUST RIGHT WITH ROOM FOR OTHER EQUIPMENT.

PROFESSIONAL



Accessories/ Attachments

Optional:

2-BAG POWERED BAGGER
KIT *(Only on Compact-Pro 44)*

CHROME WHEEL COVERS

DISCHARGE COVER KIT

FLEXTEND™ SHOULDER
SUPPORT SYSTEM

HEADLIGHT KIT

MULCHING KIT

OPERATOR CONTROLLED
CHUTE BAFFLE *(Only on
Compact-Pro 44)*

SEAT SUSPENSION KIT

STRIPING KIT
(Only on Compact-Pro 44)

Grass Catcher
(Only on Compact-Pro 34)

Compact-Pro™ Series

- **Maintenance-free XL Spindles®** with durable cast iron housings ensure lasting performance
- **Quick-release deck lift** makes it easy to change from one cut height to the next with nine cutting positions in 1/2" increments ranging from 1" - 5"
- **Large diameter fuel cap** speeds refueling to increase operator productivity
- **Kawasaki® FX Engine** featuring a heavy-duty canister air cleaner to optimize performance and extend engine life
- **High-back seat** with armrests promote operator comfort
- **Adjustable flip-out control arms** provide easy access to and from the cockpit



COMPACT-PRO™ SERIES

PRODUCT NAME	Compact-Pro 34	Compact-Pro 44
MODEL NUMBER	991088	991089
ENGINE	Kawasaki® FX481 V-Twin	Kawasaki® FX600 V-Twin
	Air-cooled Vertical twin	Air-cooled Vertical twin
	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner
HORSEPOWER	15.5	19
DISPLACEMENT (cc)	603	603
DRIVE SYSTEM	Hydrostatic Hydro-Gear® 10cc Pumps with Hydro-Gear® 12 CI Wheel motors	Hydro-Gear® ZT-3100 Transaxles
FUEL CAPACITY - Gallons (LITERS)	7.3 (27.6)	9.4 (35.6)
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	9 mph / 4.5 mph	8 mph / 4 mph
STARTER	Electric	Electric
DECK		
DECK MATERIAL	7 GA Steel with .25 inch Spindle Reinforcement	10 GA Steel with 7 GA Spindle Reinforcement
DECK CONSTRUCTION	Welded	Welded
NUMBER OF SPINDLES	2	3
BLADE TIP SPEED (FPM)	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt
DECK ENGAGEMENT	Electric Ogura® GT1A	Electric Ogura® GT1A
DECK LIFT SYSTEM	Adjustable Foot Operated	Adjustable Foot Operated
CUTTING WIDTH	34"	44"
CUTTING HEIGHTS	1"-5"	1"-5"
CUTTING POSITIONS	9	9
TIRES		
FRONT AXLE	Fixed	Fixed
FRONT	Smooth 13 x 5-6	Smooth 13 x 5-6
REAR	21 x 7-10	20 x 10-10
FEATURES		
SEAT	High-Back w/ seat springs	High-Back w/ seat springs
HOURLY METER	Standard	Standard
WEIGHT (lbs)	725	800
LENGTH (inches)	71.5	71.5
WIDTH (inches)	35.4 (w/o chute)	46.8 (w/o chute)
HEIGHT	42	42
WARRANTY		
UNIT	2 Year Limited Commercial	
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame	
SPINDLES	3 Year Limited Spindle	

Updated 01/2014

An *Ariens* Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company, Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM