



AN AMERICAN WORKHORSE SINCE 1916

TAKE ON LANDSCAPING WORK WITH A PROFESSIONAL MOWER PERFECT FOR STARTING OUT, ADDING ON, AND SETTING YOURSELF APART IN THE FIELD.

PROFESSIONAL



Accessories/ Attachments

Optional:

2 BUCKET POWERED BAGGER
MULCHING KIT
TRAILER HITCH KIT
OPERATOR CONTROLLED DISCHARGE CHUTE
DISCHARGE COVER KIT
VACUUM BAFFLE KIT
SUNSHADE
STRIPING KIT
FLEXTEND® SHOULDER SUPPORT SYSTEM
CHROME WHEEL COVERS

Pro-Turn™ Series

- **10-gauge fabricated and welded deck** design ensures lasting performance
- **Maintenance-free spindles** with durable cast iron housings ensure lasting strength
- **Heavy-duty rubber discharge chute** provides flexibility to mow around objects
- **Double-sided anti-scalp brackets** eliminate bending and breaking of scalp rollers
- **Heavy-duty commercial deck lift** with adjustable foot pedal for effortless adjustments between 15 cutting positions in 1/4" increments
- **Strong front forks** with large fork shafts and bearings add strength and durability while enhancing maneuverability
- **High-back integrated suspension seat** with adjustable armrests, seat isolators, and large diameter steering arms enhance operator comfort and reduce fatigue
- **Foldable ROPS** is standard to provide extra protection for the operator



PRO-TURN™ SERIES

PRODUCT NAME	Pro-Turn 48	Pro-Turn 52	Pro-Turn 60	Pro-Turn 60
MODEL NUMBER	991200	991201	991202	991203
ENGINE	Kawasaki® FS Air-cooled Vertical twin	Kawasaki® FS Air-cooled Vertical twin	Kawasaki® FS Air-cooled Vertical twin	Briggs & Stratton® Commercial Turf w/ Cyclonic Air Cleaner Air-cooled Vertical twin
HORSEPOWER	23	23	24	25
DISPLACEMENT (cc)	726	726	726	724
DRIVE SYSTEM	Hydro-Gear® ZT-3200 Transaxles			
FUEL CAPACITY - Gallons (LITERS)	6.0(22.7)	6.0(22.7)	6.0(22.7)	6.0(22.7)
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph	9 mph/5 mph
STARTER	Electric	Electric	Electric	Electric
DECK				
DECK MATERIAL	10 GA Steel with .25" Spindle Reinforcement			
DECK CONSTRUCTION	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GTIA Electric Clutch			
DECK LIFT SYSTEM	Adj Foot Operated	Adj Foot Operated	Adj Foot Operated	Adj Foot Operated
CUTTING WIDTH	48"	52"	60"	60"
CUTTING HEIGHTS	1.0"-5.0"	1.0"-5.0"	1.0"-5.0"	1.0"-5.0"
CUTTING POSITIONS	15	15	15	15
TIRES				
FRONT AXLE	Fixed	Fixed	Fixed	Fixed
FRONT	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6	Smooth 13 x 6.5-6
REAR	Turf 22 x 9.5-12	Turf 22 x 9.5-12	Turf 22 x 9.5-12	Turf 22 x 9.5-12
FEATURES				
SEAT	High Back Comfort w/ Integrated Suspension			
HOOD	N/A	N/A	N/A	N/A
HEADLIGHTS	Optional	Optional	Optional	Optional
HOUR METER	Standard	Standard	Standard	Standard
FOLDABLE ROPS	Standard	Standard	Standard	Standard
MACHINE DIMENSION				
WEIGHT (lbs)	918	936	963	959
LENGTH (inches)	78.5"	78.5"	78.5"	78.5"
WIDTH (inches)	62.25"	67.75"	75.25"	75.25"
WIDTH w/o CHUTE (inches)	50"	55.5"	63"	63"
HEIGHT w/ ROPS	68"	68"	68"	68"
HEIGHT w/ ROPS FOLDED DOWN	48.5"	48.5"	48.5"	48.5"
WARRANTY				
UNIT	2 Year/600 Hour Limited Commercial			

Updated 01/2014

Ariens Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM