

GRAVELY®

AN AMERICAN WORKHORSE SINCE 1916

MAKE ROOM IN YOUR FLEET FOR A MACHINE
THAT'S PRICED RIGHT AND BUILT DURABLE
TO GO THE DISTANCE.

PROFESSIONAL



Pro-Turn™ 100 XDZ Series

- **7-gauge fabricated and welded X-Factor® Deck** design ensures lasting performance
- **Maintenance-free XL Spindles®** with durable cast iron housings
- **1/2" deck integrated wear bar** with two additional gussets guard against leading edge and baffle bending
- **Heavy-duty rubber discharge chute** provides flexibility to mow around objects
- **Double-sided anti-scalp brackets** eliminate bending and breaking of anti-scalp rollers
- **Full-suspension seat** has been lowered to increase overall stability while comfortably cradling the operator
- **Foldable ROPS** is standard to provide extra protection for the operator
- **Large diameter steering arms** with vibration isolators increase operator comfort and control while reducing fatigue
- **Strong front forks** with larger fork shafts and bearings increase durability and maneuverability
- **Designated trailer tie-down points** safeguard the machine during transportation

Accessories/ Attachments

Optional:

WHEEL COVERS
DISCHARGE COVER KIT
FLEXTEND™ SHOULDER SUPPORT SYSTEM
HEADLIGHT KIT
MULCHING KIT
OPERATOR CONTROLLED DISCHARGE CHUTE
POWERED BAGGER KIT
STRIPING KIT
TRAILER HITCH KIT
SOLID FRONT TIRE KIT
BAR STYLE TIRE KIT



PRO-TURN™ 100 XDZ SERIES

PRODUCT NAME	Pro-Turn 148	Pro-Turn 148	Pro-Turn 152	Pro-Turn 152	Pro-Turn 160	Pro-Turn 160
MODEL NUMBER	991095	991079	991096	991080	991081	991097
ENGINE	Kohler® EFI	Kawasaki® FX691V	Kohler® EFI	Kawasaki® FX691V	Kawasaki® FX730V	Kohler® EFI
Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin	Air-cooled Vertical twin
Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner	Heavy-Duty Air Cleaner
HORSEPOWER	23	22	23	22	23.5	25
DISPLACEMENT (cc)	747	726	747	726	726	747
DRIVE SYSTEM	Hydro-Gear® ZT-3400 Integrated pump/motor					
FUEL CAPACITY - Gallons (LITERS)	9.4 (35.6)	9.4 (35.6)	9.4 (35.6)	9.4 (35.6)	9.4 (35.6)	9.4 (35.6)
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	10 mph / 4.5 mph	10 mph / 4.5 mph	10 mph / 4.5 mph	10 mph / 4.5 mph	10 mph / 4.5 mph	10 mph / 4.5 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric
DECK						
DECK MATERIAL	7 GA Steel with .25 inch Spindle Reinforcement					
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT2.5 Electric Clutch					
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	48"	48"	52"	52"	60"	60"
CUTTING HEIGHTS	1.5"- 5.5"	1.5"- 5.5"	1.5"- 5.5"	1.5"- 5.5"	1.5"- 5.5"	1.5"- 5.5"
CUTTING POSITIONS	17	17	17	17	17	17
TIRES						
FRONT AXLE	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
FRONT	Smooth 13 x 6.50-6	Smooth 13 x 6.50-6	Smooth 13 x 6.50-6	Smooth 13 x 6.50-6	Smooth 13 x 6.50-6	Smooth 13 x 6.50-6
REAR	Turf 23 x 10.50-12	Turf 23 x 10.50-12	Turf 23 x 10.50-12	Turf 23 x 10.50-12	Turf 23 x 10.50-12	Turf 23 x 10.50-12
FEATURES						
HOOD	N/A	N/A	N/A	N/A	N/A	N/A
HEADLIGHTS	Optional	Optional	Optional	Optional	Optional	Optional
SEAT	High-Back w/ Full Suspension					
HOUR METER	Standard	Standard	Standard	Standard	Standard	Standard
SUSPENSION SEAT	Standard	Standard	Standard	Standard	Standard	Standard
FOLDABLE ROPS	Standard	Standard	Standard	Standard	Standard	Standard
MACHINE DIMENSION						
WEIGHT (lbs)	1026	1026	1051	1051	1073	1073
LENGTH (inches)	78.6	78.6	78.6	78.6	78.6	78.6
WIDTH (inches)	50 (w/o chute)	50 (w/o chute)	55.5(w/o chute)	55.5 (w/o chute)	63 (w/o chute)	63 (w/o chute)
HEIGHT w/ ROPS	68	68	68	68	68	68
HEIGHT w/ ROPS FOLDED DOWN	48	48	48	48	48	48
WARRANTY						
UNIT	2 Year Limited Commercial					
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame					
SPINDLES	3 Year Limited Spindle					

Updated 01/2014

Ariens Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM