



AN AMERICAN WORKHORSE SINCE 1916

# COMFORT HAS GONE COMMERCIAL.

PROFESSIONAL



## Accessories/ Attachments

### Optional:

3 BUCKET POWERED  
BAGGER KIT\*  
MULCHING KIT  
STRIPING KIT  
DISCHARGE COVER KIT  
TRAILER HITCH KIT  
HEADLIGHT KIT  
FLEXTEND® SHOULDER  
SUPPORT SYSTEM  
OPERATOR CONTROL  
DISCHARGE CHUTE  
POWERED DECK LIFT  
BAR STYLE TIRE KIT  
SUNSHADE

\*Not available on 72" deck units

## Pro-Turn™ 400 Series

- **Industry-first air ride suspension seat** provides extraordinary all-day comfort
- **Adjustable foot pedal** allows operators of any size to effortlessly raise the deck
- **New deck lift system** requires minimal effort to raise or lower the deck reducing operator fatigue
- **Fully adjustable control arms** comfortably accommodate operators of any size and flip open for easy access to and from the cockpit
- **Semi-pneumatic front tires** eliminate downtime for flat tire repairs
- **Seat isolators** between the seat and frame absorb bumps and vibration
- **Dial-adjust height-of-cut**\*makes it quick and easy to switch between cutting heights
- **Rubber isolated foot platform** minimizes leg vibration to ensure all-day comfort
- **Heavy-duty rear bumper** protects the engine from accidental damage
- **Robust, 3" tall steel frame tubing** provides industry-leading durability
- **Designated trailer tie-down** points safeguard the machine during transport
- **Strong front forks** with larger fork shafts and bearings increase durability and maneuverability
- **7-gauge fabricated and welded X-Factor® Deck** design guarantees lasting performance
- **Maintenance-free XL Spindles**® with durable cast iron housings

\*Patent Pending



# PRO-TURN™ 400 SERIES

PRODUCT NAME	Pro-Turn 452		Pro-Turn 460				Pro-Turn 472	
MODEL NUMBER	992230	992231	992234	992233	992235	992244	992239	992245
ENGINE	Kawasaki® FX751V	Kohler® EFI	Kawasaki® FX850V	Kohler® EFI	Kawasaki® FX921V	Kawasaki® FX1000V	Kawasaki® FX921V	Kawasaki® FX1000V
HORSEPOWER	24.5 hp	26.5 hp	27 hp	26.5 hp	31 hp	35 hp	31 hp	35 hp
DISPLACEMENT (cc)	852	747	852	747	999	999	999	999
DRIVE SYSTEM	Hydro-Gear® ZT-5400 Integrated Pump/Motor							
FUEL CAPACITY	13.4 [50.7] (Gas & Diesel)							
GROUND SPEED (fwd/rev)	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph	13 mph / 6 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
DECK								
DECK MATERIAL	7-Gauge Fabricated and Welded with .25" Spindle Reinforcement							
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT 3.5 Electric Clutch							
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	52"	52"	60"	60"	60"	60"	72"	72"
CUTTING HEIGHTS	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"	1.0"-5.5"
CUTTING POSITIONS	19	19	19	19	19	19	19	19
TIRES								
FRONT	Semi-pneumatic 15 x 6-6	Semi-pneumatic 15 x 6-6	Semi-pneumatic 15 x 6-6	Semi-pneumatic 15 x 6-6	Semi-pneumatic 15 x 6-6	Semi-pneumatic 15 x 6-6	Semi-pneumatic 15 x 6-6	Semi-pneumatic 15 x 6-6
REAR	23 x 10-12 Turf	23 x 10-12 Turf	24 x 11.5-12 Turf	24 x 11.5-12 Turf	24 x 11.5-12 Turf	24 x 11.5-12 Turf	24 x 11.5-12 Turf	24 x 11.5-12 Turf
FEATURES								
SPECIAL FEATURES	Insulated Engine, Transmission Frame, Isolated Foot Plate							
SEAT PACKAGE	Premium Air Ride Seat with Vibration Isolators							
HOUR METER	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
CONTROL PANEL	Throttle, Choke, PTO, Ignition							
FOLDABLE ROPS	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
DIMENSIONS								
WEIGHT (lbs.)	1337	1317	1380	1360	1400	1400	1433	1433
LENGTH (inches)	80	80	80	80	80	80	82	82
WIDTH (inches)	67.75	67.75	75.25	75.25	75.25	75.25	87.25	87.25
HEIGHT W/ ROPS EXT/DOWN (inches)	70 / 47.75	70 / 47.75	70 / 47.75	70 / 47.75	70 / 47.75	70 / 47.75	70 / 47.75	70 / 47.75
WARRANTY								
DECK SHELL & FRAME	Limited Lifetime							
SPINDLES	3 Year Limited							
UNIT	3 Year Limited Commercial							
ACCESSORIES								

3 Bucket Powered Bagger Kit (excluding 72" model), Mulching Kit, Striping Kit, Discharge Cover Kit, Trailer Hitch Kit, Headlight Kit, Flextend Shoulder Support System, Operator Control Discharge Chute, Powered Deck Lift, Bar Style Tire Kit, Wheel Covers, Vacuum Baffle, Gravely Seat Cover

Updated 02/2014 Kawasaki® horsepower ratings per SAE J2723. All other horsepower ratings per SAE J1940.

An **Ariens** Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [www.ariens.com](http://www.ariens.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM