

GRAVELY

AN AMERICAN WORKHORSE SINCE 1916

COMFORT JUST BECAME EFFICIENT.

PROFESSIONAL

Accessories/ Attachments

Optional:

MULCHING KIT
STRIPING KIT
DISCHARGE COVER KIT
TRAILER HITCH KIT
HEADLIGHT KIT
FLEXTEND® SHOULDER SUPPORT SYSTEM
OPERATOR CONTROL DISCHARGE CHUTE
POWERED DECK LIFT
WHEEL COVERS

Pro-Turn™ 400 Diesel Series

- **Powerful 25hp Kubota Diesel Engine**
- **Industry-first air ride suspension seat** provides extraordinary all-day comfort
- **Adjustable foot pedal** allows operators of any size to effortlessly raise the deck
- **New deck lift system** requires minimal effort to raise or lower the deck reducing operator fatigue
- **Fully adjustable control arms** comfortably accommodate operators of any size and flip open for easy access to and from the cockpit
- **Semi-pneumatic front tires** eliminate downtime for flat tire repairs
- **Seat isolators** located between the seat and frame absorb bumps and vibration
- **Dial-adjust height-of-cut*** makes it quick and easy to switch between cutting heights
- **Rubber isolated foot platform** minimizes leg vibration to provide all-day comfort
- **Robust, 3" tall steel frame tubing** provides industry-leading durability
- **Designated trailer tie-down points** safeguard the machine during transport
- **7-gauge fabricated and welded X-Factor® Deck** design ensures lasting performance
- **Maintenance-free XL Spindles®** with durable cast iron housings

*Patent Pending



PRO-TURN™ 400 DIESEL SERIES

PRODUCT NAME	Pro-Turn 460	Pro-Turn 472
MODEL NUMBER	992236	992240
ENGINE	Kubota® Diesel	Kubota® Diesel
HORSEPOWER	25	25
DISPLACEMENT (cc)	902	902
DRIVE SYSTEM	Hydro-Gear® ZT-5400 Integrated pump/motor	
FUEL CAPACITY	13.4 (50.7)	13.4 (50.7)
GROUND SPEED (fwd/rev)	11mph/6 mph	11mph/6 mph
STARTER	Electric	Electric
DECK		
DECK MATERIAL	7 ga steel with .25 inch spindle reinforcement	
DECK CONSTRUCTION	Welded	Welded
NUMBER OF SPINDLES	3	3
BLADE TIP SPEED (FPM)	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt
DECK ENGAGEMENT	Ogura® GT3.5 Electric Clutch	
DECK LIFT SYSTEM	Foot Operated	Foot Operated
CUTTING WIDTH	60"	72"
CUTTING HEIGHTS	1.0-5.5"	1.0-5.5"
CUTTING POSITIONS	19	19
TIRES		
FRONT	Semi Pneumatic 15 x 6 - 6	
REAR	24 x 11.5-12 Turf	
SPECIAL FEATURES		
HOOD	Standard	
SEAT PACKAGE	Premium Air Ride Seat with Vibration Isolators	
HOUR METER	Standard	
CONTROL PANEL	Throttle, PTO, Ignition	
FOLDABLE ROPS	Standard	
DIMENSIONS		
WEIGHT (lbs.)	1799	1867
LENGTH (inches)	86"	88"
WIDTH (inches)	75.25"	87.25"
HEIGHT W/ ROPS EXT/DOWN (inches)	70 / 47.75	70 / 47.75
WARRANTIES		
DECK SHELL & FRAME	Limited Lifetime	
SPINDLES	3 Year Limited	
UNIT	3 Year Limited Commercial	

Mulching Kit, Striping Kit, Discharge Cover Kit, Trailer Hitch Kit, Headlight Kit, Flextend Shoulder Support System, Operator Control Discharge Chute, Electric Deck Lift, Bar Style Tire Kit, Wheel Covers, Vacuum Baffle, Gravely Seat Cover

Updated 01/2014 Kawasaki® horsepower ratings per SAE J2723. All other horsepower ratings per SAE J1940.

An **Ariens** Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM