



AN AMERICAN WORKHORSE SINCE 1916

GO GREEN WITH GRAVELY.

PROFESSIONAL



Accessories/ Attachments

Optional:

- 3 BUCKET POWERED BAGGER KIT*
- MULCHING KIT
- STRIPING KIT
- DISCHARGE COVER KIT
- TRAILER HITCH KIT
- HEADLIGHT KIT
- FLEXTEND® SHOULDER SUPPORT SYSTEM
- PNEUMATIC FRONT CASTER TIRE KIT
- OPERATOR CONTROL DISCHARGE CHUTE
- POWERED DECK LIFT
- WHEEL COVER

* 60 " Deck only

Pro-Turn™ 400 LP Series

- Kawasaki® FX850V-LP Engine** delivers the power to accomplish tough jobs
- Twin 33.5# LP Tanks** ensure long run time to complete big jobs
- Vapor withdrawal system** provides superior cold start performance
- Industry-first air ride suspension seat** delivers extraordinary comfort
- Adjustable foot pedal** allows operators of any size to effortlessly raise the deck
- New deck lift system** requires minimal effort to raise and lower the deck reducing operator fatigue
- Fully adjustable control arms** comfortably accommodate operators of any size and flip open for easy access to and from the cockpit
- Semi-pneumatic front tires** eliminate downtime for flat tire repairs
- Seat isolators** located between the seat and frame provide the most comfortable zero-turn ride on the market
- Dial-adjust height-of-cut*** makes it quick and easy to switch between cutting heights
- Rubber isolated foot platform** minimizes leg vibration to provide all-day comfort
- Robust, 3" tall steel frame tubing** provides industry-leading durability
- Designated trailer tie-down points** safeguard the machine during transport
- 7-gauge fabricated and welded X-Factor® Deck** design ensures lasting performance
- Maintenance-free XL Spindles®** with durable cast iron housings

*Patent Pending



PRO-TURN® 400 LP SERIES

PRODUCT NAME	Pro-Turn 460	Pro-Turn 472
MODEL NUMBER	992237	992243
ENGINE	Kawasaki® FX850- LPG	Kawasaki® FX850- LPG
DISPLACEMENT (cc)	852	852
DRIVE SYSTEM	Hydro-Gear® ZT-5400 Integrated pump/motor	Hydro-Gear® ZT-5400 Integrated pump/motor
FUEL CAPACITY - Gallons (LITERS)	Twin 33.5# tanks (tanks not included)	Twin 33.5# tanks (tanks not included)
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	13 mph/6 mph	13 mph/6 mph
STARTER	Electric	Electric
DECK		
DECK MATERIAL	7 ga steel with .25 inch spindle reinforcement	7 ga steel with .25 inch spindle reinforcement
DECK CONSTRUCTION	Welded	Welded
NUMBER OF SPINDLES	3	3
BLADE TIP SPEED (FPM)	18,000	18,000
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron
SPINDLE SHAFT	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt
DECK ENGAGEMENT	Ogura® GT3.5 Electric Clutch	Ogura® GT3.5 Electric Clutch
DECK LIFT SYSTEM	Foot Operated	Foot Operated
CUTTING WIDTH	60"	72"
CUTTING HEIGHTS	1.0-5.5"	1.0-5.5"
CUTTING POSITIONS	19	19
TIRES		
FRONT	Smooth 15 x 6-6 Semi Pneumatic	Smooth 15 x 6-6 Semi Pneumatic
REAR	Turf 24 x 11.5-13	Turf 24 x 11.5-13
FEATURES		
SPECIAL FEATURES	Insulated Engine, Transmission Frame, Isolated Foot Plate	Insulated Engine, Transmission Frame, Isolated Foot Plate
SEAT PACKAGE	Premium Air Ride Seat with Vibration Isolators	Premium Air Ride Seat with Vibration Isolators
HOUR METER	Standard	Standard
CONTROL PANEL	Throttle, PTO, Ignition	Throttle, PTO, Ignition
FOLDABLE ROPS	Standard	Standard
DIMENSION		
WEIGHT (lbs)	1579 w/Full LP Tanks	1633 w/Full LP Tanks
LENGTH (inches)	80"	80"
WIDTH (inches)	75.25"	87.25"
HEIGHT W/ ROPS EXT/ DOWN (inches)	70 / 47.75	70 / 47.75
WIDTH W/O CHUTE	63	75
WARRANTY		
DECK SHELL & FRAME	Limited Lifetime	Limited Lifetime
SPINDLES	3 Year Limited	3 Year Limited
UNIT	3 Year Limited Commercial	3 Year Limited Commercial
ATTACHMENTS		
3 Bucket Powered Bagger Kit (for 60" only), Mulching Kit, Striping Kit, Discharge Cover Kit, Trailer Hitch Kit, Headlight Kit, Flextend Shoulder Support System, Pneumatic Front Caster Tire Kit, Operator Control Discharge Chute, Electric Deck Lift, Bar Style Tire Kit, Hub Cap Kit, Vacuum Baffle, Gravely Seat Cover		

Updated 01/2014

Kawasaki® horsepower ratings per SAE J2723. All other horsepower ratings per SAE J1940.

An **Ariens** Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM