



AN AMERICAN WORKHORSE SINCE 1916

SHOWCASE YOUR PRIDE AS A HOMEOWNER WITH A GRAVELY ZT MOWER THAT DELIVERS UNRIVALED RESULTS

RESIDENTIAL



ZT Series

- **High back seat** ensures a comfortable ride (42" and 50" only)
- **Foot-operated deck lift** with 7 cut heights ranging from 1.5 - 4.5 is easy to use. Simply press the foot lever and select your desired height of cut.
- **Heavy-duty steel C-Channel frame** with welded joints provides structural rigidity for increased strength and stability
- **4 point deck lift system** provides unsurpassed deck stability
- **12-gauge stamped steel XLerator™ deck** with rolled top lip delivers an exceptional quality of cut
- **Low center of gravity** provides stability and traction for mowing varying terrain
- **Adjustable flip out control arms** allow for easy access to and from the cockpit
- **Speeds up to 6 mph moving forward and 3 mph in reverse** let you get the job done quickly
- **Deck washout port** makes cleaning the deck quick and convenient (42" and 50" only)
- **Maintenance free** front caster fork bushings



Limited
5 Year
Frame & Deck Shell
Warranty

ZT SERIES

	ZT34	ZT42	ZT50
MODEL NUMBER	915146	915148	915150
ENGINE	BRIGGS & STRATTON® SINGLE CYLINDER	KAWASAKI® FR	KAWASAKI® FR
HORSEPOWER	16.5	21.5	23
DISPLACEMENT (cc)	500	726	726
DRIVE SYSTEM	HYDRO-GEAR® EZT TRANSAKLES WITH 1" AXLE SHAFTS	HYDRO-GEAR® EZT TRANSAKLES WITH 1" AXLE SHAFTS	HYDRO-GEAR® EZT TRANSAKLES WITH 1" AXLE SHAFTS
FUEL CAPACITY - GALLONS (LITERS)	2.0 (7.5)	2.0 (7.5)	2.0 (7.5)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	6 MPH/3 MPH	6 MPH/3 MPH	6 MPH/3 MPH
STARTER	ELECTRIC	ELECTRIC	ELECTRIC
DECK			
DECK MATERIAL	12 GA	12 GA	12 GA
DECK CONSTRUCTION	STAMPED	STAMPED	STAMPED
NUMBER OF SPINDLES	2	3	3
BLADE TIP SPEED (FPM)	17,500	17,000	17,800
SPINDLE MATERIAL	STEEL	STEEL	STEEL
SPINDLE SHAFT	STEEL	STEEL	STEEL
SPINDLE BEARINGS	SEALED	SEALED	SEALED
DECK DRIVE	BELT	BELT	BELT
DECK ENGAGEMENT	WARNER®	WARNER®	WARNER®
DECK LIFT SYSTEM	FOOT OPERATED	FOOT OPERATED	FOOT OPERATED
CUTTING WIDTH	34"	42"	50"
CUTTING HEIGHTS	1"-4"	1.5"-4.5"	1.5"-4.5"
CUTTING POSITION	7	7	7
WHEELS			
FRONT AXLE	FIXED	FIXED	FIXED
FRONT	11 x 4-5	11 x 4-5	11 x 4-5
REAR	18 x 6.5-8	18 x 8.5-8	18 x 9.5-8
FEATURES			
HEADLIGHTS	N/A	N/A	N/A
SEAT	LOW BACK W/ SEAT SPRINGS	HIGH BACK W/ SEAT SPRINGS	HIGH BACK W/ SEAT SPRINGS
HOUR METER	N/A	N/A	N/A
WARRANTY			
UNIT	3 YEAR LIMITED CONSUMER	3 YEAR LIMITED CONSUMER	3 YEAR LIMITED CONSUMER
DECK SHELL & FRAME	5 YEAR LIMITED DECK SHELL & FRAME	5 YEAR LIMITED DECK SHELL & FRAME	5 YEAR LIMITED DECK SHELL & FRAME
DIMENSIONS			
WEIGHT (LBS)	425	440	475
LENGTH	64"	64"	64"
WIDTH WITH CHUTE	42"	54"	62"
HEIGHT	37"	37"	40"
ATTACHMENTS & ACCESSORIES	2-BUCKET NON-POWERED BAGGER, MULCH KIT, TRAILER HITCH KIT, ARM REST KIT, FLEXTEND® SHOULDER SUPPORT SYSTEM, POLY ROLLER, DETHATCHER, SPREADER, PLUG AERATOR, SPRAYER, DUMP CART, SEAT COVER, MOWER COVER		

Updated 06/2014

An **Ariens** Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit www.ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



WWW.GRAVELY.COM