



AN AMERICAN WORKHORSE SINCE 1916

## DISCOVER THE DIFFERENCE OF PROFESSIONAL ENGINEERING AND INNOVATION

RESIDENTIAL



### ZT XL Series

- **10-gauge welded deck** design with a  $\frac{1}{4}$ " thick reinforcement strip 4-inches deep provides increased airflow for a clean, precise cut
- **Full tubular frame** with fully welded construction provides enhanced strength over the competitor's bolted together frame
- **Hydro-Gear® ZT 2800 transaxles** deliver smooth variable control and a zero-turn radius
- **Lower center of gravity** and a wider frame improve stability and traction for mowing varying terrain
- **Fully damped steering mechanism** ensures smooth operation
- **Flip-up floor pan** provides easy access to the top of the mower deck for quick, efficient routine maintenance
- **Dual footrest zone** comfortably accommodates operators of various heights
- **Fully adjustable control arms** accommodate any size operator and flip open for easy access to and from the cockpit
- **Adjustable high back seat** with armrests and seat springs comes standard to ensure a comfortable ride



Limited  
5 Year  
Frame & Deck Shell  
Warranty

# ZT XL SERIES

	ZTXL 42	ZTXL 48	ZTXL 54
<b>MODEL NUMBER</b>	915160	915162	9151164
ENGINE	KAWASAKI® FR	KAWASAKI® FR	KAWASAKI® FR
HORSEPOWER	21.5	23	23
DISPLACEMENT (cc)	726	726	726
DRIVE SYSTEM	HYDRO-GEAR® ZT-2800 TRANSAXLES	HYDRO-GEAR® ZT-2800 TRANSAXLES	HYDRO-GEAR® ZT-2800 TRANSAXLES
FUEL CAPACITY - GALLONS (LITERS)	3.8 (14.4)	3.8 (14.4)	3.8 (14.4)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	6.5 MPH/3 MPH	6.5 MPH/3 MPH	6.5 MPH/3 MPH
STARTER	ELECTRIC	ELECTRIC	ELECTRIC
<b>DECK</b>			
DECK MATERIAL	10 GA WITH DOUBLER PLATE	10 GA WITH DOUBLER PLATE	10 GA WITH DOUBLER PLATE
DECK CONSTRUCTION	WELDED	WELDED	WELDED
NUMBER OF SPINDLES	3	3	3
BLADE TIP SPEED (FPM)	17,000	16,800	16,950
SPINDLE MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM
SPINDLE SHAFT	1" DIA. STEEL	1" DIA. STEEL	1" DIA. STEEL
SPINDLE BEARINGS	1" SEALED	1" SEALED	1" SEALED
DECK DRIVE	BELT	BELT	BELT
DECK ENGAGEMENT	WARNER®	WARNER®	WARNER®
DECK LIFT SYSTEM	FOOT OPERATED	FOOT OPERATED	FOOT OPERATED
CUTTING WIDTH	42"	48"	54"
CUTTING HEIGHTS	1.5"- 4.5"	1.5"- 4.5"	1.5"- 4.5"
CUTTING POSITION	7	7	7
<b>WHEELS</b>			
FRONT AXLE	FIXED	FIXED	FIXED
FRONT	11 x 4-5	11 x 4-5	11 x 4-8
REAR	20 x 8-8	20 x 10-8	20 x 10-8
<b>FEATURES</b>			
HEADLIGHTS	OPTIONAL	OPTIONAL	OPTIONAL
SEAT	HIGH BACK WITH SEAT SPRINGS & LEVER ADJUST	HIGH BACK WITH SEAT SPRINGS & LEVER ADJUST	HIGH BACK WITH SEAT SPRINGS & LEVER ADJUST
HOUR METER	STANDARD	STANDARD	STANDARD
<b>WARRANTY</b>			
UNIT	3 YEAR LIMITED CONSUMER	3 YEAR LIMITED CONSUMER	3 YEAR LIMITED CONSUMER
DECK SHELL & FRAME	5 YEAR LIMITED DECK SHELL & FRAME	5 YEAR LIMITED DECK SHELL & FRAME	5 YEAR LIMITED DECK SHELL & FRAME
<b>DIMENSIONS</b>			
WEIGHT (LBS)	615	630	645
LENGTH	69"	69"	69"
WIDTH WITH CHUTE	52"	58"	64"
HEIGHT	42"	42"	42"
<b>ATTACHMENTS &amp; ACCESSORIES</b>	3-BUCKET POWERED BAGGER, MULCH KIT, TRAILER HITCH KIT, FLEXTEND® SHOULDER SUPPORT SYSTEM, HEADLIGHT KIT, ENGINE GUARD, SUNSHADE, SNOW BLADE, POLY ROLLER, DETHATCHER, SPREADER, PLUG AERATOR, SPRAYER, DUMP CART, SEAT COVER, MOWER COVER		

Updated 03/2014

An *Ariens* Company Brand

© Copyright 2014 Ariens Company. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton, Kubota, Hydro-Gear, Kawasaki, Kohler, Ogura, Parker, Subaru and Warner are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [www.ariens.com](http://www.ariens.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of product; product may differ.



[WWW.GRAVELY.COM](http://WWW.GRAVELY.COM)