

692-Z

Sugar Beet Harvester

6 and 8 Row



692-Z Sugar Beet Harvester Specifications

Tractor Requirements	225 HP min.	
PTO	1000 RPM-CV 1-3/4-20	
Tank Conveyor	40 in. Draper Chain	
Truck Conveyor	42 in. belted chain	
Grab Rolls	3 pairs, adjustable with flex cushions	
Hydrualic Row Finder	Adjustable	
Tank Size	9,000 lbs.	
Tread Width	Adjustable	
Tires	12.4-24 8 Ply	
Lifter Wheels	28 in. cast alloy steel	
Dimensions:		
Width	23.5 ft.	
Height	14 ft.	
Length	24.5 ft.	
Dimensions: lifter head width		
6R22	12 ft.	
6R30	16 ft.	
8R22	16 ft.	
Weight w/ 8 row 22 head	35,000 lbs.	
	1	

Heads:	6 Row	8 Row
1		22 - 24 in.
2	22 - 24 in.	
3	30 in.	



Heavy Duty

New heavy duty hitch paired with steerable, offset axles allows the 692-Z to trail seemlessly through your field. Flex struts with heavy duty lifter wheels are standard!



Optimized Beet Flow

A dual driven paddle shaft moves beets into a full roll bed designed for effecient beet flow into the increased capacity ferris wheel.

Additional New Features:

- Grease bank system for all rolls
- Machined bearing housings
- ·LED road and field lights

Art's Way Manufacturing Co. Inc. reserves the right to change design or specifications without notice. Information contained herein is general and is not intended for specific application purposes. Photographs contained herein may be displayed with safety shields and/or guards removed to show mechanical functions only. AW-692-Z0917

(712) 864-3131 www.artsway-ag.com