Art's Way



## 12 Row 22 Inch Spacing

The Art's Way Defoliator delivers high performance and reliability you can count on. Its rugged design offers exceptional shredding of foliage utilizing steel cupped knives in the front rotor enclosure. Added flails on rotors 2 and 3

provide the finish work to remove remaining foliage. The Art's Way system of quality equipment has earned its reputation for supporting growers in their quest for greater efficiency, productivity and profitability.



Heavy Duty Dual Cylinder Hitch 1000 RPM CV PTO Shaft

**Heavy Duty Wheel Carriers** Wide Walking Tandem Shown 12.4 x 24 - 8 Ply

Sugar Beet
Harvesting Systems
www.artsway-ag.com

meeting your needs in the field



**Heavy Duty Gearbox** with positioned jackshaft for better PTO angle



Center Rotor, 6-pin Rubber Flails Rear Rotor, 8-pin Rubber Flails



Front Rotor, Steel Cluster Cupped **Knives** Enclosed in shredding shroud



**Top Covers** Two belted top covers with single

Easy Access, Heavy Duty Belted **Mechanical Disc or Mechanical** 

Knife Scalpers (Optional)



**Fixed Front Stabilizer Wheels** (Optional) with 7.60 X 15 - 6 Ply Tires

## **SPECIFICATIONS**

cylinder hydraulic open

Tractor Requirements	170 HP min
PTO	1000 RPM-CV
	1-3/8 or 1-3/4-20
Row Spacing	6 row 30 in., 8 row 22 in. or 12 row 22 in.
Top Cover - Front Rotor	Hinged 2-section steel covers
Top Cover - Rear 2 Rotors	Hinged 2-section HD belting w/hyd open
#1 Rotor	Cluster steel, cupped knives, enclosed shroud
#2 Rotor	Rubber cluster 12 in. 6 pin
#3 Rotor	Rubber cluster 12 in. 8 pin
Power Train	1000 RPM PTO shaft, HD gearbox,
	5V section drive belts w/spring-loaded idlers
Drive Shields	Hinged for easy access
	and protection of drive belts
Tire Size	(4) 12.4 x 24 - 8 ply
Overall Dimensions:	
Inside Width 12R22	(22 ft. 2 in.) 266 in.
Inside Width 6R30, 8R22	(14 ft. 10 in.) 178 in.
Outside Width 12R22	(24 ft. 2 in.) 290 in.
Outside Width 6R30, 8R22	(17 ft.) 204 in.
Length w/o Scalpers	(18 ft. 4 in.) 220 in.
Weight w/o Scalpers	11,480 lbs.



Art's Way reserves the right to change design or specifications without notice. Information contained herein is general in nature and is not intended for specific application purposes. Photographs herein may be displayed with safety shields and/or guards removed to show mechanical functions. Copyright Art's Way Mfg. Co. D1222HS-1016



Art's Way Manufacturing Co., Inc. PO Box 288 • Armstrong, IA 50514 (712) 864-3131 • Fax (712) 864-3154 sales@artsway-mfg.com www.artsway-mfg.com www.artsway-ag.com