## Art's Way

Since 1956

## **Land Planes**

Combine maximum production, precision performance and high speed maneuverability



Land Planes are the only way to insure even distribution of rainfall or irrigation. Water pockets can be eliminated by utilizing the natural slope of the field. On rolling ground, landsmoothing improves surface drainage thereby controlling erosion. Tile drainage will handle sub-surface moisture, but a smooth field is necessary to remove excess surface water before damage occurs.

Dead furrows, back furrows, and implement scars are all erased with the patented Art's Way floating hitch design. An Art's Way leveled field makes efficient use of expensive water. Water will run to the end of every row - each plant receives its share. There are no low spots to drown out or high spots to burn out. Art's Way land planes are designed for high speeds to save you time, labor and money by eliminating extra passes.

**Land Management System** 

www.artsway-mfg.com

meeting your needs in the field and farmyard

## **Specifications**


MODEL	1200	1650	2000	2400
Weight-With Tires	2560	2850	3700	3900
Blade Width	12 ft.	16 ft.	20 ft.	24 ft.
Blade Depth	22 in.	22 in.	22 in.	22 in.
Blade Capacity (cu. yard)	2	2 2/3	3 1/3	4
Effective Leveling Length	30-35	30-35	30-35	30-35
Transport Width	12 ft.	16 ft.	12 ft.	12 ft.
Transport Ground Clearance	11 in.	12 in.	12 in.	12 in.
Horse Power Required	75-90	100-125	120-150	150-180

Art's Way reserves the right to change design or specifications without notice. Information contained herein is general in nature and is not intended for specific application purposes. Photographs contained herein may be displayed with safety shields and/or guards removed to show mechanical functions.

## STANDARD EQUIPMENT: High flotation tires and 4 1/2" diameter depth control cylinder OPTIONAL EQUIPMENT: S-Tine attachment, Dual wheels, Cat. 3N hitch, Quick Hitch







When the tractor rear wheels are elevated, the blade stays on grade and cuts off the ridge.







When the tractor rear wheels go into a depression, the blade, again, maintains grade to fill the low spot.



Art's Way Manufacturing Co., Inc. PO Box 288 • Armstrong, IA 50514 (712) 864-3131 • Fax (712) 864-3154 sales@artsway-mfg.com www.artsway-mfg.com

Art's Way Manufacturing Co., Inc. reserves the right to change design or specifications without notice. Information contained herein is general and is not intended for specific application purposes. Photographs contained herein may be displayed with safety shields and/or guards removed to show mechanical functions only. AW-LP213















