



Manure Spreaders *X Series Vertical Beater*

X700 and X900



www.artsway-ag.com

Robust.

The X Series Manure Spreaders provide increased capacity with even material flow for dependable field coverage.

Massive Capacity

Our 18 and 20 foot boxes feature 45° flared sides for increased capacity of 683 and 909 heaped cubic feet.

Dependable

Our 667XH chain boasts a **limited lifetime warranty** so you know you are always covered while in use. 31,000 pounds of tensile strength per chain carry your material towards or away from the beaters. Solid tube slats provide additional durability while moving manure.

Simple Maintenance

A bolt tensioning system allows for in the field chain adjustment. Grease zerks maintain smooth machine operation.

Transport Visibility

LED lights and a safety chain make you more visible and secure on the road.

Even Spread Pattern

The guillotine style slop gate allows you to precisely control how the material enters the vertical beaters. Hydraulic cylinders operate the gate up and down. Combined with two powerful beaters, this creates less clumps in your field and smooth even coverage.

Easy Loading

Flared sides and low loading heights of 92" and 94" allow you to easily load material from the side over the wheels to decrease material loss and load time.

Long Box life

Densilite floors have minimal expansion for longer life as well as provide a slick surface for smooth material flow.







Two models to meet your needs.

The X700 and X900 have the capacities for a wide range of use. The X700 is 473 struck cubic feet of hauling power in an 18 foot x 6 foot box. The X900 has 625 struck cubic feet of capacity in a 20 foot x 6.5 foot box. Load cells and CV PTO options make these boxes the leaders in the industry.



Tough Tires

X Series Spreaders feature Tandem axles with 425/65R-22.5 tires. These allow you to pull the load smoothly behind your tractor without taking the field out with you. Flotation tires available for decreased soil compaction in your fields and lower loading height.



Operator Protection

A heavy duty rock guard is mounted on the flared sides for maximum cab protection. The guillotine style gate provides an additional layer when raised. Easy to hold and color coded hydraulic grips make hooking up a breeze.

Common Components

Service your spreader with quality Art's Way service parts that come in black for installation on your green or red spreader.



Beaters with History

Both models are equipped with Berma brand vertical beaters powered by dual 350 Gear Drives. The X700 uses SRT8 while the X900 uses SRT18 sized beaters. These beaters provide the best spread pattern in the industry.

Product Specifications

	X700	X900
Box Length	18 feet	20 feet
Overall Length	332 inches	371 inches
Overall Width (with tires)	133.5 inches	137.5 inches
Overall Height	118 inches	120 inches
Load Height	92 inches	94 inches
Capacity - Heaped	683 cubic feet	909 cubic feet
Capacity - Struck	473 cubic feet	625 cubic feet
Empty Weight	12,200 pounds	16,800 pounds
Inside Width of Box	72 inches	78 inches
Inside Height of Box	51 inches	56 inches
Flared Sides	16 inches 45°	12 inches 45°
Apron Chain	667XH	667XH
Floor Material	1/2" Densilite	1/2" Densilite
Reversible Apron	Yes	Yes
Pintle Hitch	2 inch	2 inch
Gear Drive	Double 350 Gear Drive	Double 350 Gear Drive
Axles	Tandem	Tandem
Tires	16.00/R-20	16.00/R-20
Flotation Tires (optional)	660/65R 22.5	660/65R 22.5
C-V PTO	Optional	Optional
Slop Gate Cylinders	Chief	Prince
Vertical Beaters	SRT8 Removable	SRT18 Removable
Power Requirement	120-150 HP	180-200 HP
Shipping Dimensions	101 inches x 28 feet x 118 inches	103 inches x 32 feet x 120 inches



Product Options

Load Cells

Monitor your load weight and application poundage with the GT400 Indicator or NT460 Indicator with GPS and record documentation for your own application or custom application projects.



GT400 Digistar Indicator



NT460 Digistar Indicator

PTO

4 PTO styles to choose from:

- 1-3/8 x 21 Spline PTO
- 1-3/4 x 20 Spline PTO
- 1-3/8 x 21 Spline C-V PTO
- 1-3/4 x 20 Spline C-V PTO

C-V PTO options allow for tighter turning and more freedom.



Flotation Tires

Create less field compaction and utilize a lower loading height when you choose the flotation tires instead of our standard tires.



Hardened Beater Teeth Kit

The X Series spreader beaters come with standard beater teeth. Art's Way offers a kit with hardened beater teeth for extended life of your machine. Weld hardened 1/2" thick formed steel teeth. With 1/2" thick flippable knives.

Manure Spreaders

X Series Vertical Beater



X700 and X900



Art's Way Manufacturing Co. Inc. reserves the right to change design or specifications without notice. Information contained herein is general and is not intended for specific application purposes. Photographs contained herein may be displayed with safety shields and/or guards removed to show mechanical functions only. AW-MS1218

(712) 864-3131
www.artsway-ag.com