

**OKAY WINTER.
IT'S JUST YOU AND ME.**

Built for medium- to full-size lighter trucks, the **Arctic SD-P** fits on all QUIK*LINK® mounts, and offers all the robust, dependable features Arctic is known for. Whether you are dusting off the street for a game of road hockey or are liberating your neighbors after a storm, the **Arctic SD-P** lets you get down to business. Winter doesn't wait for anyone – why should you?

5 LASER-CUT, STEEL REINFORCING RIBS
back our frictionless poly moldboard with the strength of steel



QUIK*LINK® IV
ATTACHMENT

FULL-SIZE TENSION SPRINGS
support the plow and are attached to a 1/4"-thick boxed quadrant that fixes to a double leg 2" X 2" boxed tubing A-frame with a 1" easy-to-remove greasable and bushed king bolt

1/4" POLYETHYLENE MOLDBOARD
throws snow further and faster resulting in less resistance and vehicle wear, and improved fuel economy

6" DEFLECTOR
keeps snow down on the blade and away from the driver's windshield

**3/8" X 4"
NON-REVERSIBLE
STEEL CUTTING
EDGE**
cuts and lifts hard packed snow and ice

**HOT-DIPPED
GALVANIZED
STEEL FRAME**
provides added resistance to abrasion, water and rust, making our plows virtually maintenance free

QUIK*LINK® III
ATTACHMENT

DISH-SHAPED SKID SHOES
improve surface clearance while plowing forward

MEET THE REST OF THE ARCTIC PRODUCT LINE



LD-P



SD-P



HD-P



HDXL-P



XHD-P




HDTE-P



HDVTE-P



HD-VAW



HDSSTE-P



HD-S



PP-S

WHY CHOOSE POLY?

Arctic's high density polyethylene moldboards combine the durable, slick characteristics of poly with advanced blade design mechanics to throw more of even the stickiest, wettest snow further and faster. This not only results in more snow being moved more quickly, it also minimizes forward resistance – meaning decreased wear on power trains and increased fuel economy. **Contact your Arctic Dealer to learn more about the high-tech, low-maintenance benefits of poly.**



M3493 SERIES HYDRAULIC POWER UNIT

The M3493 electric hydraulic system, with a 1.5" x 6" lift cylinder offers proven performance and reliability in a compact size. This unit was built for the low mount lift frame and has an operating pressure of 2000 psi and the crossover relief valves are set at 3000 psi. This pump is compatible with all our control systems.



QUIK*LINK® III & IV MOUNTING KIT

Featuring an adjustable jack stand, our mounting systems allow you to remove the entire plow assembly as a single unit with the lift frame intact. Arctic's QUIK*LINK® III & IV system makes the already-simple mounting system even easier to use by replacing the two mounting pins with a simple single, spring-loaded locking bar.

ARCTIC SD-P SPECIFICATIONS

Plow Name	SD84-P	SD90-P
Length	84"	90"
Moldboard Height	22"	22"
Material	1/4" Poly	1/4" Poly
Plowing Width (Full Angle)	75"	78"
Complete Weight	*468 lbs	*490 lbs
Mounting Type	Detachable	Detachable
Removable Lights and Power Unit	Yes	Yes

* Weight does not include frame mounting kit

OPTIONAL ACCESSORIES



SINGLE HALOGEN BULB (H9003)



DUAL HALOGEN BULB (H7, H1)



CURB GUARD



LICENSE PLATE BRACKET



POLY CUTTING EDGE

QUIK*LINK® is a registered trade-mark of Arctic Equipment Manufacturing Corporation.
LEGAL DISCLAIMER: Vehicles intended to be equipped with Arctic equipment must comply with the vehicle manufacturers' specifications for equipment application. Please consult your vehicle dealer before purchase and installation. The purchaser assumes all vehicle risk associated with the attachment and operation of Arctic equipment. Arctic reserves the right to change specifications without prior notification.

**TOUGHER
THAN A
CANADIAN
WINTER**

Arctic Equipment
Manufacturing Corporation

Toll Free **888 413 0019**
www.arcticsnowplows.com