



## ***STORM BOXX(TM) (12', 14' & 16') Specifications***

<b><i>Imperial</i></b>	<b><i>12'</i></b>	<b><i>14'</i></b>	<b><i>16'</i></b>
Blade Width	12'	14'	16'
Blade Height	40 ½"	40 ½"	40 ½"
Capacity	8 ½ cu yd	10 cu yd	11 ½ cu yd
Machine Application	Wheel Loader, Backhoe, Tractor	Wheel Loader, Backhoe, Tractor	Wheel Loader, Backhoe, Tractor
Steel Trip-Edge	Standard	Standard	Standard
Approx. Weight	2,128 lb	2,275 lb	2,512 lb
Mount Type	Interchangeable Attachments	Interchangeable Attachments	Interchangeable Attachments
Horsepower Compatibility	70+ hp	85+ hp	100+ hp

<b><i>Metric</i></b>	<b><i>12'</i></b>	<b><i>14'</i></b>	<b><i>16'</i></b>
Blade Width	3.66 m	4.27 m	4.88 m
Blade Height	102.87 cm	102.87 cm	102.87 cm
Capacity	6.50 cu m	7.65 cu m	8.79 cu m
Machine Application	Wheel Loader, Backhoe, Tractor	Wheel Loader, Backhoe, Tractor	Wheel Loader, Backhoe, Tractor
Steel Trip-Edge	Standard	Standard	Standard
Approx. Weight	965.24 kg	1,031.92 kg	1,139.42 kg
Mount Type	Interchangeable Attachments	Interchangeable Attachments	Interchangeable Attachments
Horsepower Compatibility	70+ hp	85+ hp	100+ hp