



XtremeV(TM) Specifications

Imperial	8' 6" PC or SS	9' 6" PC or SS
Blade Width	8' 6"	9' 6"
Blade Height	29" at Center 31" at End	31" at Center 33" at End
Blade Gauge	14	14
Trip Springs	4	6
Ribs	12	12
Lift Cylinder	1 1/2" x 10"	1 1/2" x 10"
Angling Rams	1 3/4" x 11"	1 3/4" x 11"
Plowing Width	7' 5" Full Angle 7' 1" Scoop 7' 7" Full V	8' 3" Full Angle 7' 11" Scoop 8' 7" Full V
Approx. Weight*	899 lb	1,013 lb
Cutting Edge	3/8 " x 6" 1/2" x 6"**	1/2" x 6"
Mount Type	Minute Mount® 2	Minute Mount® 2

Metric	8' 6" PC or SS	9' 6" PC or SS
Blade Width	2.59 m	2.90 m
Blade Height	73.66 cm at Center 78.74 cm at End	78.74 cm at Center 83.82 cm at End
Blade Gauge	2.66 mm	2.66 mm
Trip Springs	4	6
Ribs	12	12
Lift Cylinder	3.81 cm x 25.40 cm	3.81 cm x 25.40 cm
Angling Rams	4.45 cm x 27.94 cm	4.45 cm x 27.94 cm
Plowing Width	2.26 m Full Angle 2.16 m Scoop 2.31 m Full V	2.51 m Full Angle 2.41 m Scoop 2.62 m Full V
Approx. Weight*	407 kg	459 kg
Cutting Edge	0.95 cm x 15.24 cm 1.27 cm x 15.24 cm**	1.27 cm x 15.24 cm
Mount Type	Minute Mount® 2	Minute Mount® 2

PC = Powder Coated Steel

SS = Stainless Steel

*Does not include vehicle mount. Please refer to the eMatch program for specific vehicle applications.

**Optional accessory