

YORK RAKE

Model RI



A Tough Versatile Landscape Rake.
For Category 1 or 2 Tractors, 35 Horsepower and Up.

Now Quick Hitch Compatible!



Model	007116	007117	007118	007410	007126	007127	007128	007420
Weight	441#	467#	493#	578#	461#	487#	513#	598#
Max. Raking Width	6'	7'	8'	10'	6'	7'	8'	10'
Min. Raking Width	63"	73"	85"	103"	63"	73"	85"	103"
Angling	5 Positions Manual Angle, Infinite w/Optional Hydraulic Angle.							
HP Rating	35 HP & Up							
Tooth Size	5/16" x 1" x 28", Heat Treated Alloy Steel.			*	5/16" x 1" x 28", Heat Treated Alloy Steel.			*
Tooth Spacing	1"			1-1/2"	1"			1-1/2"
Hitch	Cat. 1, 3 Point or Quick Hitch				Cat. 2, 3 Point or Quick Hitch			
Storage Stand	Standard							
Caster Wheels	Optional, 13/6.50 x 6 Pneumatic Tires, 88# per Pair.			**	Optional, 13/6.50 x 6 Pneumatic Tires, 88# per Pair.			**
Grader Blade	Optional, 6' - 145#, 7' - 160#, 8' - 174# & 10' - 203#. Replaceable Cutting Edge(1/2" x 6").							
End Boots	Optional, 26# per Pair							
Scarifier	Optional, 10 Heat Treated, Reversible, Alloy Steel Points, 72" wide, 223#.							

* - 5/16" x 1-1/4" x 30", Heat Treated Alloy Steel.

** - Optional, 13/6.50 x 6 Pneumatic Tires, 102# per Pair.

A division of YORK MODERN CORPORATION • UNADILLA, NY 13849 • 800-643-YORK (9675) or 607-369-7111 • Fax: 607-369-2625

E-mail: sales@yorkmodern.com Web: www.yorkmodern.com

Form SL-RIS09 (Rev. 3/2009) Specifications subject to change without notice. Printed in USA