



AGRICULTURAL
MACHINERY




ONE WINDROW ROTARY RAKES

**RR320
RR420/450 EVO**



RR 320



Enorossi Windrow Turner RR320

A very versatile machine with unit in oil bath projected and realized for small to medium companies. Working height can be adjusted with worm screws, pivoting wheels, and articulated frame with shock absorber. Projected for raking in all situations with excellent results. Made of high quality steel ensure great performances and long durability.



Working position



Transport position

RR420/450EVO 3 POINT HITCH



Enorossi Rotary Rake RR420/450EVO 3 POINT HITCH

Enorossi has developed the RR420/450EVO especially for smaller farmers who like to organise their work independently and frequently work in small field structures.

The working widths of 4.2 metres (13'8") to 4.5 metres (14'8") make them ideal for these tasks.

The machines run smoothly with faster working speeds, and the wide track of the tandem chassis ensures high driving stability and reliable rotor guidance, even on hilly terrain.



Transport position



Pivoting headstock



Adjustable cam

RR420/450 EVO PULL TYPE



Enorossi Rotary Rake RR420/450EVO PULL TYPE

The new Enorossi rotary rakes clean sweep raking widths from 4.2 metres (13'8") to 4.5 metres (14'8") allowing you to get the most from your hay crop efficiently.

Each Enorossi Rotary Rake features a hydraulic lift system and adjustable height to ease fieldwork and maximize manoeuvrability. The adjustable front cylinder allows users to fine tune pitch and all Enorossi Rotary Rakes feature removable tine arms. Adjustable cam allows operator to set teeth according to hay conditions. Cardan shaft with slip clutch. Standard tandem axles. sealed oil bath gearbox.



Transport position



Tandem axles



High clearance lift for headland raking and transport

RR 320 - RR420EVO - RR450EVO

TECHNICAL FEATURES

SPECIFICATIONS	RR320	RR420EVO	RR450EVO
Number of arms	8/9	11	13
Number of double tines per arm	3	4	4
Working width mt./ft.	3,2/10'5"	4,20/13'8"	4,50/14'8"
Gearbox	Sealed in oil bath	Sealed in oil bath	Sealed in oil bath
Rotor diameter (working width) mt./ft.	2,30/7'6"	3,40/11'2"	3,70/12'2"
Transport width mt./ft.	1,10/3'6"	1,80/5'9"	1,80/5'9"
PTO driveline with slip clutch	540 RPM constant velocity overload protects gearbox	540 RPM constant velocity overload protects gearbox	540 RPM constant velocity overload protects gearbox
Tyres n.	2 mounted on pivoting axles 16x6.50x8	4 mounted on tandem axles 18x8.5x8	4 mounted on tandem axles 18x8.5x8
HP required	20	30/45	30/45
Weight Kg./Lb.	340/750	620/1369	640/1413



AGRICULTURAL
MACHINERY



ENOAGRICOLA ROSSI S.r.l.
Via Cortonese, SN
06018 Calzolaro di Umbertide (PG)
Tel. +39 075 930 22 22
Fax +39 075 930 23 28
info@enorossi.it
www.enoagricolarossi.com

