


MODELS AVAILABLE



MODEL INFO		12' END WHEEL NO-TILL DRILLS (pg 8-9)		13' END WHEEL MIN-TILL DRILLS (pg 10-11)		12' 3-POINT DRILLS (pg 12-13)		15' 3-POINT DRILLS (pg 12-13)						20' 3-POINT DRILLS (pg 12-13)						25' 3-POINT DRILLS (pg 14-15)																															
MODELS		1205NT		1300	1300F	1200	3PNG12	1500	1510	3PNG15	1510HDF	1510HDP	1525P	2000	2010	2010HDF	2010HDP	2020F	2020P	2025F	2025P	2025A	2510HDF	2510HDP	2520F	2520P	2525A	2525F	2525P																						
TYPE		End Wheel Pull-Type		End Wheel Pull-Type		3-Point Mounted		3-Point Mounted						3-Point Mounted						3-Point Mounted						3-Point Mounted																									
PRIMARY DESIGN		No-Till		Min-Till		Min-Till (No-Till w/cph or pfh)		Min-Till (No-Till w/cph or pfh)						Min-Till to No-Till						Min-Till to No-Till						Min-Till to No-Till																									
ROW SPACINGS		7 1/2" (19.1cm)		6" (15.4cm), 7 1/2" (19.1cm) 10" (25.4cm)		6" (15.4cm) 7" (17.8cm) 7 1/2" (19.1cm) 8" (20.3cm)		7" (17.8cm) 7 1/2" (19.1cm) 10" (25.4cm)		7 1/2" (19.1cm) 10" (25.4cm)		10" (25.4cm) 15" (38.1cm)		TR30 TR30 w/ split		6" (15.4cm) 7" (17.8cm) 7 1/2" (19.1cm) 8" (20.3cm)		7" (17.8cm) 7 1/2" (19.1cm) 10" (25.4cm)		7 1/2" (19.1cm) 8" (20.3cm) 9 1/2" (24.1cm)		9 1/2" (24.1cm) 10" (25.4cm)		TR36 TR38, TR40 TR3615		7 1/2" (19.1cm) 10" (25.4cm)		7 1/2" (19.1cm) 8" (20.3cm)		9 1/2" (24.1cm) 10" (25.4cm)		9 1/2" (24.1cm) 15" (38.1cm)		9 1/2" (24.1cm) 10" (25.4cm)																	
NUMBER OF OPENERS		19		26, 21, 16		24, 20, 19		19, 14		30, 26, 24, 22		26, 24, 22		24, 14		24, 19, 13, 12, 19		40, 34, 32, 30, 24		34, 32		32, 25, 17, 16, 25		32, 30, 26, 16, 16, 24		26, 16, 16, 12, 12, 12		26, 25, 16, 16, 25, 12		12, 12, 12, 12		40, 29, 20, 20, 29		40, 36, 32, 29, 19, 20, 20, 29, 16, 16, 16		30, 20, 20, 16, 16, 16, 16, 16		32, 29, 19, 20, 29, 16, 16, 16, 16													
TIRE SIZE		297/75R 22.5 Rib Truck Tires		7.5 x 20, 4-ply Rib Implement		9.5Lx15		9.5Lx15						11Lx15						11Lx15						11Lx15																									
H.P. REQUIREMENTS (min)		75+		65+		85+ (63kw)		110+ (82kw)						250+ w/MFWD (186kw)						275+ w/MFWD (205kw)						60+ (42kw)																									
WEIGHT (approx. range)		5965 (2705kg)		3455-4155 (1567-1871kg)		2359-2959 (1070-1342kg)		2395-2480 (1086-1125kg)		3093-3573 (1403-1621kg)		3489-3801 (1583-1724kg)		3243-3335 (1471-1513kg)		4200-4950 (1905-2245kg)		4780-5530 (2168-2508kg)		4450-5920 (2018-2685kg)		3820-4780 (1733-2168kg)		4252-5032 (1929-2282kg)		5860-6820 (2658-3094kg)		5290-7620 (2400-3456kg)		4816-8376 (2185-3799kg)		4960-8760 (2250-3900kg)		5346-8598 (2490-4042kg)		5490-8910 (2494-3538kg)		5500-7800 (2803-3937kg)		6180-8680 (2805-4735kg)		7190-9370 (3261-4250kg)		6183-10439 (2892-4953kg)		6375-10199 (3356-4089kg)		7400-10800 (3124-4815kg)		6888-10616 (3211-4909kg)	
DIMENSIONS		12' (3.66m)		13' (3.96m)		12' (3.66m)		15' (4.57m)						20' (6.10m)						25' (7.62m)						25' (7.62m)																									
WORKING WIDTH		15' 7" (4.75m)		15' 2" (4.62m)		12' (3.66m)		15' 11" (4.85m)						21' (6.4m)						25' 2" (7.67m)						25' 2" (7.67m)																									
WIDTH (transport)		13' 7" (4.14m)		12' 6" (4.62m)		62" (1.57m)		9' 9" (2.97m)						9' 9" (2.97m)						9' 9" (2.97m)						9' 9" (2.97m)																									
LENGTH (transport)		13 1/2" (3.43cm)		9" (22.9cm)		1' 5" (43.2cm)		{depends on 3-point hitch}						{depends on 3-point hitch}						{depends on 3-point hitch}						{depends on 3-point hitch}																									
CLEARANCE (transport)		7' (2.13m)		5' 6" (1.68 m)		8' 4" (2.54m)		6' 10" (208cm)																																											