

MODEL INFO	MXP040-03	TRXP046-03	TRXP055-03	TRXP066-03
WORKING WIDTH	13'	15'	18'	21' 8"
TRANSPORT WIDTH	13'	9' 8"	9' 8"	9' 8"
TRANSPORT HEIGHT	NA	10' 8"	12' 2"	14'
H.P. REQUIREMENTS*	110 to 170	140 to 180	160 to 220	200 to 260
EST. OPERATING WEIGHT*	5,380 lbs.	8,079 lbs.	10,471 lbs.	11,982 lbs.
WEIGHT PER BLADE	180	224	238	230
NUMBER OF DISCS	30	36	44	52
DISC SPACING	10"	10"	10"	10"
GANG ANGLE	9° to 25° (with fully adjustable option)			
NUMBER OF SECTIONS	1	3	3	3

*Based on 3-way angle adjustment and ML Roller
Specifications are subject to change without prior notification.

Type:

Primary or Secondary Tillage Tool

Standard Equipment:

- 20" notched blades
- 10" spacing (Net 5")
- MaxLift Roller
- Adjustable gang angle
- Roller scrapers
- Front & rear lights
- Hydraulic weight transfer on traile models (fixed pressure)

Optional Equipment:

- Hitches
- Rear drawbar



3-Point Mounted Version with Optional ST Bar attached

Alternative & Optional Equipment



ST BAR (MOUNTED X-PRESS) - Add an ST Bar ahead of the Mounted X-Press and the machine is transformed into a one-pass cultivator that can restructure the soil, taking out compaction caused by harvest traffic down to a depth of 10".



SMALL SEEDS APPLICATOR - Ideal for OSR and cover crop establishment



Great Plains Ag



@GreatPlains_Ag



Great Plains Ag