

	8118RT	8120RT	8122RT	8124RT	8126RT
Inside Length	18'	19'4"	22'	24'8"	26'
Inside Width	97"	97"	97"	97"	97"
Inside Height w/out ext.	72"	72"	72"	72"	72"
Inside Height w/14" ext.	85.5"	85.5"	85.5"	85.5"	85.5"
Overall Length	19'1"	21'1"	23'1"	25'9"	27'1"
Overall Width	102"	102"	102"	102"	102"
Overall Height w/out ext. (Top of Gate)*	103.5"	103.5"	103.5"	103.5"	103.5"
Overall Height w/14" ext. (Top of Gate)*	115.5"	115.5"	115.5"	115.5"	115.5"
Overall Side - Height no ext./ext.*	88.25/102"	88.25/102"	88.25/102"	88.25/102"	88.25/102"
Stringer Width (Truck/Trailer Mount)	33.5"	33.5"	33.5"	33.5"	33.5"
Capacity (struck level) cu. ft. w/out ext.	880	960	1075	1200	1260
Capacity (struck level) cu. ft. w/14" ext.	945	1110	1280	1400	1495
SPECIFICATIONS					
Maximum Net Load (off road rating)	25 ton	25 ton	25 ton	25 ton	25 ton
Apron Chains (Pintle)	667XH	667XH	667XH	667XH	667XH
Rear Drive Shaft	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT
Power Source/DIRECT GEARDRIVE	Hyd.	Hyd.	Hyd.	Hyd.	Hyd.-Dual
Upright Spacing	16" on center	16" on center	16" on center	16" on center	16" on center
Upright/Cross Member Construction	2"x 2" Tubing	2"x 2" Tubing	2"x 2" Tubing	2"x 2" Tubing	2"x 2" Tubing
Enclosed Side Frame/Cross Member Union	NA	NA	NA	NA	NA
Unloading Time (Dependent of Hyd. System)	40 sec.	40 sec.	40 sec.	40 sec.	50 sec.
FEATURES					
Clad Tuff Fiberglass Woven Side Panels	Standard	Standard	Standard	Standard	Standard
Stainless Steel Side Panels	Optional	Optional	Optional	Optional	Optional
Solid Poly Floor-High Molecular	Standard	Standard	Standard	Standard	Standard
Rear Gate Delay System *New RT Design!!	Optional	Optional	Optional	Optional	Optional
Automatic Rear Door Unlatch/Latch	Standard	Standard	Standard	Standard	Standard
Hydraulic Drive	Standard	Standard	Standard	Standard	Standard
Double Viewing Window in front gate	Standard	Standard	Standard	Standard	Standard
Rear Transport Lights - LED (new location)	Standard	Standard	Standard	Standard	Standard
Marker/Clearance Lights (LED) & D.O.T. Tape	Optional	Optional	Optional	Optional	Optional
Personalized Farm Name on Sides	Standard	Standard	Standard	Standard	Standard
OPTIONS					
14" Removable Side Extension (screen or solid) +optional fold-down front ext. except w/tarp	Optional	Optional	Optional	Optional	Optional
Double Center Opening Doors Hyd/Air (Barn Doors)	Optional	Optional	Optional	Optional	Optional
Grain Kit / Quick Attach for Top Pivot Door	Optional	Optional	Optional	Optional	Optional
Grain Kit / Quick Attach for Barn Pivot Door	Optional	Optional	Optional	Optional	Optional
Side-mtd, LED Turn Signals in addition to std	Optional	Optional	Optional	Optional	Optional
Reversing Apron Feature	Optional	Optional	Optional	Optional	Optional
Side Hood Deflector/backstop (RH side)	Optional	Optional	Optional	Optional	Optional
Black paint in lieu of Red	Optional	Optional	Optional	Optional	Optional
Truck Mount Kit w/steel fenders	Optional	Optional	Optional	Optional	Optional
Factory Installation of Truck Mount Kit	Optional	Optional	Optional	Optional	Optional
Wagon/Trailer Mount Kit	Optional	Optional	Optional	Optional	Optional
TARP SYSTEMS					
Front to Back Scissor Tarp (Electric)	Optional	Optional	Optional	Optional	Optional
Side-to-Side Roll Tarp (Electric)	Optional	Optional	Optional	Optional	Optional