

	Replaces 4500 Series	
Front Unload	RT516	RT518
<b>DIMENSIONS</b>		
Floor Length	16'6"	18'6"
Overall Length	19'8"	21'8"
Inside Height (without roof)	std height	6'3"
	high sides	7'3"
Overall Height (without roof) - top of side	std height	94"
	high sides	106"
Less 4" truck & trailer mounts (except on XT1600 trailer*)		
Overall Height (with roof) - wagon mount version	std height	114.5"
	high sides	126.5"
Inside Width	89.5"	89.5"
Overall Width with conveyor extension up	109.5"	109.5"
Stringer Width/Height		
truck/XT2200 trailer mount	33.5"/6"	33.5"/6"
wagon mount	42"/10"	42"/10"
Capacity (struck level) cu. ft. (without roof)	(6'3") std height	769
	(7'3") high sides	862
Capacity cu. ft. (with roof)	(6'3") std height	944
	(7'3") high sides	1058
<b>SPECIFICATIONS</b>		
Front Apron Drive Shaft	2"	2"
Tubular Upright Spacing	24"	24"
All Steel Frame - 24" centers (no wood)	24"	24"
HD Tubular Floor Supports	2x2	2x2
HD Top Rail Formed (no side supports needed)	Std	Std
Commercial Grade Geardrive (no worm gears)	Std	Std
<b>STANDARD FEATURES</b>		
RT Variable Speed System - 0-17'/minute (PTO drive standard)	Std	Std
Apron Chains (heavy duty pintle)	667H	667H
Auger Feathering System & Conveyor Clutch/Safety Clutch	Std	Std
Cross Conveyor Chain Hold-Downs	Std	Std
Fold-Down Conveyor Extension with Lift Assist	Opt	Opt
<i>Superslide</i> , Solid Poly Floor (no plywood)	N/A	N/A
<b>OPTIONAL EQUIPMENT</b>		
Hydraulic Front Drive System (in lieu of PTO)	Opt	Opt
Hydraulic In-Cab Controls (in lieu of PTO) - includes hyd lift conveyor	Opt	Opt
36" Fold-Down Cross Conveyor Extension (in lieu of 24")	Opt	Opt
Hydraulic Lift Option for Fold-Down Cross Conveyor Extension	Opt	Opt
Roof Assembly (removable)	Std	Std
6" Higher Roof Assembly (removable) - not avail. 12" higher sides	Opt	Opt
Roof Hood Assembly (right hand, open top units only)	Opt	Opt
Truck Mount/Trailer Mount/Wagon Mount	Opt	Opt
Tarp Systems (with front enclosures)		
Front to Back Scissor Tarp (electric)	Opt	Opt
Side to Side Roll Tarp (electric)	Opt	Opt
Clad Tuff Fiberglass Sides & Back	Opt	Opt
12" Higher Sides with 4th Beater System	N/A	N/A

	Replaces 4600 Series			
Front Unload	RT616	RT618	RT620	RT622
<b>DIMENSIONS</b>				
Floor Length	16'6"	18'6"	20'6"	22'6"
Overall Length	19'8"	21'8"	23'8"	25'8"
Inside Height (without roof)	std height	6'3"	6'3"	6'3"
	high sides	7'3"	7'3"	7'3"
Overall Height (without roof) - top of side	std height	94"	94"	94"
	high sides	106"	106"	106"
Less 4" truck & trailer mounts (except on XT1600 trailer*)				
Overall Height (with roof) - wagon mount version	std height	114.5"	114.5"	114.5"
	high sides	126.5"	126.5"	126.5"
Inside Width	89.5"	89.5"	89.5"	89.5"
Overall Width with conveyor extension up	109.5"	109.5"	109.5"	109.5"
Stringer Width/Height				
truck/XT2200 trailer mount	33.5"/6"	33.5"/6"	33.5"/6"	33.5"/6"
wagon mount	42"/10"	42"/10"	42"/10"	42"/10"
Capacity (struck level) cu. ft. (without roof)	(6'3") std height	769	862	956
	(7'3") high sides	892	1000	1108
Capacity cu. ft. (with roof)	(6'3") std height	944	1058	1174
	(7'3") high sides	1067	1196	1326
<b>SPECIFICATIONS</b>				
Front Apron Drive Shaft	2"	2"	2"	2"
Tubular Upright Spacing	24"	24"	24"	24"
All Steel Frame - 24" centers (no wood)	24"	24"	24"	24"
HD Tubular Floor Supports	2x2	2x2	2x2	2x2
HD Top Rail Formed (no side supports needed)	Std	Std	Std	Std
Commercial Grade Geardrive (no worm gears)	Std	Std	Std	Std
<b>STANDARD FEATURES</b>				
RT Variable Speed System - 0-17'/minute (PTO drive standard)	Std	Std	Std	Std
Apron Chains (heavy duty pintle)	667X	667X	667X	667X
Auger Feathering System & Conveyor Clutch/Safety Clutch	Std	Std	Std	Std
Cross Conveyor Chain Hold-Downs	Std	Std	Std	Std
Fold-Down Conveyor Extension with Lift Assist	Std	Std	Std	Std
Superslide, Solid Poly Floor (no plywood)	Std	Std	Std	Std
<b>OPTIONAL EQUIPMENT</b>				
Hydraulic Front Drive System (in lieu of PTO)	Opt	Opt	Opt	Opt
Hydraulic In-Cab Controls (in lieu of PTO) - includes hyd lift conveyor	Opt	Opt	Opt	Opt
36" Fold-Down Cross Conveyor Extension (in lieu of 24")	Opt	Opt	Opt	Opt
Hydraulic Lift Option for Fold-Down Cross Conveyor Extension	Opt	Opt	Opt	Opt
Roof Assembly (removable)	Std	Std	Std	Std
6" Higher Roof Assembly (removable) - not avail. 12" higher sides	Opt	Opt	Opt	Opt
Roof Hood Assembly (right hand, open top units only)	Opt	Opt	Opt	Opt
Truck Mount/Trailer Mount/Wagon Mount	Opt	Opt	Opt	Opt
Tarp Systems (with front enclosures)				
Front to Back Scissor Tarp (electric)	Opt	Opt	Opt	Opt
Side to Side Roll Tarp (electric)	Opt	Opt	Opt	Opt
Clad Tuff Fiberglass Sides & Back	Opt	Opt	Opt	Opt
12" Higher Sides with 4th Beater System	Opt	Opt	Opt	Opt