



Our hydrostatic drive system (HST) eliminates gear-shifting by safely engaging color-coded forward or reverse pedals. Combining HST with supersmooth joystick control makes front loader work fast and efficient.



Our newest feature, Crank Assist<sup>™</sup>, safely takes you stepby-step through the tractor's start-up process.



Electric PTO engagement for your mid and rear implements designed to prevent accidental activation.

1 US

.



OJA is a world-class software and hardware technology platform created to improve your Mahindra's performance and safeguard your investment. With the new MyOJA phone app, you'll always be able to communicate with your tractor and local dealer. Features include real-time tractor health warnings and alerts, customized geofencing, security features, and more.

mahindra

9020 Jackrabbit Road, Suite 600 Houston, Texas 77095 (877) 449-7771 mahindrausa.com mahindracanada.ca

local Mahindra dealer and the product operation manual. Engine power (hp/kw) and other specifications are based on various standards and best practices. This brochure is intended for the United States and its territories only. For more information visit our website. **Rev 04302024** 

OFFICIAL

TRACTOR

OF TOUGH



SUBCOMPACT CLASS



20-25 HP



# **PUNCHES ABOVE** THEIR WEIGHT CLASS.

Meet the newest subcompact class of fighters ... the Mahindra 1120 and Mahindra 1126. They're smart, friendly, and tough tractors. Phone app lovers will be pumped by their intelligent Mahindra MyOJA software. First-time operators will smile at Smart Assist and their intuitive cockpits. Weekend warriors will be rocked when testing their mettle. Discover why the Mahindra 1100 Series will deliver every day, every time, for the small acreage or estate homeowner.

#### www.mahindrausa.com

## **IDEAL USES**

Planting a garden Landscaping projects Material handling Trenching Mowing lawn & pastures Spreadings weed & feed Fence work Grading driveways Clearing snow



# **SMARTER.** TOUGHER.

**POWER:** The Mahindra 1100 Series has a formidable engine powering its mid and rear PTOs. Its robust hydraulic pumps command steering, attachment, and simple operations.


**ADVANCED:** Mahindra MyOJA phone app connects and empowers the homeowner to their tractor's diagnostics. Other 1100 Series features include push-button PTO activation for both mid and rear implement work and no-hassle hydrostatic forward & reverse pedals with a buttery joystick for super fast loader work.

**EASE OF USE:** The Mahindra 1100 Series touts features like Crank Assist<sup>™</sup>. intuitive controls, tilt power steering, a form-fitting mComfort seat, and a wellappointed heated cab.

The Mahindra 1100 Series ROPS cab (Rollover Protection Structure) is designed, fabricated, and fitted at our assembly plant. It can be heated quickly and efficiently to provide warmth on extremely cold days. Additionally, the glass-enclosed cab provides a 360-degree view and includes work lights, mirrors, and wipers to deliver an exceptional experience, setting a new class standard.



Try sitting on a tractor all day, and then you'll see why the 1100 series comes standard with power steering and a form-fitting mComfort seat our most comfy combo yet.



Easy-to-use levers, knobs, and pedals are labeled for easy reference and ergonomically placed for no-hassle use.



Our projector-style headlights offer bright, white lighting for after-dark chores.



### NO DPF (DIESEL PARTICULATE FILTER) MEANS:

- No regen downtime No wasted fuel
- No wasted warranty hours Quieter operation
- Fewer parts to replace

ENGINE	1120 HST	1126 HST
Brand & Model	Mitsubishi MVL3E3	
Туре	Four-stroke, Naturally Aspirated, Indirect Injection, Water-cooled Diesel Engine	
Cylinders		3
Engine HP (kW) @ RPM	20.1 (15.0) @ 2900	25.3 (18.9) @ 2900
Compression Ratio	22:1	
Displacement cubic inch <sup>3</sup> (cc)	67.2 (1102)	
Fuel Tank Capacity gallons (L)	6.6	6 (25)
ELECTRICAL		
Battery Capacity	12 volt, 650 CCA	
Alternator	12 volt, 55 A	
TRANSMISSION		
Туре	HST - 2 range	
Number of Speeds	Infinite	
STEERING		
Туре	Hydrostatic Power	
BRAKES		
Туре	Single Pedal	
HYDRAULIC SYSTEM		
Туре	Open center, full-live hydraulic with position control	
Pump Output (gallons per minute)	11.2	
Loader Lift Capacity (lb.)	792	
3-pt Linkage	CAT I with Check Chains	
3 pt Lift Capacity (lb.) 24-inch from pin	770	
Rear Auxiliary Remote Valves	Optional Single or Dual	
РТО		
Туре	Live	
PTO RPM (Rear)	540 @ 2837	
PTO RPM (Mid)	2500 @ 2837	
PTO HP (kW)	13.9 (10.4)	19.2 (14.3)
OPERATING WEIGHT		
Total Operating Weight (lb.)	1576 OS / 1916 Cab	
DIMENSIONS		
Overall Length Inches (mm)	100.4 (2550)	
Overall Width Inches (mm)	46.3 (1177)	
Overall OS Height Inches (mm)	86.6 (2200)	
Overall Cab Height Inches (mm)	80.5 (2044)	
Turning Radius Min. Feet (meters)	7.2 (2.2)	
TIRES SIZES & OPTIONS		
Industrial (Front / Rear)	18 x 8.5 - 10 / 26 x 12 - 12	
Turf (Front / Rear)	16 x 7.5 - 10 / 24 x 12 - 12	

Note: Specifications and design subject to change without notice.



NO