



eMax S SERIES

- #1 Selling Tractor in the World
- 98% Customer Loyalty Rating
- 7-year Limited Powertrain Warranty



DEMING PRIZE 2003



JAPAN QUALITY MEDAL 2007

Mahindra
Tractors

SUB-COMPACT VERSATILITY

- eMax S Series

The new Tier IV emissions-compliant eMax S sub-compact tractors have once again redefined the sub-compact market with tractors that offer true tractor performance. Featuring a complete range of available attachments and implements including a drive-over mower deck, snow removal equipment and a backhoe that can be added at any time, you have a powerful and versatile tractor that provides the industry's best value.

Key Features:

- Versatility – A wide range of available implements to handle any task
- Maneuverability – Best in class turning radius to get work done in tight spaces
- Comfort – Express seat with Backhoe for easy turn around operation, easy on and off with an open platform
- Safety – Bigger tires, better traction, stability and safety for all jobs
- Lift Capacity – More loader lift and more 3-point lift means Push More, Pull More and Lift More to get more done
- Engine Performance – Lower RPMs results in smooth, quiet operation and maximum fuel efficiency
- Available fabricated (not stamped) Drive-Over Mower Deck for quick connect and disconnect features faster blade tip speed for better cut quality
- 7-year limited powertrain warranty*
- Twin Pedal HST or economical gear drive

Ideal For:

- Speciality / Hobby Farming
- Rural Lifestyle
- Equine
- Home
- Grounds Maintenance / Municipal

*See Mahindra warranty and your dealer for details



Engine Left



Hitch



Platform

- Easy-open hood
- Removable side panels
- Powerful Tier IV engine
- Service items in easy reach

- Full-size Cat I hitch lifts most in class
- Large draw bar
- Standard 540 RPM PTO

- Instrument panel in clear view
- Warning lights quickly inform operator when service required
- Two-pedal HST makes operation easy and comfortable
- Operator seat swivels for backhoe use

EXCEPTIONAL PERFORMANCE. GREAT VALUE.



Engine – Four-stroke, indirect-injection, water-cooled diesel

Transmission – HST – 2 ranges and sliding with synchromesh on 2nd range

Hydraulics – Open center, full live

Operating Weight – 1,540 to 1,870 (varies by model) – sturdy, well-built steel subcompact chassis

Horsepower – 22, 24

Tires – Ag, industrial or turf

Loader – Lift up to 900 lbs. at 75.3" with the eMAX 25L-S front loader

Warranty – 7-year limited powertrain (see Mahindra warranty and your dealer for details)



eMax S 25 HST



eMax S 22 Gear

AVAILABLE IMPLEMENTS


Mahindra offers a huge selection of implements to help you accomplish whatever task you wish to tackle and provide a complete Mahindra experience.

- Wide array of implements (186 variations)
- Competitive financing terms
- Standard-, Medium-, and Heavy-Duty implements to meet your needs
- Implements feature rugged construction with heavy-duty components
- 5-year rotary cutter gearbox limited warranty
- SNOW BLOWERS and SNOW REMOVAL equipment to meet cold-weather needs
- BEST VALUE in the market today



TRACTOR ATTACHMENTS

TRACTOR	eMax S 22 Gear	eMax S 22 HST	eMAX S 25 HST	eMAX S 25 HST Cab
LOADER	EMAX 25L-S			EMAX 25L-S
Maximum Lift Height		75.3"		75.3"
Clearance with Attachment Dumped		57.4"		57.4"
Reach at Maximum Height		24.9"		24.9"
Maximum Dump Angle		38°		38°
Attachment Rollback Angle		20°		20°
Digging Depth Below Grade		4.1"		4.1"
Lift Capacity to Full Height @ Pivot Pins		900		900
Breakout Force @ Pivot Pins		2000		2000
Rated Flow (Tractor System)		4.6 gpm		4.6 gpm
Attachment Width		50"		50"
Attachment Rated Capacity		5.3 cu. ft.		5.3 cu. ft.
Cycle Times @ rpm		2500		2500
Raise Boom (seconds)		4.4		4.4
Lower Boom (seconds)		2.5		2.5
Dump Attachment (seconds)		5.3		5.3
Retract Attachment (seconds)		3.8		3.8
Transport Weight (lbs.)		507		507
BACKHOE MODEL		eMax 26B		N/A
TRANSPORT				
Transport Height		70"		N/A
Transport Overhang		37"		N/A
Transport Weight (lbs.)		710		N/A
OPERATIONAL				
Maximum Digging Depth		76.3"		N/A
Digging Depth (2 Ft.) Flat Bottom		74.9"		N/A
Overall Operating Height - Fully Raised		104.8"		N/A
Loading Height (bucket @ 60°)		62"		N/A
Loading Reach (bucket @ 60°)		36"		N/A
Reach From Swing Post		102"		N/A
Bucket Rotation		180°		N/A
Swing Arc		150°		N/A
Stabilizer Spread Operating Position		74"		N/A
Stabilizer Down Below Grade		6"		N/A
System Relief Valve Setting		2000		N/A
Digging Force - Bucket (lbs.)		2145		N/A
Digging Force - Dipper (lbs.)		903		N/A



TRACTOR SPECIFICATIONS



TRACTOR	eMax S 22 Gear	eMax S 22 HST	eMAX S 25 HST	eMAX S 25 HST Cab
ENGINE				
Type	Four stroke, indirect injection water-cooled diesel			Four stroke, indirect injection water-cooled diesel
Cylinders	3			3
Engine HP (kW) @ rpm	22 [16.4] @ 3000		24 [17.9] @ 3000	24 [17.9] @ 3000
Compression Ratio	21:1			21:1
Displacement cubic inch ³ (cc)	61.5 [1007]			61.5 [1007]
Fuel Tank Capacity	5.8 gallons			5.8 gallons
ELECTRICAL				
Battery Capacity	12V 50AH			12V 50AH
Alternator	12V 50A			12V 50A
CLUTCH				
Type	Single plate, dry			Single plate, dry
TRANSMISSION				
Type	Mechanical	HST - 2 ranges		HST - 2 ranges
Number of Gears / Speeds	6F / 2R	Infinite		Infinite
STEERING				
Type	Hydrostatic Power			Hydrostatic Power
Pump Output (gallons per minute)	2.6			2.6
BRAKES				
Type	Wet disc			Wet disc
HYDRAULIC SYSTEM				
Type	Open center, full live hydraulic			Open center, full live hydraulic
Pump Output (gallons per minute)	4.5			4.5
3-Point Linkage	Category 1, with check chains			Category 1, with check chains
Lift Capacity (lbs.)	1320			1320
Rear Auxiliary Remote Valves	1 spool optional			1 spool optional
PTO				
Type	Trans	Independent		Independent
PTO RPM (engine rpm)	540 @ 2893			540 @ 2893
Mid PTO RPM (engine rpm)*	2000 @ 2875			2000 @ 2875
PTO HP (kW)	15.9 [11.8]	14.9 [11.1]	16.9 [12.6]	16.9 [12.6]
OPERATING WEIGHT				
Total (lbs.)	1540			1870
DIMENSIONS with Ag Tires				
Overall Length Inches (mm)	100.5 [2553]			100.5 [2553]
Overall Width Inches (mm)	50.8 [1290]			50.8 [1290]
Overall Height Inches (mm)	89.7 [2278]			78.2 [1986]
Turning Radius Minimum Feet (meters)	7.2 [2.2]			7.2 [2.2]
TIRES Sizes and Options				
Ag (Front / Rear)	6x12 / 9.5x16			6x12 / 9.5x16
Industrial (Front / Rear)	20x8-10 / 27x12.5-15			20x8-10 / 27x12.5-15
Turf (Front / Rear)	20x8-10 / 29x12.5-15			20x8-10 / 29x12.5-15

Specifications and design subject to change without notice.

9020 JACKRABBIT RD., Suite 600 • Houston, Texas 77095 • 877-449-7771

MahindraUSA.com • MahindraCanada.com

© 2017 Mahindra N.A. MAH-0817 MAH54eMaxS