

Mahindra 2600

SERIES

38 - 65 HP Tractor

MORE POWER, PERFORMANCE & VALUE



WORLD'S #1 SELLING TRACTOR



TOP 5 MAJOR ADVANTAGES

NO DIESEL PARTICULATE FILTER

- Eliminates lost time, maintenance, and high heat for better overall operator comfort, NO Regeneration Cycle

ENGINE DISPLACEMENT

- From 8% - 45% larger displacement than the competition with lower operating RPM for quieter operation and a longer life

mCOMFORT™ SEAT

- Extra cushion with integrated armrests and retractable belt for ultimate operator comfort

EASY TO ENTER

- Flattest operator station in it's class with a full rubber mat allows easy entry and helps filter vibration for better operator comfort

INDUSTRY LEADING WARRANTY

- 7 year/3000 hour no deductible powertrain warranty provides ultimate peace of mind



**3000 HOURS.
NO DEDUCTIBLE.
BEST IN THE INDUSTRY!**



MAHINDRA ADVANTAGE

ENGINE

3 Cylinder mCRD™ High Pressure Common Rail Tier IV

- Long-lasting, easy to service wet-sleeved, intercooled and turbocharged
- Varying fuel tank sizes to get your work done

mCRD™ with NO Particulate Filter

- Eliminates wasted fuel due to NO Regeneration Cycle
- Eliminates high heat
- Eliminates high maintenance
- Eliminates high operator involvement

JUST GET ON & GO!

MAHINDRA ADVANTAGE

SERVICE

- Ease of access for radiator, battery, filter replacement and oil check
- The hood opens vertically & side panels come off quickly. NO TOOLS REQUIRED
- Tier IV compliant



MAHINDRA ADVANTAGE

mCOMFORT™ SEAT

- US designed and manufactured with industry-leading comfort and support
- Retractable seat belt for greater operator ease of use
- Foldable armrest and recline feature to suit each operator's preference
- Vinyl covering on open station models for excellent durability in the elements
- Cloth covering on cab models
- Adjustable mechanical suspension standard

MAHINDRA ADVANTAGE

CAB

- Flat deck and ergonomic operator platform
- Spacious and comfortable cab with standard heater and air conditioning
- Wide opening doors on left and right
- Excellent visibility to loader
- Front window wiper is standard (optional rear)
- Bluetooth radio, USB port, 12V socket come standard



OUTSTANDING PERFORMANCE. GREAT VALUE.



Reinforced Steel Fenders and Hood

Easy Access to Battery, Air Filter and Fuel Tank

Stylish Grill and Headlight Assembly

Push Button Controls

HVAC (Cab)

Bluetooth Radio, USB Port, 12V Standard (Cab)

Fender Mounted Loader Joystick

mComfort Suspension Seat

Easy Access Flat Platform

Rear Remote Valves
(optional or standard depending on model)

ENGINE

Four-stroke, direct-injection, turbo-charged and intercooled diesel (no DPF) or naturally aspirated direct-injection diesel (2638 & 2645)

TRANSMISSION

Synchro shuttle 12 forward and reverse with partial synchromesh on 2645, 2655 & 2665 or 3 range HST on 2638 & 2655

HYDRAULICS

Open center

OPERATING WEIGHT

3,130 to 5,070 lbs. (varies by model) - sturdy, well-built, steel chassis

HORSEPOWER

37.4, 44, 55, 65

LOADER

Lift up to 3,122 lbs. at 115.4" high with the 2665CL front loader

WARRANTY

7-year limited powertrain (see Mahindra warranty statement and your dealer for details)

MAHINDRA ADVANTAGE IMPLEMENTS

Mahindra offers a large selection of implements to help you accomplish whatever task you wish to tackle and provide a complete Mahindra experience.

**GET YOUR
WORK DONE**

Mahindra

- Wide array of implements with 186 variations
- Standard-, medium-, and heavy-duty implements to meet your needs
- Rugged construction with heavy-duty components
- 5-year rotary cutter gear box limited warranty
- Snow blowers and snow removal equipment to meet cold-weather needs
- Best value in the market today



MAHINDRA ADVANTAGE BACKHOE

COMPATIBLE WITH	60B 2638 / 2645	65B 2655 / 2665
Transport Height (in.)	88	98
Transport Overhang (in.)	50	65
Max Dig Depth (in.)	95	108
Dig Depth (2' Flat Bottom) (in.)	94	104
Overall Operating Height Fully Raised (in.)	122	121
Loading Height (Bucket @ 60°) (in.)	73	90
Loading Reach (Bucket @ 60°) (in.)	96	66.3
Reach from Swing Post (in.)	129	150
Bucket Rotation	180°	180°
Swing Arc	180°	180°
Stabilized Spread - Down (in.)	92	90
Stabilizer Down - Below Grade (in.)	9	10
Digging Force - Bucket (lbs.)	3,439	3,800
Digging Force - Dipper (lbs.)	2,214	2,400
Transport Weight (lbs.)	1,250	1,100

- Curved Boom
- Comfortable Operators Platform
- Mechanical thumb kit option
- Fits on both open station and cab models
- Easy to remove when not in use
- No change in ground clearance with backhoe installed

Ask your dealer about big savings when you add Mahindra Implements with your New Mahindra tractor



MAHINDRA ADVANTAGE LOADER

TRACTOR	2638 HST	2638 HST Cab	2645 Shuttle	2645 Shuttle Cab	2655 Shuttle	2655 HST	2655 Shuttle Cab	2655 HST Cab	2665 Shuttle Cab
LOADER	2638L	2638CL	2645L	2645CL	2655L		2655CL		2665CL
Maximum Lift Height (in.)	101.4		101.9		115.4				
Clearance with Bucket Fully Dumped (in.)	79.3		73		82.3				
Reach at Maximum Dump Angle (in.)	21.5		21.9		23				
Maximum Dump Angle	40°		42°		69°				
Attachment Rollback Angle	30°		35°		39°				
Digging Depth Below Grade (in.)	4.5		4.8		5.2				
Lift Capacity to Maximum Height at Pivot Pins (lbs.)	1634		2041		3122				
Breakout Force @ Pivot Pins (lbs.)	2696		3430		5225				
Rated Flow Tractor System (gpm)	7.6		8.2		9.5			11	
Attachment Width (in.)	66				72				
Attachment Rated Capacity (ft ³)	10.8	11.8			11.2			12.8	
Cycle Times @ rpm	2400		2600						
Raise Boom (seconds)	3.5		4.3		6				
Lower Boom (seconds)	2		3		4				
Dump Attachment (seconds)	2.6		3.5		4.9				
Retract Attachment (seconds)	1.5		2.6		3.2				
Loader Transport Weight (lbs.)	985	981	1177		1270			1318	



MAHINDRA ADVANTAGE SPECIFICATIONS

	2638 HST	2638 HST Cab	2645 Shuttle	2645 Shuttle Cab	2655 Shuttle	2655 Shuttle Cab	2655 HST	2655 HST Cab	2665 Shuttle Cab
ENGINE:									
Displacement (in ³)	166.7				161.5				
Engine HP @ rpm	37.4 @ 2400		44 @ 2600		55 @ 2300			65 @ 2300	
Number of Cylinders	4				3				
Fuel Tank Size (gal)	9				16			18.5	
ELECTRICAL:									
Battery Capacity	12V 80 AH				12V 96 AH				
Alternator	12V 90 A								
TRANSMISSION:									
Type	HST - 3 Range		Synchro Mesh				HST - 3 Range		Synchro Mesh
No. of Speed	Infinite	Infinite	12F / 12R	12F / 12R	12F / 12R	12F / 12R	Infinite	Infinite	12F / 12R
STEERING:									
Type	Hydrostatic								
Pump Output (gpm)	4.1		4.5		5			5.4	
BRAKES:									
Type	Wet Disc								
POWER TAKE OFF:									
PTO RPM Rear	540 @ 2385		540 @ 2650		540 @ 2300				
PTO HP	31	29.5	35	33.5	44.5			50	
Mid (optional)	2000		NA				2000		NA
HYDRAULICS:									
Max Total Flow (gpm)	7.6	7.6	8.2	8.2	9.5	9.5	9.7	9.7	11
Category, 3 Pt Hitch	Cat 1								Cat 2
Hitch Lift Capacity (lbs.)	2646				3314			3528	
Lift Control Type	Open Center with Position Control								Position/Draft
Rear Hydraulic Remote Valves	1 Spool Optional				1 Spool Standard				
DIMENSIONS:									
Minimum Ground Clearance (in.)	12.8				13.8			15.4	
Overall Height (in.)	94.5				102			99.2	
Overall Length (in.)	119.3				135			142	
Overall Width (in.)	63.2				71.1			71.5	
Weight (lbs.)	3130	3351	3285	3506	4056	4299	4056	4299	5070
TIRES:									
Ag (Front / Rear)	7-16 / 11.2-24		8.3 / 12.4x24		9.5x16 / 14.9x24			9.5x20 / 14.9x28	
Industrial (Front / Rear)	10-16.5 / 43x16-20				12x16.5 / 16.9x24			10.5/80x18 / 18.4x24	
Turf (Front / Rear)	NA				LSW305-521 / LSW570-648 6PR				




We have tripled the size of our parts operation to a 120,000 square foot warehouse, which currently offers more than 40,000 items. The expansion supports and fuels our growth from order placement to shipment with same or next day shipment on all orders. In addition, the Mahindra Parts Catalog System offers 24/7 look-up and order online or via mobile app. Our product range includes spare parts for tractors, attachments and utility vehicles, plus numerous competitive items, such as lubricants, fuel additives, chemicals, anti-freeze, canopies, glopower, oil & filter service packs, radios and hitch parts.



2003 DEMING APPLICATION PRIZE 2007 JAPAN QUALITY MEDAL

The Deming Application Prize is considered the Nobel Prize for manufacturing, the farming equipment sector of Mahindra & Mahindra received the honor for establishing Total Quality Management in all business operations in 2003. Mahindra was awarded the Japan Quality Medal for excellence in 2007 for customer focus, overall quality, and business processes - the first tractor company to receive the honor.



For more information, go to:

mahindraUSA.com • mahindraCANADA.com

9020 Jackrabbit Rd., Suite 600 • Houston, Texas 77095 • 877-449-7771

©2018 Mahindra USA MAH-0218 MAH542600