

DIMENSIONS	9124RT	9126RT	9128RT	9130RT	9132RT
Inside Length	24'8"	26'	28'8"	30'	32'8"
Inside Width	98"	98"	98"	98"	98"
Inside Height - no extension	72"	72"	72"	72"	72"
Inside Height w/14" extension	85.5"	85.5"	85.5"	85.5"	85.5"
Overall Length	25'9"	27'1"	29'9"	31'1"	33'9"
Overall Width	102"	102"	102"	102"	102"
Overall Height - no extension (top of gate) *	103.5"	103.5"	103.5"	103.5"	103.5"
Overall Height w/14" extension (top of gate) *	115.5"	115.5"	115.5"	115.5"	155.5"
Overall Side Height - no ext. / ext. *	88.25/102"	88.25/102"	88.25/102"	88.25/102"	88.25/102"
Stringer Width (Truck/Trailer Mount)	33.5"	33.5"	33.5"	33.5"	33.5"
Capacity (struck level) Cu. Ft. - w/o ext.	1200	1260	1390	1460	1590
Capacity (struck level) Cu. Ft. - w14" ext.	1400	1495	1640	1720	1865
<b>SPECIFICATIONS</b>					
Maximum Net Load (off road rating)	27 ton	27 ton	27 ton	27 ton	27 ton
Apron Chains (pintle)	667XH	667XH	667XH	667XH	667XH
Rear Drive Shaft	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT	2-3/8" HD SOLID SHAFT
Power Source / <b>DIRECT GEARDRIVE</b>	hyd-dual	hyd-dual	hyd-dual	hyd-dual	hyd-dual
Upright Spacing	16" on ctr	16" on ctr	16" on ctr	16" on ctr	16" on ctr
Upright / Cross member Construction	2x2 tubing	2x2 tubing	2x2 tubing	2x2 tubing	2x2 tubing
Enclosed Side Frame/Cross Member Union	STD	STD	STD	STD	STD
Unloading Time (Dependent of Hyd. System)	50 sec	50 sec	50 sec	55 sec	50 sec
<b>FEATURES</b>					
Clad-Tuff Fiberglass Woven Side Panels	NA	NA	NA	NA	NA
Stainless Steel Side Panels	STD	STD	STD	STD	STD
Solid Poly Floor - High Molecular	STD	STD	STD	STD	STD
Rear Gate Delay System *new RT design!!	STD	STD	STD	STD	STD
Automatic Rear Door Unlatch / Latch	STD	STD	STD	STD	STD
Hydraulic Drive	STD	STD	STD	STD	STD
Double Viewing Window in front gate	STD	STD	STD	STD	STD
Rear Transport Lights - LED (new location)	STD	STD	STD	STD	STD
Marker/Clearance Lights (LED) & D.O.T. Tape	STD	STD	STD	STD	STD
Personalized Farm Name on Sides	STD	STD	STD	STD	STD
<b>OPTIONS</b>					
14" Removable Side Extension (screen or solid)	OPT	OPT	OPT	OPT	OPT
+includes fold-down front ext. <u>except w/tarp</u>					
Double Center Opening Doors Hyd/Air (Barn Doors)	OPT	OPT	OPT	OPT	OPT
Grain Kit / Quick Attach for Top Pivot Door	OPT	OPT	OPT	OPT	OPT
Grain Kit / Quick Attach for Barn Door Gate	OPT	OPT	OPT	OPT	OPT
Side-mtd, LED Turn Signals in addition to std	OPT	OPT	OPT	OPT	OPT
Reversing Apron Feature	OPT	OPT	OPT	OPT	OPT
Set Back Axle Design / Air Lift Pusher Axles	N/A	N/A	N/A	N/A	N/A
Side Hood Deflector/backstop (RH side)	OPT	OPT	OPT	OPT	OPT
Black paint in lieu of Red	OPT	OPT	OPT	OPT	OPT
Truck Mount Kit w/Steel Fenders	OPT	OPT	OPT	OPT	OPT
Factory Install of Truck Mount Kit	OPT	OPT	OPT	OPT	OPT
Wagon/Trailer Mount Kit	OPT	OPT	NA	NA	NA
<b>TARP SYSTEMS</b>					
Front to Back Scissor Tarp (electric)	OPT	OPT	OPT	OPT	OPT
Side-to-Side Roll Tarp (electric)	OPT	OPT	OPT	OPT	OPT
*Height measurements - <b>Straight Truck Mounted Units</b> require hardware which adds approximately 1.5" to height listed above					