

# WOODS BACKHOES



Powerful diggers with a reputation  
as the best built backhoe in the industry

# WOODS

## Backhoes

### Table of Contents

|                                   |          |
|-----------------------------------|----------|
| <b>BH6000</b> .....               | <b>3</b> |
| <b>BH70-X and BH80-X</b> .....    | <b>4</b> |
| <b>BH90-X</b> .....               | <b>5</b> |
| <b>Specifications Chart</b> ..... | <b>6</b> |

### Woods Groundbreaker-X

Woods has been manufacturing backhoes since 1982 and continues to be the industry leader with the most innovative, powerful, and reliable backhoes. Groundbreaker-X backhoes provide proven performance for the toughest of jobs.

The “X” means extra everything. Styled after the design used in construction equipment, Woods brings the advantages of an excavator-style curved boom to estate owners and commercial contractors.

- Extra durable – heavy-duty, construction grade Gannon® bucket
- Extra simple – easy on/easy off, no tools required
- Extra capacity – up to six bucket sizes available with greater capacity than the competition
- Extra ability – curved boom reaches over obstacles with better visibility and less repositioning than a straight boom
- Extra strong – “box section” design adds strength without weight, which harnesses lifting power
- Extra productivity – optional mechanical thumb with six adjustable positions allow for easy pickup of materials such as tree limbs and concrete chunks

### Legend

#### Standard-duty

Designed and manufactured for typical usage and basic applications.

#### Medium-duty

Designed and manufactured for harsher usage and more robust applications.

#### Heavy-duty

Designed and manufactured for extended usage and the most demanding applications.



Woods products are proudly made in the USA. As part of a global economy, we work with business partners around the world and export our equipment to international markets. Since 1946, we've been manufacturing in Oregon, Illinois, and supporting the growth of American jobs.



Maintain the quality and performance of your Woods equipment with WoodsCare genuine replacement parts, paint, and lubricants. Available from your authorized Woods dealer.

#### Find a Woods Dealer

Woods equipment is distributed through a network of authorized dealers. To find your nearest store visit us at [woodsequipment.com](http://woodsequipment.com) or call 800-319-6637.

# BH6000 Groundbreaker-X Backhoe

Built on the proven performance from our Groundbreaker® line of backhoes, the BH6000 is engineered specifically for subcompact tractors for use in tight spaces, and hard-to-reach digging and trenching jobs in the yard, garden, and pasture.

Tractor PTO range: 15–30 hp

**Model**  
**BH6000** 74-inch

- Six-foot maximum digging depth
- Three different bucket choices: 9-inch trenching, 12-inch all-purpose digging, and 16-inch max-capacity digging
- Easy transport due to high ramp angle and ground clearance
- Operates with most loaders and undermount mowers attached



**BH6000** shown with optional thumb

BH6000 Backhoe



## Extra Productivity

Optional hydraulic or adjustable mechanical thumbs allow you to easily pick up a range of materials from large tree limbs to concrete chunks.

# WOODS

## Backhoes

### BH70-X and BH80-X Groundbreaker-X Backhoes

Ideal for hard-to-reach commercial or residential digging and clean up. Designed for compact tractors.

Tractor PTO range: 18–45 hp

#### Models

|               |         |
|---------------|---------|
| <b>BH70-X</b> | 84-inch |
| <b>BH80-X</b> | 96-inch |

- Seven- and eight-foot maximum digging depths
- Bucket widths from 9- to 36-inches
- Durable, heavy-duty boom, dipper stick, and dual swing cylinders
- Many 4-point mounts compatible with OEM belly mowers
- Two-year warranty – the best in the industry
- Optional hydraulic thumb available on BH80-X



**BH80-X** shown with optional thumb



**BH70-X** shown with optional thumb



**BH90-X** shown with optional thumb

## BH90-X Groundbreaker-X Backhoe

The BH90-X has been designed to endure the most rigorous commercial operation and provide years of worry-free service.

Tractor PTO range: 30–70 hp

### Model

**BH90-X** 109-inch

- Nine-foot maximum digging depth
- Bucket widths from 12- to 36-inches
- Will dig a two-foot flat bottom at 9-foot, 1-inch below grade
- Optional hydraulic thumb available
- Two-year warranty – the best in the industry



# WOODS

## Backhoes

Specifications Chart

| Specifications                        | BH6000 WITH<br>9" BUCKET | BH6000 WITH<br>12" AND 16" BUCKET |
|---------------------------------------|--------------------------|-----------------------------------|
| Tractor PTO HP                        | 15–30 hp                 |                                   |
| Digging Depth – 2' Flat Bottom        | 74"                      | 72.5"                             |
| Digging Depth – 8' Flat Bottom        | 47"                      | 44"                               |
| Reach From Swing Pivot                | 98"                      | 96.3"                             |
| Loading Height                        | 54"                      | 54.5"                             |
| Loading Reach                         | 33.5"                    | 35.5"                             |
| Transport Height                      | 60"                      |                                   |
| Swing Arc                             | 150°                     |                                   |
| Bucket Rotation                       | 180°                     |                                   |
| Stabilizer Spread – Up (transporting) | 51"                      |                                   |
| Stabilizer Spread – Down (operating)  | 77.5"                    |                                   |
| Relief Pressure                       | 2,000 psi                |                                   |
| Rated Pressure                        | 1,780 psi                |                                   |
| Bucket Digging Force                  | 2,025 lbs                | 2,200 lbs                         |
| Dipperstick Digging Force             | 1,150 lbs                | 1,180 lbs                         |
| 2-Cylinder Swing                      | –                        | –                                 |
| Swing Speed Control                   | –                        | –                                 |
| Bucket Widths                         | 9–16"                    |                                   |
| Bolt-On or Pin-On Teeth               | bolt-on                  |                                   |
| Thumb                                 | optional                 |                                   |
| Flip-Over Stabilizers                 | optional                 |                                   |
| Stabilizer Street Pads                | optional                 |                                   |
| PTO Pump Kit                          | –                        | –                                 |
| Clean-Up Bucket (ditching)            | –                        | –                                 |
| Cemetery Bucket                       | –                        | –                                 |
| Quick-Attach Bucket                   | –                        | –                                 |
| Multi-Position Bucket                 | –                        | –                                 |
| BH600 Backhoes                        |                          |                                   |

| BH70-X          | BH80-X                           | BH90-X            |
|-----------------|----------------------------------|-------------------|
| 18–40 hp        | 20–45 hp                         | 30–70 hp          |
| 84.5"           | 96.5"                            | 109"              |
| 61.25"          | 75.75"                           | 91"               |
| 113.5"          | 125.5"                           | 145"              |
| 66"             | 75.25"                           | 89"               |
| 45.25"          | 52.5"                            | 57"               |
| 74.75"          | 82.25"                           | 97"               |
|                 | 180°                             |                   |
|                 | 180°                             |                   |
|                 | 58.5"                            | 66"               |
|                 | 88.5"                            | 100"              |
| 2,030 psi       | 2,470 psi                        | 2,500 psi         |
| 2,030 psi       | 2,470 psi                        | 2,500 psi         |
| 3,110           | 3,780 lbs                        | 4,180 / 5,070 lbs |
| 2,000 lbs       | 2,480 lbs                        | 2,900 lbs         |
|                 | yes                              |                   |
| –               | yes                              |                   |
| 9–24"           | 9–36"                            | 12–36"            |
|                 | bolt-on                          | pin-on            |
| optional        | optional mechanical or hydraulic |                   |
|                 | standard                         |                   |
|                 | optional                         |                   |
|                 | optional                         |                   |
| –               | 36"                              |                   |
| –               | 36"                              |                   |
| –               | –                                | optional          |
| –               | –                                | standard          |
| BH70-X Backhoes | BH80-X Backhoes                  | BH90-X Backhoes   |

**Woods Equipment** A Blount International Company  
2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 woodsequipment.com



Warning! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2014 Woods Equipment Company. All rights reserved. WOODS, and the Woods logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.

