


## Technical Specifications

WEIGHT	UNIT	HR70C-9	HR110C-9	HR120C-9	HR140C-9	STANDARD EQUIPMENT
Operating weight CECE	kg (lb)	7,100(15,652)	11,200(24,691)	12,000(26,455)	13,900(30,644)	Canopy type with ROPS roll bar and waterproof seat
Axle load, front	kg (lb)	3,800 (8378)	6,100 (13,448)	6,900 (15,212)	8,000 (17,637)	Low-maintenance centre-pivot steering
Axle load, rear	kg (lb)	3,300 (7274)	5,100 (11,243)	5,100 (11,243)	5,900 (13,007)	Low-maintenance vibratory system with 2 amplitudes and frequencies
<b>COMPACTION PERFORMANCE</b>						
Linear drum load	kg/cm	22.40	29.00	32.80	38.00	No-spin rear axle
Amplitude high/low	mm	1.8 / 0.8	1.8 / 0.8	1.8 / 0.6	1.9 / 0.7	Four-stage hydrostatic drive and traction control at the drum (not for HR70C-9)
Frequency at high/low Amplitude	HZ	30 / 40	30 / 38	30 / 40	30 / 40	Both drives equipped with spring-loaded brake
Centrifugal force at high/low Ampl.	kN	120 / 90	220 / 150	240 / 140	280 / 180	Battery main switch
<b>DRUM</b>						
Drum width	mm (in)	1,700 (67)	2,100 (83)	2,100 (83)	2,100 (83)	Reverse gear alarm
Drum diameter	mm (in)	1,250 (50)	1,500 (59)	1,500 (59)	1,500 (59)	Adjustable driver's seat with armrest
Drum thickness	mm (in)	20 (.78)	25 (.98)	30 (1.18)	30 (1.18)	Adjustable steering column (not for canopy type)
<b>DRIVE / TRANSMISSION</b>						
Speed range	km/h	0-10	0-12.5	0-12.5	0-12.5	Radio
Angular movement	-	±12	±12	±12	±12	Emergency switch
Gradeability w/wo vibration	%	45 / 50	43 / 48	45 / 48	40 / 45	4 working headlights
Tires	-	16.9-24	23.1-26	23.1-26	23.1-26	Adjustable scraper
<b>ENGINE</b>						
Model	-	Perkins	Deutz	Deutz	Deutz	Hot water heating with fresh-air fan (only for cabin type)
Type	-	1104C-44	TCD 2012 L4	TCD 2012 L4	TCD 2012 L4	
Output	kW	61.5 (84 HP)	96 (130 HP)	96 (130 HP)	103 (140 HP)	
<b>TANK CAPACITIES</b>						
Fuel capacity	l (gal)	167 (44)	300 (80)	300 (80)	300 (80)	
Hydraulic oil capacity	l (gal)	68 (18)	106 (28)	106 (28)	106 (28)	
<b>DIMENSION</b>						
A Distance between axles	mm (in)	2,720 (107)	3,195 (126)	3,195 (126)	3,195 (126)	
B Width	mm (in)	1,850 (73)	2,270 (89)	2,270 (89)	2,270 (89)	
D Road clearance	mm (in)	375 (15)	490 (20)	490 (20)	490 (20)	
H Height	mm (in)	2,723 (107)	2,920 (115)	2,920 (115)	2,920 (115)	
H <sub>i</sub> Drum diameter	mm (in)	1,250 (50)	1,500 (59)	1,500 (59)	1,500 (59)	
L Length	mm (in)	5,032 (198)	5,757 (227)	5,757 (227)	5,757 (227)	
R Inside turning radius	mm (in)	3,900 (154)	4,860 (191)	4,860 (191)	4,860 (191)	
R <sub>i</sub> Outside turning radius	mm (in)	5,600 (220)	7,015 (276)	7,015 (276)	7,015 (276)	
W Width between tires	mm (in)	1,700 (67)	2,090 (82)	2,090 (82)	2,090 (82)	
W <sub>i</sub> Drum width	mm (in)	1,700 (67)	2,100 (83)	2,100 (83)	2,100 (83)	
α Angle of steering lock	mm	±30°	±30°	±30°	±30°	



PLEASE CONTACT

**HYUNDAI**  
HEAVY INDUSTRIES CO.,LTD.  
**CONSTRUCTION EQUIPMENT**

Head Office  
1000 BANGGEOJINSUNHWAN-DORO, DONG-GU, ULSAN, 682-792, KOREA  
TEL:(82)52-202-7722, 9807 FAX:(82)52-202-7720



www.hyundai-ce.com

2013. 10 Rev. 0

# HR 70/110/120/140c-9

HYUNDAI Compaction Rollers

MOVING YOU FURTHER

HYUNDAI HEAVY INDUSTRIES



\*Photo may include optional equipment.

**HYUNDAI**  
HEAVY INDUSTRIES CO.,LTD.





### Machine Walk-Around

#### Front chassis and drum

Front and rear scrapers remove material in case humid or cohesive soils are compacted.

As an optional accessory, a pad foot segment kit can be attached to the smooth drum and the drum unit itself can be easily dismantled without lifting gear.

Furthermore, the front frame and the drum provide additional static load.

#### HA control

Perfect adaptation to different types of soil.

A continuous tractive force adjustment automatically ensures maximum traction at the axle and the drum at all times.

#### Vibration

2-stage vibration system with a high compaction capacity. 2 frequencies and amplitudes for surface and deep compaction can be selected. Large exterior bearings greased in an oil bath ensure long inspection intervals.

#### Safety


Ideal circumferential visibility, even while going backwards, thanks to the inclined engine hood and a compact design.

The ROPS panoramic cabin is equipped with individually adjustable operating elements.

#### Engine

Water-cooled Diesel engines with large fuel tanks, high durability and low fuel consumption. A minimized noise level is attained by means of special engine bearings.





### Engines

Machine	HR70C-9	HR110C-9	HR120C-9	HR140C-9
Maker	-	Perkins	Deutz	Deutz
Type	-	1104C-44	TCD 2012 L4	TCD 2012 L4
Output	kW	61.5 (84 HP)	96 (130 HP)	96 (130 HP)
Model	-	Natural aspirated	Turbo charged	Turbo charged

### Rear axle & Articulated pendulum joint

#### ECO Mode Vibration drive


ECO speed enables the driver to reduce the rotational speed of the Diesel engine to the ideal engine torque and the pump for the hydrostatic drive of the vibration unit establishes the required rotational speed of the exciter shaft by adjusting the volumetric current.

#### No-Spin-Axle

Part of the standard equipment of all Hyundai compaction rollers. A permanent differential lock serves to attain optimal traction. The differential lock unlatches automatically whenever different wheel speeds are the result of frequent turns and winding terrain.

## Improved workability

Drum: Vibration system



The HYUNDAI vibration system consists of an exciter shaft with a rigid welded, off-center weight. In addition, there is a metallic housing containing a flexible mass which is brought into an off-center position by means of centrifugal force. The flexible mass consists of steel balls Ø 3mm (roller bearings) – inserted with graphite for dry lubrication. Changing the sense of rotation causes the position of center of gravity of the flexible mass to shift. Depending on the sense of rotation of the vibration shaft, the steel ball mass is either added to or subtracted from the rigid eccentric mass via the centrifugal force. This means that a sense of rotation adds an even greater eccentricity to the existing unbalanced mass.

#### High amplitude (for deep compaction)

By confronting it with the flexible mass, the opposite sense of rotation partly neutralizes the unbalanced mass created by the rigid eccentric mass.

#### Low amplitude (for surface compaction)

Depending on the rotational speed, different centrifugal forces can be attained. The entire kinetic force is composed of the vibrating mass of the drum and its rigidly attached components. Thus, the compaction capacity of the machine is established.



#### Articulated pendulum joint

The front and the rear end run in a single track. The articulated pendulum joint requires little maintenance, thanks to the Teflon® bearing seats. No lubrication points at the machines. The articulated pendulum is identical for all machines with operating weights ranging from 7 to 14 tons.





Door to be opened in the direction of motion (see our wheel loaders) Bended window panes which serve to avoid "pumping" of the windows during operation with vibration.



## Preference

### Operator Comfort

## Easy Maintenance



A spacious cabin with excellent circumferential visibility and a low construction height. Individually adjustable driver's seat. Thanks to the use of special cabin bearings, vibrations are damped. Specifically shaped screens serve to reduce the noise level.



### Sun screen

Roller style sun screens on the front window allow the operator to reduce glare and improve visibility.

### Console - Joystick

- 1 Engine idle speed
- 2 Half throttle 1200 rpm
- 3 Full throttle 2400 rpm
- 4 Vibration on /off
- 5 ECO Speed, without this optional feature, no vibration possible at reduced Diesel engine speed
- 6 Overmodulation hydraulic motor, rear (accelerating the hydraulic motor of the drum to the max. rotational speed, e.g. reverse motion on slopes)
- 7 Amplitude low / high / off
- 8 Overmodulation hydraulic motor, front (accelerating the hydraulic motor of the axle to the max. rotational speed, e.g. forward motion on slopes)



### Easy access

All maintenance components and aggregates are easily accessible, thanks to the wide opening of the engine hood.

The maintenance-free articulated joint and the low-maintenance vibration unit warrant a long service life and reduce maintenance expenditures.

### Easy air filter replacements



Adjustable scrapers



Easy accessible battery

