

	V-Max 2636	V-Max 3245	V-Max 3954
Capacity Bushels/cu.ft./gallons Without Height Extension With 9" Height Extension	260/181/1355 360/233/1745	320/227/1694 450/292/2189	390/272/2033 540/350/2617
Weight	6100#	7640#	8650#
Height W/14L-Tire	58 1/2"	58 1/2"	58 1/2"
W/9" Height Ext.	Add 9"	Add 9"	Add 9"
Opt. 16.5 Tire	Add 1 1/2"	Add 1 1/2"	Add 1 1/2"
	Single/Tandem	Tandem	Tandem
Overall Width W/14L Outside of tires	84 1/2"/96"	96"	96"
Opt 16.5 Tire	Add 7"	Add 7"	Add 7"
Tank Length	12'	15'	18'
Overall Length	18'5"	21'5"	24'5"
SPECIFICATIONS	V-Max 2636	V-Max 3245	V-Max 3954
Maximum Load w/spreader weight	12,000#/24,000#	24,000#	32,000#
	Single/Tandem	Tandem	Tandem
Roller Chain Drive	80-120	80-120	80-120
Constant Velocity PTO w/overrunning clutch	Standard 540 RPM	Standard 540 RPM	Standard 540 RPM
Axle	Single/Tandem	Tandem	Tandem
Hub Size	8 bolt-6000#	8 bolt-6,000#	8 bolt-8,000#
Spindle Size	2 3/4"	2 3/4"	3"
Frame Construction	8" Channel	8" Channel	8" Channel
Door Opening	27" x 42"	27" x 42"	27" x 42"
Tank Steel Copper Bearing	3/16"	3/16"	3/16"
Auger Diameter	20"	20"	20"
Auger Flighting Thickness	3/8" sectional	3/8" sectional	3/8" sectional
Drive Line Protection	Overrunning Slip Clutch	Overrunning Slip Clutch	Overrunning Slip Clutch
Expeller Speed	540 RPM	540 RPM	540 RPM
H.P. Requirements Min.	65	85	100
Light Package	Standard	Standard	Standard
Independent Lower Auger Shear Hub Sprockets	Standard	Standard	Standard
Options	V-Max 2636	V-Max 3245	V-Max 3954
Height Extension (Normal 9")	Optional	Optional	Optional
Height Extension (4"-6")	Optional	Optional	Optional
High Volume Poultry Extension	Optional	Optional	Optional
3rd Auger (for solid material)	Optional	Optional	Optional
Auto Oiler	Optional	Optional	Optional
1000 RPM PTO	Optional	Optional	Optional
Hydraulic Lid	Optional	Optional	Optional
Truck Mount	Optional	Optional	Optional