

Model	Style	Capacity	Tread Width	Spindle Size	Heavy Duty Hubs	Frame Design	Weight	Overall Length	Bed Length	Overall Width	Bed Width	Stake Spacing	Bed Height	Adj. Clevis Hitch	Options	Surge Brakes	Swivel Clevis Hitch	4" Riser Package	Various Tire Sizes
XT1600 162	Tandem O-Beam	32,000 lbs.	81.25" w/16.5L 81.4" w/425/65 85" w/11Rx22.5	3"	8 Bolt 8000# at 10 MPH	3x6x1/4" Tubing	3145# w/riser w/425/65x22.5	20' 8.5"	13' 7"	100.5" w/ 16.5L x 16.1 98.25" w/ 425/65x22.5	42"	42"	32" w/ 14Lx16.1 w/o riser 38 1/2" w/425/65x22.5 w/riser	Standard		N/A	N/A	Optional Req. for 16.5L, 19L or 425/65	See Dealer
XT1600-L 202	Tandem O-Beam	32,000 lbs.	81.25" w/16.5L 81.4" w/425/65 85" w/11Rx22.5	3"	8 Bolt 8000# at 10 MPH	3x6x1/4" Tubing	3240# w/riser w/425/65x22.5	24'	16' 10.5"	100.5" w/ 16.5L x 16.1 98.25" w/ 425/65x22.5	42"	42"	32" w/ 14Lx16.1 w/o riser 38 1/2" w/425/65x22.5 w/riser	Standard		N/A	N/A	Optional Req. for 16.5L, 19L or 425/65	See Dealer
XT2200+ 216	Tandem O-Beam	44,000 lbs.	82" w/21.5Lx16.1 82" w/425/65	3.5"	10 Bolt 15,000# at 10 MPH	4x8x1/4" Tubing	3680# w/21.5Lx16.1	25' 5.5"	18'	102.5" w/ 21.5L x 16.1 98.5" w/ 425/65x22.5	42"	42" or 33.5" (Opt. or Std)	44" w/ 21.5Lx16.1 43 1/4" w/425/65x22.5	Standard		Optional	Optional	N/A	See Dealer
XT2200+ 240	Tandem O-Beam	44,000 lbs.	82" w/21.5Lx16.1 82" w/425/65	3.5"	10 Bolt 15,000# at 10 MPH	4x8x1/4" Tubing	3810# w/21.5Lx16.1	27' 5.5"	20'	102.5" w/ 21.5L x 16.1 98.5" w/ 425/65x22.5	42"	42" or 33.5" (Opt. or Std)	44" w/ 21.5Lx16.1 43 1/4" w/425/65x22.5	Standard		Optional	Optional	N/A	See Dealer
XT2200+ 264	Tandem O-Beam	44,000 lbs.	82" w/21.5Lx16.1 82" w/425/65	3.5"	10 Bolt 15,000# at 10 MPH	4x8x1/4" Tubing	3950# w/21.5Lx16.1	30' 5.5"	22'	102.5" w/ 21.5L x 16.1 98.5" w/ 425/65x22.5	42"	42" or 33.5" (Opt. or Std)	44" w/ 21.5Lx16.1 43 1/4" w/425/65x22.5	Standard		Optional	Optional	N/A	See Dealer
XT2200+ 280	Tandem O-Beam	44,000 lbs.	82" w/21.5Lx16.1 82" w/425/65	3.5"	10 Bolt 15,000# at 10 MPH	4x8x1/4" Tubing	4705# w/21.5L x16.1	31' 7"	23' 4"	102.5" w/ 21.5L x 16.1 98.5" w/ 425/65x22.5	42"	42" or 33.5" (Opt. or Std)	44" w/ 21.5Lx16.1 43 1/4" w/425/65x22.5	Standard		Optional	Optional	N/A	See Dealer