

	Capacity	Weight w/ tires	Tread Width	Spindle Diameter	Hub Size	Bolster Size / Height	Reach Size	Wheel Base	Quick Hitch Pole	Pole Adj.	Hyd. Surge Brakes
<b>Single Axle</b>											
<b>X0804W</b>	8 ton	900# w/ 11L	90"	1 3/4"	6 bolt 3560#	4" x 8" tube 27" w/11L	4" wide x 88" L Opt. 112"	93" to 141"	Standard w/ spring asst.	82"-100"	N/A
<b>X1004</b>	10 ton	1025# w/12.5L	76"	2"	6 Bolt 4570#	4" x 8" tube 28" w/12.5L	4" wide x 88" L Opt. 112"	93" to 141"	Standard w/ spring asst.	82"-100"	N/A
<b>SRX1304</b>	13 ton	1,780# w/14L	83"	2 3/4"	8 Bolt 6000#	4" x 8" tube 31" w/14L	5" Wide x 112"L opt. 136"	117" to 165"	Standard w/ spring asst.	97"-115"	Optional
<b>DRX1604</b>	16 ton	2,085 w/16.5L	88"	2 3/4"	8 Bolt 8000#	4" x 8" tube 32" w/16.5L	(x2) 4" wide x 112"L opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional
<b>DRX1704</b>	17 ton	2,770# w/trk tires	85"	3"	8 Bolt 8000#	4" x 8" tube 34" w/Trk tires	(x2) 4" wide x 112"L opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional
<b>X2004</b>	20 ton	3,250# w/trk tires	86.5"	3.5"	10 Bolt 15,000#	4" x 10" tube 36.75" w/Trk Tires	5" Wide x 112"L opt. 136"	117" to 165"	Standard w/ spring asst.	84" - 110"	Optional
<b>Tandem Axle</b>											
<b>X1206</b>	12 ton	1,525# w/12.5L	76"	2"	6 Bolt 4570#	4" x 8" tube 28" w/12.5L	4" wide x 88" L Opt. 112"	93" to 141"	Standard w/ spring asst.	97"-115"	N/A
<b>SRX1506</b>	15 ton	2,415# w/14L	83"	2 3/4"	8 Bolt 6000#	4" x 8" tube 31" w/14L	5" Wide x 112"L opt. 136"	117" to 165"	Standard w/ spring asst.	97"-115"	Optional
<b>DRX1906</b>	19 ton	2,890# w/16.5L	88"	2 3/4"	8 Bolt 8000#	4" x 8" tube 32" w/16.5L	(x2) 4" wide x 112"L opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional
<b>DRX2206</b>	22 ton	4,065# w/ trk tires	85"	3"	8 Bolt 8000#	4" x 8" tube 34" w/Trk tires	(x2) 4" wide x 112"L opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional